

# Connecting cable NEBC-R3G4-ES-1-S-R3G4-ET

Part number: 8040455

FESTO



 General operating condition

## Data sheet

Feature	Value
Approval	c UL us - Listed (Oil)
Certificate issuing authority	UL E520706
Cable designation	With inscription label holder
Frequency of connection	750
Product weight	89.5 g
Electrical connection 1, function	Field device side
Electrical connection 1, design	Square
Electrical connection 1, connection type	Plug
Electrical connection 1, cable outlet	Straight
Electrical connection 1, connector system	RJ45 to IEC 60603-7-3
Electrical connection 1, number of connections/cores	8
Electrical connection 1, used connections/cores	4
Electrical connection 1, type of mounting	Snap-locking
Electrical connection 1, compatible type of mounting	Compatible with latching lock
Electrical connection 1, connection pattern	00995653
Electrical connection 2, function	Control side
Electrical connection 2, design	Square
Electrical connection 2, connection type	Plug
Electrical connection 2, cable outlet	Straight
Electrical connection 2, connector system	RJ45 to IEC 60603-7-3
Electrical connection 2, number of connections/cores	8
Electrical connection 2, used connections/cores	4
electrical connection 2, type of mounting	Snap-locking
Electrical connection 2, compatible type of mounting	Compatible with latching lock
Electrical connection 2, connection pattern	00995653
Operational voltage range DC	0 V ... 60 V
Note on operational voltage range DC	0 - 30 V for UL applications
Permissible current load	1.5 A
Immunity to surge	0.8 kV
Shielding	Yes
Transmission characteristics	In accordance with category 5, ISO/IEC 11801, class D
Cable length	1 m
Cable characteristic	Suitable for energy chains
Test conditions cable	Bending strength: to Festo standard Test conditions on request Energy chain: > 2 million cycles, bending radius 100 mm

Feature	Value
Bending radius, fixed cable	≥40 mm
Bending radius, moving cable	≥100 mm
Cable diameter	6.7 mm
Cable diameter tolerance	± 0.3 mm
Cable structure	4 x 0.34 mm <sup>2</sup>
Nominal cross section conductor	0.34 mm <sup>2</sup>
Conductor nominal cross section	AWG22
Degree of protection	IP20
Note on degree of protection	In mounted state
Special characteristics	Oil-resistant
Vibration resistance	Prüfbedingungen nach Anfrage
Shock resistance	Prüfbedingungen nach Anfrage
Ambient temperature	-25 °C ... 80 °C
Ambient temperature with moving cable	-20 °C ... 60 °C
Storage temperature	-25 °C ... 80 °C
Relative air humidity	25 - 75%
Overvoltage category	II
CE mark (see declaration of conformity)	In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
LABS (PWIS) conformity	VDMA24364-B2-L
Note on materials	RoHS compliant
Pollution degree	3
Note on the contamination level	In mounted state
Corrosion resistance class CRC	1 - Low corrosion stress
Material cable sheath	TPE-U(PUR)
Cable sheath colour	Green
Material housing	Brass, nickel-plated Process automation
Housing colour	Black
Material electrical contact	Brass Gold-plated
Material insulating sheath	Packaging unit