

Linear drive DGPL-25-1000-PPV-A-B-KF

Part number: 526652

FESTO



 General operating condition

Data sheet

| Feature | Value |
|--|--|
| Stroke | 1000 mm |
| Piston diameter | 25 mm |
| Cushioning | Pneumatic cushioning, adjustable at both ends Shock absorber, hard characteristic curve |
| Mounting position | optional |
| Guide | Recirculating ball bearing guide |
| Coupling design | Positive-locking (slot) |
| Position detection | Via proximity switch |
| Symbol | 00991254 |
| Operating pressure | 0.2 MPa ... 0.8 MPa |
| Operating pressure | 2 bar ... 8 bar |
| Mode of operation | Double-acting |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:-:-] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -10 °C ... 60 °C |
| Cushioning length | 18 mm |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke | 295 N |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 295 N |
| Moving mass | 600 g |
| Moving mass for 0 mm stroke | 600 g |
| Additional moving mass per 10 mm stroke | 53 g |
| Basic weight for 0 mm stroke | 1520 g |
| alternative connections | See product drawing |
| Pneumatic connection | G1/8 |
| Material cover | Die-cast aluminium Coated |
| Material seals | NBR TPE-U(PU) |
| Material housing | Anodised |