

### **Commissioning CANopen device CMMP-AS with Schneider Electric PLC M340**

This document describes exemplarily how to set the parameters in the Schneider Electric PLC M340 with CANopen-Master to establish the CANopen-communication with a servo motor controller of type CMMP-AS-M3, without much details.

CMMP-AS-...-M3  
CMMP-AS-...-M0

Title ..... Commissioning CANopen device CMMP-AS with PLC M340  
Version ..... 1.10  
Document no. .... 100020  
Original ..... en  
Author ..... Festo  
  
Last saved ..... 31.03.2015

## Copyright Notice

This documentation is the intellectual property of Festo AG & Co. KG, which also has the exclusive copyright. Any modification of the content, duplication or reprinting of this documentation as well as distribution to third parties can only be made with the express consent of Festo AG & Co. KG.

Festo AG & Co KG reserves the right to make modifications to this document in whole or in part. All brand and product names are trademarks or registered trademarks of their respective owners.

## Legal Notice

Hardware, software, operating systems and drivers may only be used for the applications described and only in conjunction with components recommended by Festo AG & Co. KG.

Festo AG & Co. KG does not accept any liability for damages arising from the use of any incorrect or incomplete information contained in this documentation or any information missing therefrom.

Defects resulting from the improper handling of devices and modules are excluded from the warranty.

The data and information specified in this document should not be used for the implementation of safety functions relating to the protection of personnel and machinery.

No liability is accepted for claims for damages arising from a failure or functional defect. In other respects, the regulations with regard to liability from the terms and conditions of delivery, payment and use of software of Festo AG & Co. KG, which can be found at [www.festo.com](http://www.festo.com) and can be supplied on request, shall apply.

All data contained in this document do not represent guaranteed specifications, particularly with regard to functionality, condition or quality, in the legal sense.

The information in this document serves only as basic information for the implementation of a specific, hypothetical application and is in no way intended as a substitute for the operating instructions of the respective manufacturers and the design and testing of the respective application by the user.

The operating instructions for Festo products can be found at [www.festo.com](http://www.festo.com).

Users of this document (application note) must verify that all functions described here also work correctly in the application. By reading this document and adhering to the specifications contained therein, users are also solely responsible for their own application.

## Table of contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Components/Software used .....</b>  | <b>4</b>  |
| 1.1      | Introduction .....   | 5         |
| <b>2</b> | <b>Instruction .....</b>   | <b>6</b>  |
| 2.1      | Download CANopen EDS.....  | 6         |
| 2.2      | Install the EDS-File in the programming software Unity Pro XL V7.0 .....         | 6         |
| 2.3      | Implementing of the CANopen-Device “motor controller” CMMP-AS.....               | 8         |
| 2.4      | Setting CAN-parameters for the CANopen device CMMP-AS .....                      | 10        |
| 2.5      | Setting the communication parameters for PDO 1 and 2 (transmit and receive)..... | 12        |
| 2.6      | Error control tab: Monitoring of network participants .....                      | 14        |
| 2.7      | Bootup procedure configuration .....   | 16        |
| 2.8      | Object Dictionary tab .....  | 17        |
| 2.9      | Parameterizing the CANopen-Master (Master Configuration).....                    | 18        |
| 2.10     | Bus Parameters .....   | 19        |
| 2.11     | EMCY_Emergency Message .....   | 20        |
| 2.12     | Checklist .....  | 21        |
| <b>3</b> | <b>Appendix.....</b>   | <b>22</b> |
| 3.1      | 6.6 Object 1F84h – Device type identification.....                               | 22        |
| 3.2      | 6.7 Object 1F85h – Vendor identification.....                                    | 22        |
| 3.3      | 6.8 Object 1F86h – Product code.....   | 22        |
| 3.4      | 6.9 Object 1F87h – Revision number .....   | 23        |
| 3.5      | 6.10 Object 1F88h – Serial number .....  | 23        |

## 1 Components/Software used


| Type/Name  | Version Software/Firmware | Date of manufacture |
|--|---------------------------|---------------------|
| CMMP-AS-C2-3A-M3   | 4.0.1501.2.1              | HW 4.7              |
| FCT ...Festo Configuration Tool                            | PlugIn CMMP-AS V2.4.1.4   | ---                 |
| Schneider PLC Modicon M340<br>CPU 340-20 Ethernet CANopen2 | 2.50                      | ---                 |
| Unity Pro XL V7.0  | V7.0 120823C              | ---                 |

Table 1.1: 1 Components/Software used


## 1.1 Introduction

This document describes exemplarily how to set the parameters in the Schneider Electric PLC M340 with CANopen-Master to establish the CANopen-communication with a servo motor controller of type CMMP-AS-M3. It is a step-by-step instruction without much detail. It is as well possible, that not every step is mentioned and described. Just to have a quick information source to get run the fieldbus communication. For more information you can consult the online help of the programming software Unity Pro XL from Schneider Electric.

PLC with CANopen-Master from Schneider Electric of type Medicon M340  
(CPU 340-20, Ethernet TCP/IP, CANopen master)



The programming software is Unity Pro XL V7.0 from Schneider Electric:



## 2 Instruction


### 2.1 Download CANopen EDS

Download the relevant CANopen EDS-files (Device Description files) for the CANopen device 'motor controller' from the Support Portal on the Festo internet homepage. Please select the belonging file to your motor controller (type) and the used communication protocol FHPP or CiA402.

|  |            |                              |
|--|------------|------------------------------|
| <b>CANopen EDS</b>   | 2.9        | → Device Description Files   |
| <input type="checkbox"/> EDS files for CMMP-AS M3 with CAN (CiA 402 and FHPP)  | 12/08/2014 | → File and language versions |
| ★★★★★  |            |                              |
| <b>Supported systems:</b>  |            |                              |
| <ul style="list-style-type: none"> <li>• Motor controller CMMP-AS-C10-11A-P3-M3 (1501328)</li> <li>• Motor controller CMMP-AS-C10-11A-P3-M3-C1 (2106335)</li> <li>• Motor controller CMMP-AS-C2-3A-M3 (1501325)</li> <li>• Motor controller CMMP-AS-C2-3A-M3-C1 (2106332)</li> <li>• Motor controller CMMP-AS-C5-11A-P3-M3 (1501327)</li> <li>• Motor controller CMMP-AS-C5-11A-P3-M3-C1 (2106334)</li> <li>• Motor controller CMMP-AS-C5-3A-M3 (1501326)</li> <li>• Motor controller CMMP-AS-C5-3A-M3-C1 (2106333)</li> </ul> |            |                              |

### 2.2 Install the EDS-File in the programming software Unity Pro XL V7.0


#### 1. Start the Hardware Catalog Manager



2. Add an new device by clicking right mouse button into the chapter 'Third party products'.

Select your relevant EDS-File from the previous downloaded and stored place on your computer drive.


Click 'Build Catalog' and then the process is starting to import the EDS-file. The imported EDS-file (e.g. CMMP\_AS\_C2\_3A\_M3\_FHPP) is now available in the programming software Unity Pro XL V7.0




3. Close the Hardware Catalog Manager.

## 2.3 Implementing of the CANopen-Device “motor controller” CMMP-AS

1. Click double onto the CANopen-Master in the project tree:




2. Click double into the empty rectangle:






3. Select your CANopen-device in the chapter 'Third party products' and set the needed node ID in the field 'Topological Address [1..63]':




4. Finally the CANopen-Device is implemented:



## 2.4 Setting CAN-parameters for the CANopen device CMMP-AS

1. Click double into the CANopen device in the project tree (1: CANopen drop) or in the graphical symbol. Then you open the needed place for parameterizing the CAN-settings for the CANopen device (CANopen node):



- Please set the number of PDO's for 'receive' and 'transmit'. Depending on your settings in FCT (FCT...Festo Configuration Tool) you need different numbers of PDO's (FHPP, FHPP and FPC, FHPP and FPC and FHPP+). In the following example we are using FHPP and FPC, which means 16 Byte IO resulting into two TxPDO and two RxPDO.

Please untick in the tab 'PDO' the PDO's 3 and 4 for Transmit and Receive:

CanOpen Info Set (CMMP-AS-C2-3A\_CAN\_FHPP.EDS)

CMMP\_AS\_C2\_3A\_F  
Channel 0

**PDO** | Error control | Bootup | Object Dictionary | Configuration

Transmit (%I) ☐ Display only active PDO

| PDO  | Tr.Type | InhibitTime | Event Tim... | Symbol | Topo.Addr.      | %M.. | COBID  | Index   |
|--|---------|-------------|--------------|--------|-----------------|------|--------|---------|
| <input checked="" type="checkbox"/> PDO 1 (Static)                 | 255     | 0           |              |        |                 |      | 16#181 |         |
| SCON   |         |             |              |        | %I\3.10.0.0.48  |      |        | 3020:00 |
| SPOS   |         |             |              |        | %I\3.10.0.0.49  |      |        | 3021:00 |
| REC_NR/SDIR  |         |             |              |        | %I\3.10.0.0.50  |      |        | 3022:00 |
| RSB/ACT_VAL1   |         |             |              |        | %I\3.10.0.0.51  |      |        | 3023:00 |
| ACT_POS/AC...  |         |             |              |        | %ID\3.10.0.0.38 |      |        | 3024:00 |
| <input checked="" type="checkbox"/> PDO 2 (Static)                 | 255     | 0           |              |        |                 |      | 16#281 |         |
| RES  |         |             |              |        | %I\3.10.0.0.52  |      |        | 3030:00 |
| SUBINDEX   |         |             |              |        | %I\3.10.0.0.53  |      |        | 3031:00 |
| RESPCODE_...   |         |             |              |        | %I\3.10.0.0.54  |      |        | 3032:00 |
| PARAVAL  |         |             |              |        | %ID\3.10.0.0.40 |      |        | 3033:00 |
| <input type="checkbox"/> <input checked="" type="checkbox"/> PDO 3 | 255     | 0           |              |        |                 |      | 16#381 |         |
| <input type="checkbox"/> <input checked="" type="checkbox"/> PDO 4 | 255     | 0           |              |        |                 |      | 16#481 |         |

Receive (%Q) ☐ Display only active PDO


| PDO  | Tr.Type | InhibitTime | Event Tim... | Symbol | Topo.Addr.      | %M.. | COBID  | Index   |
|--|---------|-------------|--------------|--------|-----------------|------|--------|---------|
| <input checked="" type="checkbox"/> PDO 1 (Static)                 | 255     |             |              |        |                 |      | 16#201 |         |
| CCON   |         |             |              |        | %Q\3.10.0.0.54  |      |        | 3000:00 |
| CPOS   |         |             |              |        | %Q\3.10.0.0.55  |      |        | 3001:00 |
| REC_NR/CDIR  |         |             |              |        | %Q\3.10.0.0.56  |      |        | 3002:00 |
| RES/DEM_VA...  |         |             |              |        | %Q\3.10.0.0.57  |      |        | 3003:00 |
| RES/DEM_VA...  |         |             |              |        | %QD\3.10.0.0.42 |      |        | 3004:00 |
| <input checked="" type="checkbox"/> PDO 2 (Static)                 | 255     |             |              |        |                 |      | 16#301 |         |
| RES  |         |             |              |        | %Q\3.10.0.0.58  |      |        | 3010:00 |
| SUBINDEX   |         |             |              |        | %Q\3.10.0.0.59  |      |        | 3011:00 |
| REQCODE_P...   |         |             |              |        | %Q\3.10.0.0.60  |      |        | 3012:00 |
| PARAVAL  |         |             |              |        | %QD\3.10.0.0.44 |      |        | 3013:00 |
| <input type="checkbox"/> <input checked="" type="checkbox"/> PDO 3 | 255     |             |              |        |                 |      | 16#401 |         |
| <input type="checkbox"/> <input checked="" type="checkbox"/> PDO 4 | 255     |             |              |        |                 |      | 16#501 |         |

## 2.5 Setting the communication parameters for PDO 1 and 2 (transmit and receive)

For motion applications we recommend to change the PDO transmission type no. 255\_ asynchronous (application event is defined in the device profile) to type no. 1-240<sup>1</sup>\_cyclic\_synchronous (<sup>1</sup> the type indicates the number of SYNC objects between two PDO transmissions).

- Click double on each Tr-Type...Transmission Type for changing it to 'Synchronous cyclic (1)'.

The Inhibit Time for transmit PDO



CanOpen Info Set (CMMP-AS-C2-3A\_CAN\_FHPP.EDS)

CMMP\_AS\_C2\_3A\_FHPP  
Channel 0

**Transmit (%I)** ☐ Display only active PDO

| PDO                     | Tr.Type | InhibitTime | Event Tim... | Symbol | Topo.Addr.      | %M... | COBID  | Index   |
|-------------------------|---------|-------------|--------------|--------|-----------------|-------|--------|---------|
| ✓ <b>PDO 1 (Static)</b> | 1       | 0           |              |        |                 |       | 16#181 |         |
| SCON                    |         |             |              |        | %dW13.N0.0.0.48 |       |        | 3020:00 |
| SPOS                    |         |             |              |        | %dW13.N0.0.0.49 |       |        | 3021:00 |
| REC_NR/SDIR             |         |             |              |        | %dW13.N0.0.0.50 |       |        | 3022:00 |
| RSB/ACT_VAL1            |         |             |              |        | %dW13.N0.0.0.51 |       |        | 3023:00 |
| ACT_POS/AC...           |         |             |              |        | %dD13.N0.0.0.38 |       |        | 3024:00 |
| ✓ <b>PDO 2 (Static)</b> | 1       | 0           |              |        |                 |       | 16#281 |         |
| RES                     |         |             |              |        | %dW13.N0.0.0.52 |       |        | 3030:00 |
| SUBINDEX                |         |             |              |        | %dW13.N0.0.0.53 |       |        | 3031:00 |
| RESPCODE_...            |         |             |              |        | %dW13.N0.0.0.54 |       |        | 3032:00 |
| PARAVAL                 |         |             |              |        | %dD13.N0.0.0.40 |       |        | 3033:00 |
| ✗ PDO 3                 | 255     | 0           |              |        |                 |       | 16#381 |         |
| ✗ PDO 4                 | 255     | 0           |              |        |                 |       | 16#481 |         |

**Receive (%Q)** ☐ Display only active PDO

| PDO                     | Tr.Type | InhibitTime | Event Tim... | Symbol | Topo.Addr.      | %M... | COBID  | Index   |
|-------------------------|---------|-------------|--------------|--------|-----------------|-------|--------|---------|
| ✓ <b>PDO 1 (Static)</b> | 1       |             |              |        |                 |       | 16#201 |         |
| CCON                    |         |             |              |        | %QW13.N0.0.0.54 |       |        | 3000:00 |
| CPOS                    |         |             |              |        | %QW13.N0.0.0.55 |       |        | 3001:00 |
| REC_NR/CDIR             |         |             |              |        | %QW13.N0.0.0.56 |       |        | 3002:00 |
| RESIDEM_VA...           |         |             |              |        | %QW13.N0.0.0.57 |       |        | 3003:00 |
| RESIDEM_VA...           |         |             |              |        | %QD13.N0.0.0.42 |       |        | 3004:00 |
| ✓ <b>PDO 2 (Static)</b> | 1       |             |              |        |                 |       | 16#301 |         |
| RES                     |         |             |              |        | %QW13.N0.0.0.58 |       |        | 3010:00 |
| SUBINDEX                |         |             |              |        | %QW13.N0.0.0.59 |       |        | 3011:00 |
| REQCODE_P...            |         |             |              |        | %QW13.N0.0.0.60 |       |        | 3012:00 |
| PARAVAL                 |         |             |              |        | %QD13.N0.0.0.44 |       |        | 3013:00 |
| ✗ PDO 3                 | 255     |             |              |        |                 |       | 16#401 |         |
| ✗ PDO 4                 | 255     |             |              |        |                 |       | 16#501 |         |

- Display only active PDO's to see the result

CanOpen Info Set (CMMP-AS-C2-3A\_CAN\_FHPP.EDS)

CMMP\_AS\_C2\_3A\_FHPP  
Channel 0

**Transmit (%I)** ☒ Display only active PDO

| PDO                     | Tr.Type | InhibitTime | Event Tim... | Symbol | Topo.Addr.      | %M... | COBID  | Index   |
|-------------------------|---------|-------------|--------------|--------|-----------------|-------|--------|---------|
| ✓ <b>PDO 1 (Static)</b> | 1       | 0           |              |        |                 |       | 16#181 |         |
| SCON                    |         |             |              |        | %dW13.N0.0.0.48 |       |        | 3020:00 |
| SPOS                    |         |             |              |        | %dW13.N0.0.0.49 |       |        | 3021:00 |
| REC_NR/SDIR             |         |             |              |        | %dW13.N0.0.0.50 |       |        | 3022:00 |
| RSB/ACT_VAL1            |         |             |              |        | %dW13.N0.0.0.51 |       |        | 3023:00 |
| ACT_POS/AC...           |         |             |              |        | %dD13.N0.0.0.38 |       |        | 3024:00 |
| ✓ <b>PDO 2 (Static)</b> | 1       | 0           |              |        |                 |       | 16#281 |         |
| RES                     |         |             |              |        | %dW13.N0.0.0.52 |       |        | 3030:00 |
| SUBINDEX                |         |             |              |        | %dW13.N0.0.0.53 |       |        | 3031:00 |
| RESPCODE_...            |         |             |              |        | %dW13.N0.0.0.54 |       |        | 3032:00 |
| PARAVAL                 |         |             |              |        | %dD13.N0.0.0.40 |       |        | 3033:00 |

**Receive (%Q)** ☒ Display only active PDO

| PDO                     | Tr.Type | InhibitTime | Event Tim... | Symbol | Topo.Addr.      | %M... | COBID  | Index   |
|-------------------------|---------|-------------|--------------|--------|-----------------|-------|--------|---------|
| ✓ <b>PDO 1 (Static)</b> | 1       |             |              |        |                 |       | 16#201 |         |
| CCON                    |         |             |              |        | %QW13.N0.0.0.54 |       |        | 3000:00 |
| CPOS                    |         |             |              |        | %QW13.N0.0.0.55 |       |        | 3001:00 |
| REC_NR/CDIR             |         |             |              |        | %QW13.N0.0.0.56 |       |        | 3002:00 |
| RESIDEM_VA...           |         |             |              |        | %QW13.N0.0.0.57 |       |        | 3003:00 |
| RESIDEM_VA...           |         |             |              |        | %QD13.N0.0.0.42 |       |        | 3004:00 |
| ✓ <b>PDO 2 (Static)</b> | 1       |             |              |        |                 |       | 16#301 |         |
| RES                     |         |             |              |        | %QW13.N0.0.0.58 |       |        | 3010:00 |
| SUBINDEX                |         |             |              |        | %QW13.N0.0.0.59 |       |        | 3011:00 |
| REQCODE_P...            |         |             |              |        | %QW13.N0.0.0.60 |       |        | 3012:00 |
| PARAVAL                 |         |             |              |        | %QD13.N0.0.0.44 |       |        | 3013:00 |

## 2.6 Error control tab: Monitoring of network participants

The Heartbeat mechanism consists of sending cyclical presence messages generated by a Heartbeat Producer. A Heartbeat transmitter (producer) sends messages recurringly. The sending time is configured with the Node Heartbeat Producer Time Value. One or several elements connected to the network receive this message. The Heartbeat consumer surveys the Heartbeat message reception. The default value of consumer time is set to  $(1.5 * \text{Producer Heartbeat Time})$ . If its duration exceeds the Heartbeat Consumer Time ( $1.5 * \text{Producer Heartbeat Time}$ ), a Heartbeat event is created and the device is in default.

The Error control tab for CANopen slave modules allows you to configure the monitoring.


The Festo motor controller CMMP-AS supports the mechanism Node Guarding Protocol and Heartbeat Protocol.



### Note

**For devices which support Heartbeat and Node Guarding, the only choice in Unity Pro is the Heartbeat mechanism.**

- In case of using Heartbeat, please set the producer time.




- CAN-Trace with 200 ms Heartbeat from motor controller CMMP-AS (COB-ID 0x701)

The Master (COB-ID 0x77F) can send Heartbeat messages to the slaves. The Master Heartbeat producer time is set at 200 ms and is not modifiable.

| Trace 1 - Running   |      |       |                         |                    |  |                         |  |
|---|------|-------|-------------------------|--------------------|--|-------------------------|--|
| <span>Relative ms</span> <span>Fixed</span> <span>Bus load: 5,71% Peak: 5,93% Ave: 5,62%</span> |      |       |                         |                    |  |                         |  |
| Time  | Cnt  | ID    | Msg Type                | Node               | Details                                    | Raw Message             |  |
| 00000199,748  | 87   | 0x77F | Node Guarding/Heartbeat | [0x7F (127)] PLC   | Operational                                | 05                      |  |
| 00000200,473  | 86   | 0x701 | Node Guarding/Heartbeat | [0x01 (1)] CMMP-AS | Operational                                | 05                      |  |
| 00000009,983  | 1736 | 0x301 | Default: PDO            |                    | Default: RPDO 2 of Node [0x01 (1)] CMMP-AS | 00 00 00 00 00 00 00 00 |  |
| 00000010,025  | 1736 | 0x281 | Default: PDO            |                    | Default: TPDO 2 of Node [0x01 (1)] CMMP-AS | 00 00 00 00 00 00 00 00 |  |
| 00000009,983  | 1736 | 0x201 | Default: PDO            |                    | Default: RPDO 1 of Node [0x01 (1)] CMMP-AS | 00 00 00 00 00 00 00 00 |  |
| 00000009,983  | 1736 | 0x181 | Default: PDO            |                    | Default: TPDO 1 of Node [0x01 (1)] CMMP-AS | 10 00 00 00 F8 FF FF FF |  |
| 00000009,983  | 1736 | 0x080 | SYNC Sync               |                    |  |                         |  |

- You can switch off the Heartbeat mechanism when you set the node heartbeat producer time to 0.




### 1. CAN-Trace with 0 ms Heartbeat: Heartbeat of motor controller CMMP-AS is switched off

| Trace 1 - Running   |      |       |                         |                  |  |                         |  |
|---|------|-------|-------------------------|------------------|--|-------------------------|--|
| <span>Relative ms</span> <span>Fixed</span> <span>Bus load: 5,68% Peak: 5,94% Ave: 5,60%</span> |      |       |                         |                  |  |                         |  |
| Time  | Cnt  | ID    | Msg Type                | Node             | Details                                    | Raw Message             |  |
| 00000199,923  | 77   | 0x77F | Node Guarding/Heartbeat | [0x7F (127)] PLC | Operational                                | 05                      |  |
| 00000009,983  | 1544 | 0x301 | Default: PDO            |                  | Default: RPDO 2 of Node [0x01 (1)] CMMP-AS | 00 00 00 00 00 00 00 00 |  |
| 00000009,983  | 1544 | 0x281 | Default: PDO            |                  | Default: TPDO 2 of Node [0x01 (1)] CMMP-AS | 00 00 00 00 00 00 00 00 |  |
| 00000009,983  | 1544 | 0x201 | Default: PDO            |                  | Default: RPDO 1 of Node [0x01 (1)] CMMP-AS | 00 00 00 00 00 00 00 00 |  |
| 00000009,983  | 1544 | 0x181 | Default: PDO            |                  | Default: TPDO 1 of Node [0x01 (1)] CMMP-AS | 10 00 00 00 F8 FF FF FF |  |
| 00000009,984  | 1544 | 0x080 | SYNC Sync               |                  |  |                         |  |

## 2.7 Bootup procedure configuration

The Bootup tab allows you to configure the Bootup procedure.

Please follow the needed settings:



The type of restore: Please keep the default option 'No Restore' enabled

The type of reset: You can use the default setting 'Reset node'. 'Reset communication parameters' is as well possible

Check node: Both settings are possible. When checked, then content of 0x1000 and 0x1018:xx in the motor controller must be equal to EDS-file. For more details, please see appendix

Download Configuration: Unchecked

Start: Please keep option checked (default value), the CANopen master starts automatically the device after the bootup procedure.



## 2.8 Object Dictionary tab

Area Filter: 0x1000...0x11FF (communication profile area)

Status Filter: Configured

Uncheck the consumer heartbeat time:

CanOpen Info Set (CMMP-AS-C2-3A\_CAN\_FHPP.EDS)

CMMP\_AS\_C2\_3A\_FHPP  
Channel 0

Area Filter: [ 0x1000 ... 0x11FF ] Status Filter: Configured

| Index/Subindex                                | Name                      | Current Value | Default Value | Access | Type |
|---|---------------------------|---------------|---------------|--------|------|
| 0x1016  | consumer_heartbeat_time   |               |               |        |      |
| <input type="checkbox"/> 0x1016:01            | consumer_heartbeat_time_1 | 0x007F012C    | 0x00          | R/W    | UI32 |
| 0x1017  | producer_heartbeat_time   |               |               |        |      |
| <input checked="" type="checkbox"/> 0x1017:00 | producer_heartbeat_time   | 200           | 0x00          | R/W    | UI16 |



### Caution

If not, then the boot-up-sequence (initializing) is in an endless-loop. The CANopen-Master is getting a SDO Abort by trying to write of CANopen object 0x1016:01 and finally the CANopen-Master is sending an NMT Master Request 'Reset Node' (CS 81h).

Area Filter: All

Status Filter: Configured

Uncheck the communication and mapping parameter of PDO 3 and 4, receive and transmit:

CanOpen Info Set (CMMP-AS-C2-3A\_CAN\_FHPP.EDS)

CMMP\_AS\_C2\_3A\_FHPP  
Channel 0

Area Filter: All Status Filter: Configured

| Index/Subindex                                | Name                        | Current Value | Default Value  | Access | Type |
|---|-----------------------------|---------------|----------------|--------|------|
| 0x1017  | producer_heartbeat_time     |               |                |        |      |
| <input checked="" type="checkbox"/> 0x1017:00 | producer_heartbeat_time     | 200           | 0x00           | R/W    | UI16 |
| 0x1400  | receive_pdo_parameter_rpdo1 |               |                |        |      |
| <input checked="" type="checkbox"/> 0x1400:01 | cob_id_used_by_pdo_rpdo1    | 0x00000201    | \$NodeID+0x200 | R/W    | UI32 |
| <input checked="" type="checkbox"/> 0x1400:02 | transmission_type_rpdo1     | 1             | 0xFF           | R/W    | UI8  |
| 0x1401  | receive_pdo_parameter_rpdo2 |               |                |        |      |
| <input checked="" type="checkbox"/> 0x1401:01 | cob_id_used_by_pdo_rpdo2    | 0x00000301    | \$NodeID+0x300 | R/W    | UI32 |
| <input checked="" type="checkbox"/> 0x1401:02 | transmission_type_rpdo2     | 1             | 0xFF           | R/W    | UI8  |
| 0x1402  | receive_pdo_parameter_rpdo3 |               |                |        |      |
| <input type="checkbox"/> 0x1402:01            | cob_id_used_by_pdo_rpdo3    | 0x80000401    | \$NodeID+0x400 | R/W    | UI32 |
| <input type="checkbox"/> 0x1402:02            | transmission_type_rpdo3     | 255           | 0xFF           | R/W    | UI8  |
| 0x1403  | receive_pdo_parameter_rpdo4 |               |                |        |      |
| <input type="checkbox"/> 0x1403:01            | cob_id_used_by_pdo_rpdo4    | 0x80000501    | \$NodeID+0x500 | R/W    | UI32 |
| <input type="checkbox"/> 0x1403:02            | transmission_type_rpdo4     | 255           | 0xFF           | R/W    | UI8  |
| 0x1602  | receive_pdo_mapping_rpdo3   |               |                |        |      |
| <input type="checkbox"/> 0x1602:00            | receive_pdo_mapping_rpdo3   | 8             | 0x08           | R/W    | UI8  |
| <input type="checkbox"/> 0x1602:01            | first_mapped_object_rpdo3   | 0x31010008    | 0x31010008     | R/W    | UI32 |
| <input type="checkbox"/> 0x1602:02            | second_mapped_object_rpdo3  | 0x31020008    | 0x31020008     | R/W    | UI32 |
| <input type="checkbox"/> 0x1602:03            | third_mapped_object_rpdo3   | 0x31030008    | 0x31030008     | R/W    | UI32 |
| <input type="checkbox"/> 0x1602:04            | fourth_mapped_object_rpdo3  | 0x31040008    | 0x31040008     | R/W    | UI32 |
| <input type="checkbox"/> 0x1602:05            | fifth_mapped_object_rpdo3   | 0x31050008    | 0x31050008     | R/W    | UI32 |
| <input type="checkbox"/> 0x1602:06            | sixth_mapped_object_rpdo3   | 0x31060008    | 0x31060008     | R/W    | UI32 |
| <input type="checkbox"/> 0x1602:07            | seventh_mapped_object_rpdo3 | 0x31070008    | 0x31070008     | R/W    | UI32 |
| <input type="checkbox"/> 0x1602:08            | eighth_mapped_object_rpdo3  | 0x31080008    | 0x31080008     | R/W    | UI32 |
| 0x1603  | receive_pdo_mapping_rpdo4   |               |                |        |      |

Result:

CanOpen Info Set (CMMP-AS-C2-3A\_CAN\_FHPP.EDS)

CMMP\_AS\_C2\_3A\_FHPP  
Channel 0

Area Filter: All Status Filter: Configured

| Index/Subindex | Name                         | Current Value | Default Value  | Access | Type |
|----------------|------------------------------|---------------|----------------|--------|------|
| 0x1017         | producer_heartbeat_time      |               |                |        |      |
| 0x1017:00      | producer_heartbeat_time      | 200           | 0x00           | R/W    | UI16 |
| 0x1400         | receive_pdo_parameter_rpdo1  |               |                |        |      |
| 0x1400:01      | cob_id_used_by_pdo_rpdo1     | 0x00000201    | \$NodeID+0x200 | R/W    | UI32 |
| 0x1400:02      | transmission_type_rpdo1      | 1             | 0xFF           | R/W    | UI8  |
| 0x1401         | receive_pdo_parameter_rpdo2  |               |                |        |      |
| 0x1401:01      | cob_id_used_by_pdo_rpdo2     | 0x00000301    | \$NodeID+0x300 | R/W    | UI32 |
| 0x1401:02      | transmission_type_rpdo2      | 1             | 0xFF           | R/W    | UI8  |
| 0x1800         | transmit_pdo_parameter_tpdo1 |               |                |        |      |
| 0x1800:01      | cob_id_used_by_pdo_tpdo1     | 0x00000181    | \$NodeID+0x180 | R/W    | UI32 |
| 0x1800:02      | transmission_type_tpdo1      | 1             | 0xFF           | R/W    | UI8  |
| 0x1800:03      | inhibit_time_tpdo1           | 0             | 0x0000         | R/W    | UI16 |
| 0x1801         | transmit_pdo_parameter_tpdo2 |               |                |        |      |
| 0x1801:01      | cob_id_used_by_pdo_tpdo2     | 0x00000281    | \$NodeID+0x280 | R/W    | UI32 |
| 0x1801:02      | transmission_type_tpdo2      | 1             | 0xFF           | R/W    | UI8  |
| 0x1801:03      | inhibit_time_tpdo2           | 0             | 0x0000         | R/W    | UI16 |

## 2.9 Parameterizing the CANopen-Master (Master Configuration)

### Inputs and Outputs Configuration

To configure the inputs of the bus slaves, it is necessary to indicate the memory areas to which they will be periodically recopied. To configure the outputs, it is necessary to indicate, as for the inputs, the word and bits tables that will contain the values of the bus slave outputs.

File Edit View Services Tools Build PLC Debug Window Help

Project Browser

Structural view

Project

- Configuration
  - 0 : PLC bus
    - 0 : BMX XBP 0800
    - (P) (P) : BMX CPS 2000
    - 0 : BMX P34 20302
    - CANopen
    - Ethernet
  - 1 : BMX DDM 16022
  - 2
  - 3
  - 4
  - 5
  - 6
  - 7
- 3 : CANopen
  - Derived Data Types
  - Derived FB Types
  - Variables & FB Instances
    - Elementary Variables
    - Derived Variables
    - Device DDT Variables
    - IO Derived Variables
    - Elementary FB Instances
    - Derived FB Instances
  - Motion
  - Communication
  - Program
    - Tasks
      - MAST
    - Events

Communicator head CANopen

CANopen comm head Expert

Channel 2

Configuration

Inputs

Outputs

Fallback

Bus Stop when PLC stop

Maintain RESET

Nb. of words (%Mv) 128

Index of 1st %Mv 0

Nb. of bits (%M) 32

Index of 1st %M 0

Nb. of words (%Mv) 128

Index of 1st %Mv 128

Nb. of bits (%M) 32

Index of 1st %M 32

Bus parameters

Transmission speed 1000 kBaud

SYNC Message COB-ID 128

SYNC Message Period 10 ms

NMT inhibit time 5 ms

Device Bootstrap Time Out 50 ms

| Adr. | Device Name        | Specific SDO timeout (ms) |
|------|--------------------|---------------------------|
| 1    | CMMP_AS_C2_3A_FHPP | 15000                     |
| 2    |                    | 15000                     |
| 3    |                    | 15000                     |
| 4    |                    | 15000                     |
| 5    |                    | 15000                     |
| 6    |                    | 15000                     |
| 7    |                    | 15000                     |
| 8    |                    | 15000                     |
| 9    |                    | 15000                     |
| 10   |                    | 15000                     |
| 11   |                    | 15000                     |
| 12   |                    | 15000                     |

Function: CANopen expert

Task: MAST

**Configuration**

**Inputs**

Nb. of words (%Mw) 128

Index of 1st %Mw 0

Nb. of bits (%M) 32

Index of 1st %M 0

**Outputs**

**Fallback**

☐ Bus Stop when PLC stop

☐ Maintain ☒ RESET

Nb. of words (%Mw) 128

Index of 1st %Mw 128

Nb. of bits (%M) 32

Index of 1st %M 32

## 2.10 Bus Parameters

The figure below illustrates the bus parameters configuration area:

**Bus parameters**

Transmission speed 1000 kBaud

SYNC Message COB-ID 128

SYNC Message Period 10 ms

NMT inhibit time 5 ms

Device Bootup Time Out 50 ms


| Adr. | Device Name        | Specific SDO timeout (ms) |
|------|--------------------|---------------------------|
| 1    | CMMP_AS_C2_3A_FHPP | 15000                     |
| 2    |                    | 15000                     |
| 3    |                    | 15000                     |
| 4    |                    | 15000                     |

- the transmission speed: 250kBauds default, example project 1000 kBaud
- the COB-ID of the synchronization message: 128 default, => 80h
- the synchronization message period: 100ms default, example project 10ms
- the NMT inhibit time: 5ms default. During Bootup, the CANopen Master implements a delay between each NMT messages to avoid slave overload. The value must be given in multiple of 100  $\mu$  s. The value 0 disables the inhibit time.
- the Device Bootup Time Out: 50ms default. The global SDO timeout for the master is related to the scanning of the network. During this time, the master reads the object 1000 of each slave to analyse the CANopen bus configuration.


## 2.11 EMCY\_Emergency Message

Example: EMCY-Producer servo controller CMMP-AS

E08-6: Faulty angle encoder communication:



FCT\_Online to servo controller:



## 2.12 Checklist

This is just a kind of conclusion regarding important settings:

### **Bootup: sequence has to be modified in Unity Pro XL**

- No Restore
- Reset communication parameters or reset node
- Start node

### Object Dictionary: uncheck some CAN-objects:

- Uncheck object 0x1016:01 consumer heartbeat time
- Uncheck object 0x1402, 0x1403, 0x1602, 0x1603, 0x1802, 0x1803, 0x1a02 and 0x1A03 (Mapping and communication parameters of transmit and receive PDO 3 and 4. In case of FHPP+ you keep checked it

### PDO transmission mode:

- Using transmission mode cyclic synchronous '1' instead of asynchronous '255' for all PDO's receive and transmit.
- Check as well if the SYNC signal with COB-ID 128=80h is activated by the sync period time with e.g. 10 ms

### General:

Check all relevant settings in FCT and Unity Pro XL:

- Baud rate
- Node-ID
- Communication profile FHPP or DS402

### 3 Appendix

The following sections are excerpted from the:

#### CiA 302 Draft Standard Proposal

Additional application layer functions Part 2: Network Management / Version 4.1.0 / 02 February 2009

#### 3.1 6.6 Object 1F84h – Device type identification

This object is used for verification of the device type of the CANopen devices in the network.

The **device type** (object 1000h – see /CiA301/) of the CANopen device in the network shall be matched against the value of this object in case the value is unequal 0. An error event shall be generated if the values mismatch. In case the value of this object is 0 the device type of

the CANopen device in the network may not be verified. Table 34 and Table 35 define the object description and the entry description.

The following sections are related to **Device Identity (object 1018 sub-Index 1-4)**

#### 3.2 6.7 Object 1F85h – Vendor identification

The vendor-ID (object 1018h sub-index 01h – see /CiA301/) of the CANopen device in the network shall be matched against the value of this object in case the value is unequal 0.

An error event shall be generated if the values mismatch. In case the value of this object is 0 the vendor-ID of the CANopen device in the network may not be verified. Table 36 and Table 37 define the object description and the entry description.

#### 3.3 6.8 Object 1F86h – Product code

This object shall be used for verification of the product code of the CANopen devices in the network.

The product code (object 1018h sub-index 02h – see /CiA301/) of the CANopen device in the network shall be matched against the value of this object in case the value is unequal 0.

An error event shall be generated if the values mismatch. In case the value of this object is 0 the product code of the CANopen device in the network may not be verified. Table 38 and Table 39 define the object description and the entry description.

### **3.4 6.9 Object 1F87h – Revision number**

This object shall be used for verification of the revision number of the CANopen devices in the network.

The revision number (object 1018h sub-index 03h – see /CiA301/) of the CANopen device in the network shall be matched against the value of this object in case the value is unequal 0.

An error event shall be generated if the values mismatch. A mismatch is defined as:

- the major revision number is unequal to the expected major revision number, or
- the minor revision number is less than the expected minor revision number,

In case the value of this object is 0 the revision number of the CANopen device in the network shall not be verified. Table 40 and Table 41 define the object description and the entry description.

### **3.5 6.10 Object 1F88h – Serial number**

This object shall be used for verification of the serial number of the CANopen devices in the network.

The serial number (object 1018h sub-index 04h – see /CiA301/) of the CANopen device in the network shall be matched against the value of this object in case the value is unequal 0.

An error event shall be generated if the values mismatch. In case the value of this object is 0 the serial number of the CANopen device in the network may not be verified. Table 42 and Table 43 define the object description and the entry description.