



Project name: 100612

File date: 19.08.2026 09:11:38 Report date: 19.08.2026 Checksum: 73fbe6dae3246e3d9ae4a49835ecfc73

PR Project name: 100612**Project file name:** C:\Users\jkh\Documents\Projects\20260112-002 P54E - SC Cat3 PL d\100612 Sistema Project - V3.0.4 - EN.ssm**Creation date:** 19.08.2026 09:08:10**Project status:****Project number:****Project version:****Authors:****Project managers:****Inspectors:****Dangerous point/machine:****Documentation:****Document:****Version of software:** 3.0.4 build 3**Version of standard:** ISO 13849-1:2023, ISO 13849-2:2012**Checksum:** 73fbe6dae3246e3d9ae4a49835ecfc73**Options:** ☒ Use DC intermediate levels for calculation of PFH (more precise)
☐ MTTFD capping for category 4 lower from 2500 to 100 years.**Status:** ☒ green**Note:** There are no warnings listed for this project (or it's subordinate basic elements).**Print options**


- | | |
|--|---|
| ☒ Show device details | ☒ Show requirements on PL and Category |
| ☒ Show documentations on SF, SB, BL and EL | ☒ Show parameter documentations on PLr, PL, Category, CCF, MTTFD and DC |
| ☐ Show CCF and DC measures in detail | ☒ Show messages |

Contained safety functions**SF** Name: SC**Required:** PLr d **Reached:** PL e **PFH [1/h]:** 4,29E-8 **Status:** green**List of documented messages:**

- No messages known -

List of devices with a permissible operation time (T10D) of less than 20 years:

- No devices known -



Project name: 100612

File date: 19.08.2026 09:11:38 Report date: 19.08.2026 Checksum: 73fbe6dae3246e3d9ae4a49835ecfc73

SF Safety function: SC

Identifier of the Safety function:

Safety function type:

Triggering event:

Reaction and
Behaviour on power failure:

Safe state:

Operation mode:

Interfaces:

Demand rate:

Running-on time:

Priority:

Documentation:

Document:

Required Performance Level Safety function


PLr (by risk graph): d

Severity of injury (S): Serious (normally irreversible) injury or death

Frequency / exposure times to hazard (F): Frequent to continuous / exposure time is long

Possibility of avoiding (P): Possible under specific conditions

Risk graph:



Documentation:

Document:

Performance Level Safety function

Reached PL: e

PFH [1/h]: 4,29E-8


*Electromagnetic immunity, EMI (Annex L) Safety function*Route for fulfilment
of EMI measures: n/a

Documentation:

Document:

List of devices with a permissible operation time (T10D) of less than 20 years:

Device list:



Project name: 100612

File date: 19.08.2026 09:11:38 Report date: 19.08.2026 Checksum: 73fbe6dae3246e3d9ae4a49835ecfc73

SF Safety function: SC*Status / Messages Safety function***Status:** green**Subsystems (1 / 1)****SB Name:** Output**Reference designator:****Inventory number:***Device details Subsystem***Device Manufacturer:****Device Identifier:****Device group:****Part number:****Revision:****Function:**☐ Input☒ Output☐ Logic☐ unknown**Use case:****Description of the use case:***Documentation Subsystem***Documentation:****Document:***Performance Level Subsystem***PL determination:** Determine PL/PFH from Category, MTTFD and DCavg*Qualitative aspects (e.g. software, see sections 7, 10.3) Subsystem***Qualitative aspects suitable up to PL:** n/a**Documentation:****Document:***Electromagnetic immunity, EMI (Annex L) Subsystem***Route for fulfilment of EMI measures:** The fulfilment of the measures for electromagnetic immunity (EMI) was documented in the associated safety function.**PL requirements:** fulfilled**The PL shall be determined by the estimation of the following aspects (section 6.1.1):**

- Behaviour of the safety function under fault conditions [fulfilled]
- Safety-related software according to clause 7 and Annex J or no software included [fulfilled]
- Systematic failure (see clause 6.1.7 and Annex G) [fulfilled]
- Ability to perform a safety function under expected environmental conditions [fulfilled]



Project name: 100612

File date: 19.08.2026 09:11:38 Report date: 19.08.2026 Checksum: 73fbe6dae3246e3d9ae4a49835ecfc73

Safety function: SC

Reached PL:	e	PFH [1/h]:	4,29E-8
-------------	---	------------	---------

Documentation:

Category Subsystem

Cat.:	3
-------	---

Category requirements:	fulfilled
------------------------	-----------

Requirements for the category:

- Accordance with relevant standards to withstand the expected influences. [fulfilled]
- Basic safety principles are being used. [fulfilled]
- Well-trying safety principles are being used. [fulfilled]
- A single fault tolerance and reasonable fault detection are given. [fulfilled]
- MTTFD is at least Low. [fulfilled]
- Requirement fulfilled because of the assumed limit value accuracy of 5 percentage points. [fulfilled]
- The achieved score of the CCF-rating is at least 65. [fulfilled]

Documentation:

Source (e.g. standard) Category:

File:

MTTFD and Mission time Subsystem

MTTFD [a]:	100 (High)
------------	------------

Mission time [a]:	20	Shortest mission time [a]:	20
-------------------	----	----------------------------	----

Diagnostic coverage Subsystem

DCavg [%]:	90 (Medium)
------------	-------------

Common cause failure Subsystem

CCF Points:	100 (fulfilled)
-------------	-----------------

CCF Measures:


- 15 Points | Separation/segregation
- 20 Points | Diversity
- 15 Points | Protection against over-voltage, over-pressure, over-current, over-temperature
- 5 Points | Components used are well-trying
- 5 Points | Assessment/analysis
- 5 Points | Training
- 25 Points | Prevention of EMI or impurity of fluidic medium
- 10 Points | Other influences

Documentation:

Document:

Status / Messages Subsystem

Status:	green
---------	-------



Project name: 100612


File date: 19.08.2026 09:11:38 Report date: 19.08.2026 Checksum: 73fbe6dae3246e3d9ae4a49835ecfc73

SF Safety function: SC**Channels / Test channels (1 / 2)****CH** Name: Channel 1

MTTFD [a]: 100

Blocks (1 / 1)**BL** Name: 5/4-way valve**Reference designator:** Q1**Inventory number:***Device details Block***Device Manufacturer:****Device Identifier:****Device group:****Part number:****Revision:****Function:**☐ Input
☒ Output☐ Logic
☐ unknown**Technology:** unknown**Category:** -**Use case:****Description of the use case:***Documentation Block***Documentation:****Document:***MTTFD and Mission time Block***MTTFD [a]:** 380,5 (High)**Mission time [a]:** 20**Shortest mission time [a]:** 20**B10 [cycles]:** 10000000**RDF [%]:** 50**B10D [cycles]:** 20000000**nop [cycles/a]:** 525600**Documentation:****Document:***Diagnostic coverage Block***DC [%]:** 90 (Medium)**Measure:**

Indirect monitoring (e.g. monitoring by pressure switch, electrical position monitoring of machine actuators)



Project name: 100612

File date: 19.08.2026 09:11:38 Report date: 19.08.2026 Checksum: 73fbe6dae3246e3d9ae4a49835ecfc73

SF Safety function: SC**Documentation:****Document:***Status / Messages Block***Status:** green**Channels / Test channels (2 / 2)****CH** Name: Channel 2

MTTFD [a]: 100

Blocks (1 / 1)**BL** Name: 3/2-way valve**Reference designator:** Q2**Inventory number:***Device details Block***Device Manufacturer:****Device Identifier:****Device group:****Part number:****Revision:****Function:**☐ Input
☐ Output☐ Logic
☒ unknown**Technology:** unknown**Category:** -**Use case:****Description of the use case:***Documentation Block***Documentation:****Document:***MTTFD and Mission time Block***MTTFD [a]:** 182648,4 (High)

Mission time [a]:	20	Shortest mission time [a]:	20
--------------------------	----	-----------------------------------	----

B10 [cycles]:	10000000	RDF [%]:	50
----------------------	----------	-----------------	----

B10D [cycles]:	20000000	nop [cycles/a]:	1095
-----------------------	----------	------------------------	------



Project name: 100612

File date: 19.08.2026 09:11:38 Report date: 19.08.2026 Checksum: 73fbe6dae3246e3d9ae4a49835ecfc73

SF Safety function: SC

Documentation:

Document:

Diagnostic coverage Block

DC [%]: 90 (Medium)

Measure:


Indirect monitoring (e.g. monitoring by pressure switch, electrical position monitoring of machine actuators)

Documentation:

Document:

Status / Messages Block

Status: green



Project name: 100612

File date: 19.08.2026 09:11:38 Report date: 19.08.2026 Checksum: 73fbe6dae3246e3d9ae4a49835ecfc73

EXCLUSION OF LIABILITY

Care has been taken in production of the software SISTEMA, which corresponds to the state of the art. It is made available to users free of charge.

Die Haftung des Institut für Arbeitsschutz der DGUV (IFA) ist damit auf Vorsatz und grobe Fahrlässigkeit (§ 521 BGB) bzw. bei Sach- und Rechtsmängel auf arglistig verschwiegene Fehler beschränkt (523, 524 BGB).

The Institute for Occupational Safety and Health of the German Social Accident Insurance undertakes to keep its website free of viruses; nevertheless, no guarantee can be given that the software and information provided are virus-free. The user is therefore advised to take appropriate security precautions and to use a virus scanner prior to downloading software, documentation or information.

German Social Accident Insurance (DGUV)
Glinkastraße 40
D-10117 Berlin

E-mail: info@dguv.de
Internet: www.dguv.de

NOTE

This document is not a complete technical documentation according to EN ISO 13849-1:2023, clause 12.

CONTACT

Company contact details unknown

Name in block letters

Date, signature

Authors

Authors

Inspectors

Inspectors