

Pinch valve VZQA-C-M22C-15-TT-V2V4S1-2

Part number: 3412429

FESTO



[PDF](#) [General operating condition](#)

Data sheet

| Feature | Value |
|-----------------------------|---|
| Design | Pinch valve, pneumatically actuated |
| Type of actuation | Pneumatic |
| Sealing principle | Soft |
| Mounting position | optional |
| Type of mounting | In-line installation |
| Connection Process valve | 1/2 NPT |
| Nominal size DN | 15 |
| Valve function | 2/2-way, closed, monostable |
| Flow direction | Reversible |
| Medium pressure | 0 MPa ... 0.2 MPa |
| Medium pressure | 0 bar ... 2 bar |
| Medium pressure | 0 psi ... 29 psi |
| Note on the medium pressure | Use in the vacuum range was tested up to -0.09 MPa with the air at room temperature. Depending on the application, a counter-vacuum may have to be created on the control side to guarantee the media flow. |
| Operating pressure | 0.35 MPa ... 0.6 MPa |
| Operating pressure | 3.5 bar ... 6 bar |
| Operating pressure | 50.75 psi ... 87 psi |
| Nominal pressure PN | 10 |
| Burst pressure | 1.6 MPa |
| Burst pressure | 16 bar |
| Burst pressure | 232 psi |
| Type of reset | Mechanical spring |
| Type of piloting | Externally controlled |
| Auxiliary pilot air port 12 | M5 |
| Pilot medium | Compressed air to ISO 8573-1:2010 [7:4:1] |
| Symbol | 00992981 |
| Medium | Compressed air to ISO 8573-1:2010 [-:::1] Water |
| Max. viscosity | 4000 mm ² /s |

| Feature | Value |
|-------------------------------|-------------------------------|
| Media temperature | -5 °C ... 100 °C |
| Ambient temperature | -5 °C ... 60 °C |
| Storage temperature | 5 °C ... 30 °C |
| Flow rate Kv | 5 m ³ /h |
| Switching time on | 150 ms |
| Switching time off | 250 ms |
| Note on materials | RoHS-compliant |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Material housing | High-alloy stainless steel |
| Material number housing | 1.4301 |
| Material housing cover | High-alloy stainless steel |
| Material number housing cover | 1.4404 / AISI 316L |
| Material seals | FPM |
| Material shut-off element | VMQ (silicone) |
| Product weight | 549 g |
| Suitable for use with food | See declaration of conformity |
| Material bowl | PPS |