


Parallel gripper HGPT-63-A-B-G2

Part number: 560230

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|--|--|
| Size | 63 |
| Stroke per gripper jaws | 16 mm |
| Max. replacement accuracy | ≤0.2 mm |
| Max. angular gripper jaw backlash ax, ay | ≤0.1 deg |
| Max. gripper jaw backlash Sz | ≤0.02 mm |
| Rotationally symmetrical | ≤0.2 mm |
| Repetition accuracy, gripper | ≤0.05 mm |
| Number of gripper jaws | 2 |
| Drive system | Pneumatic |
| Mounting position | optional |
| Mode of operation | Double-acting |
| Gripper function | Parallel |
| Gripper force back-up | During closing |
| Design | Wedge-shaped drive Force pilot operated motion sequence |
| Position detection | Via proximity switch |
| Symbol | 00991895 |
| Operating pressure | 4 bar ... 8 bar |
| Operating pressure of blocked air | 0 bar ... 0.5 bar |
| Max. operating frequency of gripper | ≤2 Hz |
| Min. opening time at 0.6 MPa (6 bar, 87 psi) | 294 ms |
| Min. closing time at 0.6 MPa (6 bar, 87 psi) | 185 ms |
| Max. mass per external gripper finger | 1260 g |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Degree of protection | IP40 |
| Ambient temperature | 5 °C ... 60 °C |
| Mass moment of inertia | 93.034 kgcm ² |
| Max. force on gripper jaw Fz static | 5000 N |
| Max. torque at gripper Mx static | 160 Nm |
| Max. torque at gripper My static | 180 Nm |
| Max. torque at gripper Mz static | 140 Nm |
| Lubrication interval for guide components | 5 MioCyc |

| Feature | Value |
|-----------------------------------|---|
| Product weight | 3562 g |
| Type of mounting | Either: Via female thread and centring sleeve Via through-hole and centring sleeve Via through-hole and dowel pin Via female thread and dowel pin |
| Pneumatic connection, blocked air | M5 |
| Pneumatic connection | G1/8 |
| Note on materials | RoHS-compliant |
| Material cover cap | High-alloy stainless steel |
| Material housing | Anodised aluminium |
| Material gripper jaws | Hardened steel |