

Sub-base VMPAL-AP-4X10-QS6-2

Part number: 561084

FESTO



 General operating condition

Data sheet

| Feature | Value |
|------------------------------------|--|
| Width | 42.8 mm |
| Length | 107.3 mm |
| Grid dimension | 10.7 mm |
| Valve size | 10 mm |
| Max. number of valve positions | 4 |
| Flow direction | Reversible |
| Valve terminal structure | Valve sizes can be mixed |
| Max. number of valve coils | 8 |
| Operating pressure | -0.09 MPa ... 1 MPa |
| Operating pressure | -0.9 bar ... 10 bar |
| Pilot pressure | 0.3 MPa ... 0.8 MPa |
| Pilot pressure | 3 bar ... 8 bar |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 3 - high corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -5 °C ... 50 °C |
| Product weight | 110 g |
| Pneumatic connection, port 2 | For tubing outside diameter of 6 mm |
| Pneumatic connection, port 4 | For tubing O.D. 6 mm |
| Note on materials | RoHS-compliant |
| Material sub-base | PA-reinforced |