

Parallel gripper DHPC-25-A-NO-S

Part number: 8116855

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|---|---|
| Size | 25 |
| Stroke per gripper jaws | 7 mm |
| Max. replacement accuracy | 0.2 mm |
| Max. angular gripper jaw backlash ax, ay | 0 deg |
| Max. gripper jaw backlash Sz | 0 mm |
| Rotationally symmetrical | ≤0.2 mm |
| Repetition accuracy, gripper | ≤0.02 mm |
| Number of gripper jaws | 2 |
| Drive system | Pneumatic |
| Mounting position | optional |
| Mode of operation | Single-acting Open |
| Gripper function | Parallel |
| Gripper force back-up | During opening |
| Design | Connection direction at side Lever Standard mounting method for gripper fingers Force pilot operated motion sequence |
| Guide | Ball guide |
| Position detection | Via proximity switch |
| Symbol | 00997349 |
| Operating pressure | 0.25 MPa ... 0.8 MPa |
| Operating pressure | 2.5 bar ... 8 bar |
| Operating pressure | 36.25 psi ... 116 psi |
| Max. operating frequency of gripper | 3 Hz |
| Min. opening time at 0.6 MPa (6 bar, 87 psi) | 131 ms |
| Min. closing time at 0.6 MPa (6 bar, 87 psi) | 38 ms |
| Max. mass per external gripper finger | 160 g |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Suitability for the production of Li-ion batteries | Suitable for battery production with reduced Cu/Zn/Ni values (F1a) |
| Ambient temperature | -10 °C ... 60 °C |
| Total gripping force, closing, 0.6MPa (6bar, 87 psi) | 241.3 N |
| Gripper force per gripper jaw, closing, 0.6 MPa (6 bar, 87 psi) | 120.6 N |

| Feature | Value |
|-------------------------------------|---|
| Mass moment of inertia | 1.6 kgcm ² |
| Max. force on gripper jaw Fz static | 155.9 N |
| Max. torque at gripper Mx static | 4.83 Nm |
| Max. torque at gripper My static | 2.52 Nm |
| Max. torque at gripper Mz static | 2.52 Nm |
| Product weight | 441 g |
| Type of mounting | Either: Direct mounting via through-hole Direct mounting via thread On mounting frame Via through-hole and dowel pin Via female thread and dowel pin |
| Pneumatic connection | M5 |
| Note on materials | RoHS-compliant |
| Material housing | Anodised aluminium |
| Material gripper jaws | High-alloy stainless steel |