

Compact cylinders ADN/AEN, to ISO 21287

FESTO




Key features

At a glance

Sensor slots on three sides for flush mounting of proximity switches

Piston rod with choice of male or female thread

Mounting option: Female thread and through-hole



Centring hole in the end cap suitable for centring pins ZBS

Magnet for contactless position sensing

Integrated cushioning for absorbing residual energy

More than the standard

- The compact cylinders comply with or are based on the ISO 21287 standard, depending on the piston diameter
- The ADN/AEN is characterised by its compact design and wide range of application thanks to the large number of variants
- The variants can be configured using a modular product system

Powerful

- Integrated cushioning for absorbing residual energy
- Long service life thanks to exceptional cushioning characteristics and low friction values

Convenient

- Easy to mount with a comprehensive range of mounting accessories for just about every type of installation
- Highly flexible thanks to the wide range of variants
- Contactless position sensing using proximity switches

Reliable

- Optimised manufacturing methods, patented technology and more than 40 years of experience in the field of cylinders make Festo and ADN/AEN a great partner

Cushioning types

Cushioning P

Operating mode

- The drive is fitted with polymer elastic end-position cushioning

Application

- Small loads
- Low speeds
- Small cushioning capacity

Advantages

- No adjustment required
- Saves time

Cushioning PPS

Operating mode

- The drive has self-adjusting, pneumatic end-position cushioning

Application


- Larger loads
- Higher speeds
- Larger cushioning capacity

Advantages

- No adjustment required
- Cushioning capacity is four times bigger than ADN-...-P
- Saves time
- Reduces noise

Cushioning capacity of ISO 21287 and ISO 15552

The cushioning capacity of the compact cylinder ADN-...-PPS fills the gap between ADN-...-P and standards-based cylinders to ISO 15552.



For manufacturing lithium-ion batteries





ADN-...-F1A

Recommended for production systems for manufacturing lithium-ion batteries. Metals with copper, zinc or nickel as the main constituent are excluded from use. Exceptions are nickel in steels, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils.

Accessories

Please contact your Festo representative for information on which accessories are suitable for manufacturing lithium-ion batteries.

Key features

Variants from the modular product system		
Symbol	Key features	Description
	S1 Reinforced piston rod	Increased transverse forces. Absorbs many times more transverse force than a basic cylinder
	S2 Through piston rod	The piston rod can be used for attachment at both ends of the cylinder
	S6 Heat-resistant seals	Temperature resistance up to max. 120°C
	S10 Constant motion (slow speed) at low piston speeds	• Break-away pressure: very low • Dynamic response: suitable for very slow, constant and stick-slip-free movements Application example: slow, constant feed motion
	S11 Low friction	• Break-away pressure: very low • Dynamic response: especially suitable for slow movements with considerably reduced system friction • Application example: slow applications where standstill is critical
	S20 Through, hollow piston rod	The piston rod can be used for attachment at both ends of the cylinder. The piston rod is hollow inside. This means it can be used to carry vacuum or compressed air
	K2 Extended male piston rod thread	–
	K5 Special piston rod thread	Metric standard thread to ISO
	K8 Extended piston rod	–
	K10 Smooth anodised aluminium piston rod	Ideal for use in welding environments: • Protection against welding spatter • Small moving masses • Harder surface compared to steel • Long service life
	KP With clamping unit	Integrated clamping unit on the piston rod
	EL With end-position locking	Positive locking in the end position as a drop guard. If there is a drop in pressure, the cylinder is secured in its end position to prevent it from dropping
	Q Square piston rod	Protection against rotation. For position-oriented feeding
	R3 High corrosion protection	All external cylinder surfaces comply with corrosion resistance class 3 to Festo standard 940 070. The piston rod is made from corrosion- and acid-resistant steel
	R8 Dust protection with scraper	The cylinder has a hard-chrome-plated piston rod and a hard scraper, which protects against dry, dusty media
	TL Captive rating plate	Laser-etched rating plate. Easy identification for spare parts, even after years in a harsh environment
	TT Low temperature	Temperature resistance down to max. -40°C
	F1A Recommended for production plants for manufacturing lithium-ion batteries	Cylinders free of copper, zinc and nickel (§ 1%)




Product range overview

Function	Version	Type	Piston ø	Stroke	Position sensing	Recommended for production systems for manufacturing lithium-ion batteries	Cushioning		
			[mm]	[mm]			Fixed	Self-adjusting	
					A	F1A	P	PPS	
Double-acting	Basic version								
		ADN	12	5, 10, 15, 20, 25, 30, 35, 40, 50, 60	1 ... 300	■	■	■	■ ø 20 ... 100 As of 5 mm stroke
			16	5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70	1 ... 300				
			20	5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70	1 ... 300				
			25	5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70, 80	1 ... 300				
			32, 40, 50	5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70, 80	1 ... 400				
			63	10, 15, 20, 25, 30, 35, 40, 50, 60, 70, 80	1 ... 400				
			80, 100	10, 15, 20, 25, 30, 40, 50, 60, 80	1 ... 500				
			125	–	1 ... 500				
		ADN-...-S2 Through piston rod	12, 16, 20, 25	–	1 ... 300	■	■	■	■ ø 20 ... 100 As of 5 mm stroke
			32, 40, 50, 63	–	1 ... 400				
			80, 100, 125	–	1 ... 500				
		ADN-...-S20 Through, hollow piston rod	16, 20, 25	–	1 ... 300	■	–	■	■ ø 20 ... 100 As of 5 mm stroke
			32, 40, 50, 63	–	1 ... 400				
			80, 100, 125	–	1 ... 500				
	Reinforced piston rod								
		ADN-...-S1	25	–	5 ... 300	■	–	■	–
			40, 63	–	10 ... 400				
			100	–	10 ... 500				
	Protected against rotation with square piston rod								
		ADN-...-Q	12, 16, 20, 25	–	1 ... 300	■	–	■	–
			32, 40, 50, 63	–	1 ... 400				
			80, 100, 125	–	1 ... 500				
		ADN-...-Q-S2 Through piston rod	12, 16, 20, 25	–	1 ... 300	■	–	■	–
			32, 40, 50, 63	–	1 ... 400				
			80, 100, 125	–	1 ... 500				
	ADN-...-Q-S20 Through, hollow piston rod	16, 20, 25	–	1 ... 200	■	–	■	–	
		32, 40, 50, 63	–	1 ... 300					
		80, 100, 125	–	1 ... 400					
Standard hole pattern, with clamping unit									
	ADN-...-KP	20, 25	–	10 ... 300	■	–	■	–	
		32, 40, 50, 63	–	10 ... 400					
		80, 100	–	10 ... 500					
Standard hole pattern, with end-position locking									
	ADN-...-EL	20, 25	–	10 ... 300	■	–	■	–	
		32, 40, 50, 63	–	10 ... 400					
		80, 100	–	10 ... 500					

Product range overview

Type	Male piston rod thread	Female piston rod thread	Extended male piston rod thread	Special piston rod thread	Extended piston rod	Smooth anodised piston rod	Heat-resistant seals max. 120 °C	Slow speed (constant motion)	Low friction	High corrosion protection	Dust protection	Low temperature	→ Page/Internet
	A	I	K2	K5	K8	K10	S6	S10	S11	R3	R8	TT	
Basic version													
ADN	■	■	■	■	■	■ from Ø 20	■	■	■	■	■ from Ø 20	■ Ø 20 ... 100	13
ADN-...-S2 Through piston rod	■	■	■	■	■	—	■	—	—	—	—	■ Ø 20 ... 100	13
ADN-...-S20 Through, hollow piston rod	■	—	■	■	■	—	■	—	—	—	—	—	13
Reinforced piston rod													
ADN-...-S1	■	■	■	■	■	—	■	—	—	■	—	—	13
Protected against rotation with square piston rod													
ADN-...-Q	■	■	■	■	■	—	■	—	—	—	—	—	13
ADN-...-Q-S2 Through piston rod	■	■	■	■	■	—	■	—	—	—	—	—	13
ADN-...-Q-S20 Through, hollow piston rod	■	—	■	■	■	—	■	—	—	—	—	—	13
Standard hole pattern, with clamping unit													
ADN-...-KP	■	■	■	■	■	—	—	—	—	—	—	—	44
Standard hole pattern, with end-position locking													
ADN-...-EL	■	■	■	■	■	—	—	—	—	—	—	—	53

Product range overview

Function	Version	Type	Piston Ø	Stroke		Position sensing	Cushioning	
							Fixed	Self-adjusting
			[mm]	[mm]		A	P	PPS
Double-acting	Standard hole pattern, non-rotating with yoke							
		ADNGF	12	5, 10, 15, 20, 25, 30, 40	1 ... 200	■	■	■ Ø 20 ... 100
			16	5, 10, 15, 20, 25, 30, 40, 50	1 ... 200			
			20, 25	5, 10, 15, 20, 25, 30, 40, 50, 60	3 ... 200			
			32, 40, 50	5, 10, 15, 20, 25, 30, 40, 50, 60, 80	5 ... 300			
			63, 80	10, 15, 20, 25, 30, 40, 50, 60, 80	5 ... 300			
			100	10, 15, 20, 25, 30, 40, 50, 60, 80	5 ... 400			
		ADNGF-...-S2 Through piston rod	12, 16	–	1 ... 200	■	■	■ Ø 20 ... 100
			20, 25		3 ... 200			
			32, 40, 50, 63, 80, 100		5 ... 250			
		ADNGF-...-S6 Heat-resistant seals max. 120°C	12	5, 10, 15, 20, 25, 30, 40	1 ... 200	■	■	–
			16	5, 10, 15, 20, 25, 30, 40, 50	1 ... 200			
			20, 25	5, 10, 15, 20, 25, 30, 40, 50, 60	3 ... 200			
			32, 40, 50	5, 10, 15, 20, 25, 30, 40, 50, 60, 80	5 ... 250			
			63, 80, 100	10, 15, 20, 25, 30, 40, 50, 60, 80	5 ... 250			
	Standard hole pattern, high-force cylinder							
		ADNH	25	–	1 ... 150	■	■	–
			40					
			63					
			100					
	Standard hole pattern, multi-position cylinder							
		ADNM	25	–	1 ... 2 000	■	■	–
			40					
			63					
100								

Product range overview

Type	Male piston rod thread	Female piston rod thread	Extended male piston rod thread	Special piston rod thread	Extended piston rod	→ Page/Internet
	A	I	K2	K5	K8	
Standard hole pattern, non-rotating with yoke						
ADNGF	—	—	—	—	—	adngf
ADNGF-....S2 Through piston rod	—	—	—	—	—	adngf
ADNGF-....S6 Heat-resistant seals max. 120°C	—	—	—	—	—	adngf
Standard hole pattern, high-force cylinder						
ADNH	■	■	■	■	■	adnh
Standard hole pattern, multi-position cylinder						
ADNM	■	■	■	■	■	adnh


Product range overview

Function	Version	Type	Piston Ø	Stroke	Position sensing	Cushioning
			[mm]	[mm]	A	P
Single-acting	Basic version					
		AEN	12	1 ... 10		
			16, 20, 25, 32, 40, 50, 63, 80, 100	1 ... 25		
		AEN-...-Z Pulling	12	1 ... 10		
			16, 20, 25, 32, 40, 50, 63, 80, 100	1 ... 25		
	Protected against rotation with square piston rod					
		AEN-...-Q	16	1 ... 25		
20, 25, 32, 40, 50, 63, 80, 100			1 ... 25			

Product range overview

Type	Male piston rod thread	Female piston rod thread	Extended male piston rod thread	Special piston rod thread	Extended piston rod	Smooth anodised piston rod	Heat-resistant seals max. 120 °C	→ Page/Internet
	A	I	K2	K5	K8	K10	S6	
Basic version								
AEN	■	■	■	■	■	■ from Ø 20	■	63
AEN-...-Z Pulling	■	■	■	■	■	■ from Ø 20	■	63
Protected against rotation with square piston rod								
AEN-...-Q	■	■	■	■	■	—	■	63

Peripherals overview



Peripherals overview

Mounting attachments and accessories		Description	→ Page/Internet
[1]	Compact cylinder ADN	Double-acting cylinder	13
	Compact cylinder AEN	Single acting cylinder	63
[2]	One-way flow control valve GRLA/GRLZ	For regulating speed	89
[3]	Push-in fitting QS	For connecting tubing with standard O.D.	qs
[4]	Foot mounting HNA	For bearing or end caps	78
[5]	Flange mounting FNC	For bearing or end caps	79
[6]	Trunnion flange ZNCF/CRZNG	For bearing caps	86
[7]	Trunnion support LNZG	For trunnion flange ZNCF/CRZNG	87
[8]	Swivel flange SNCL/SNCL-...-R3	For end caps	80
[9]	Multi-position kit DPNA	For connecting two cylinders with the same piston diameter to form a multi-position cylinder	83
[10]	Swivel flange SNCS/CRSNCS/SNCS-...-R3	For end caps	81
[11]	Swivel flange SNCB/SNCB-...-R3	For swivel flange SNCL	85
[12]	Clevis foot LBN/CRLBN	For swivel flange SNCL	84
[13]	Clevis foot LBG/LBG-...-R3	For swivel flange SNCS	82
[14]	Proximity switch SME-8	Can be integrated in the cylinder profile barrel	91
[15]	Proximity switch SME/SMT-8M	Can be integrated in the cylinder profile barrel	91
[16]	Proximity switch SMT-8G	Inserted into the slot lengthwise	91
[17]	Slot cover ABP-5-S	For protecting the sensor cables and the sensor slots from contamination	92
[18]	Proximity switch SMPO-8E	Pneumatic output signal	92
[19]	Mounting kit SMB-8E	For proximity switch SMPO-8E	92
[20]	Self-aligning rod coupler FK/CRFK/DARP	To compensate for radial and angular deviations	88
[21]	Rod clevis SG/CRSG	Permits a swivelling movement of the cylinder in one plane	88
[22]	Adapter AD	For mounting a suction cup on a hollow piston rod	88
[23]	Coupling piece KSG/KSZ	To compensate for radial deviations	88
[24]	Rod eye SGS/CRSGS	With spherical bearing	88
[25]	Right-angle clevis foot LQG	For rod eye SGS	89
[26]	Rod clevis SGA	With male thread	88

Type codes

001	Series
ADN	Compact cylinder, double-acting, based on ISO 21287

002	Piston diameter [mm]
12	12
16	16
20	20
25	25
32	32
40	40
50	50
63	63
80	80
100	100
125	125

003	Stroke range [mm]
...	1 ... 500

004	Piston rod thread type
A	Male thread
I	Female thread

005	Cushioning
P	Elastic cushioning rings/plates on both sides
PPS	Pneumatic cushioning, self-adjusting at both ends

006	Position sensing
A	For proximity sensor

007	Special material properties
	None
F1A	Recommended for production plants for manufacturing lithium-ion batteries, F1A

008	Protection against rotation
	None
Q	Square piston rod

009	Piston rod type
	At one end
S2	Through piston rod
S20	Through, hollow piston rod

010	Custom thread
"M5"K5	M5
"M6"K5	M6
"M8"K5	M8
"M10"K5	M10
"M10x1,25"K5	M10x1.25
"M12"K5	M12
"M16"K5	M16
"M20"K5	M20
"M20x1,5"K5	M20x1.5

011	Temperature range
	Standard
S6	Heat-resistant seals max. 120 °C

012	Constant motion
	Standard
S10	Uniform, slow movement

013	Running characteristics
	Standard
S11	Low friction

014	Improved running performance
	None
K10	Smooth anodised aluminium coated piston rod

015	Corrosion protection
	Standard
R3	High corrosion protection

016	Increased lateral force
	None
S1	Reinforced piston rod or extended piston rod bearing

017	Captive rating plate
	Rating plate, glued
TL	Laser etched rating plate


018	Low temperature
	None
TT	-40 °C ... +80 °C

019	Scraper variant
	Standard
R8	Dust protection


020	EU certification
	None
EX4	II 2GD

Datasheet

Function
cushioning P



PPS cushioning



⌀ - Diameter
12 ... 125 mm

— - Stroke length
1 ... 500 mm

Variants → page 3



www.festo.com



General technical data												
Piston Ø	12	16	20	25	32	40	50	63	80	100	125	
Standard	Based on ISO 21287		Conforms to ISO 21287								Based on ISO 21287	
Design	Piston											
	Piston rod											
	Cylinder barrel											
Operating mode	Double-acting											
Cushioning												
P	Elastic cushioning rings/plates at both ends											
PPS	–		Pneumatic cushioning, self-adjusting at both ends								–	
Cushioning length												
PPS	[mm]	–	3	3.5	4	5	6	7	7.5	10	–	
Position sensing	Via proximity switch											
Type of mounting	With through-hole											
	With female thread											
	With accessories											
Mounting position	Any											

Technical data – Basic version and variants						
Piston Ø	12	16	20	25	32	40
Pneumatic connection						
—	M5	M5	M5	M5	G1/8	G1/8
S1	—	—	—	M5	—	M5
Female piston rod thread						
—	M3	M4	M6	M6	M8	M8
K5	—	—	M5	M5	M6	M6
S1	—	—	—	M6	—	M10
S1-K5	—	—	—	M5	—	M8
Male piston rod thread						
—	M5	M6	M8	M8	M10x1.25	M10x1.25
K5	M6	M8	M10; M10x1.25	M10; M10x1.25	M10; M12	M10; M12
S1	—	—	—	M8	—	M12x1.25
S1-K5	—	—	—	M10; M10x1.25	—	M10x1.25; M12
Q-K5	M6	M8	M10; M10x1.25	M10; M10x1.25	M10	M10
Max. torsional backlash of the piston rod [°]						
Q	2	1.8	1.6	1.6	1.2	1.2

Datasheet

Technical data – Basic version and variants											
Piston Ø	50		63		80		100		125		
Pneumatic connection											
–	G1/8		G1/8		G1/8		G1/8		G1/4		
S1	–		G1/8		–		G1/8		–		
Female piston rod thread											
–	M10		M10		M12		M12		M16		
K5	M8		M8		M10		M10		–		
S1	–		M12		–		M16		–		
S1-K5	–		M10		–		–		–		
Male piston rod thread											
–	M12x1.25		M12x1.25		M16x1.5		M16x1.5		M20x1.5		
K5	M12; M16		M12; M16		M16; M20; M20x1.5		M16; M20; M20x1.5		M20		
S1	–		M16x1.5		–		M20x1.5		–		
S1-K5	–		M12x1.25; M16		–		M16x1.5; M20		–		
Q-K5	M12		M12		M16		M16		M20		
Max. torsional backlash of the piston rod [°]											
Q	1		1		0.8		0.8		0.8		

Operating and environmental conditions												
Piston Ø	12	16	20	25	32	40	50	63	80	100	125	
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]											
Note on the operating/pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)											
Operating pressure												
in [MPa]												
–	0.1 ... 1		0.06 ... 1									
PPS	–		0.15 ... 1			0.1 ... 1			–			
Q	0.15 ... 1		0.1 ... 1									
Q-S6	0.15 ... 0.6		0.1 ... 0.6									
S1	–			0.1 ... 1	–	0.1 ... 1	–	0.1 ... 1	–	0.1 ... 1	–	
S2, S20	0.15 ... 1		0.12 ... 1		0.1 ... 1			0.08 ... 1				
S6	0.1 ... 1		0.06 ... 1									
S11	0.045 ... 1				0.025 ... 1							
R8, TT	–		0.15 ... 1			0.1 ... 1			–			
in [bar]												
–	1 ... 10		0.6 ... 10									
PPS	–		1.5 ... 10			1 ... 10			–			
Q	1.5 ... 10		1 ... 10									
Q-S6	1.5 ... 6		1 ... 6									
S1	–			1 ... 10	–	1 ... 10	–	1 ... 10	–	1 ... 10	–	
S2, S20	1.5 ... 10		1.2 ... 10		1 ... 10			0.8 ... 10				
S6	1 ... 10		0.6 ... 10									
S11	0.45 ... 10				0.25 ... 10							
R8, TT	–		1.5 ... 10			1 ... 10			–			
in [psi]												
–	14.5 ... 145		8.7 ... 145									
PPS	–		21.76 ... 145			14.5 ... 145			–			
Q	21.76 ... 145		14.5 ... 145									
Q-S6	21.76 ... 87		14.5 ... 87									
S1	–			14.5 ... 145	–	14.5 ... 145	–	14.5 ... 145	–	14.5 ... 145	–	
S2, S20	21.76 ... 145		17.4 ... 145		14.5 ... 145			11.6 ... 145				
S6	14.5 ... 145		8.7 ... 145									
S11	6.53 ... 145				3.63 ... 145							
R8, TT	–		21.76 ... 145			14.5 ... 145			–			
Ambient temperature1) [°C]												
–	–20 ... +80											
S6	0 ... +120											
S10, S11	+5 ... +80											
R3	–20 ... +80											
TT	–		–40 ... +80									–

1) Note operating range of proximity switches

Datasheet

Operating and environmental conditions											
Piston Ø	12	16	20	25	32	40	50	63	80	100	125
Corrosion resistance class CRC ¹⁾											
–	2 - Moderate corrosion stress										
R3	3 - High corrosion stress										
F1A	0 - no corrosion stress										
ATEX	Selected types → www.festo.com										

1) More information www.festo.com/x/topic/crc

Forces [N] and impact energy [J]											
Piston Ø	12	16	20	25	32	40	50	63	80	100	125
Theoretical force at 6 bar, advancing											
–	68	121	188	295	483	754	1178	1870	3016	4712	7363
S1	–	–	–	295	–	754	–	1870	–	4712	–
S2	51	90	141	247	415	686	1057	1750	2827	4524	7069
Theoretical force at 6 bar, retracting											
–	51	90	141	247	415	686	1057	1750	2827	4524	7069
S1	–	–	–	247	–	633	–	1681	–	4417	–
S2	51	90	141	247	415	686	1057	1750	2827	4524	7069
Max. impact energy in the end positions											
–	0.07	0.15	0.2	0.3	0.4	0.7	1	1.3	1.8	2.5	3.3
S1	–	–	–	0.3	–	0.7	–	1.3	–	2.5	–
S6, S10, S11, TT	0.035	0.075	0.1	0.15	0.2	0.35	0.5	0.65	0.9	1.25	1.75
K10	–	–	0.16	0.24	0.32	0.56	0.8	1	1.4	2	2.6
S20	–	0.016	0.024	0.083	0.15	0.39	0.48	0.62	0.8	0.9	0.95

 Note

These specifications represent the maximum values that can be achieved. The maximum permissible impact energy must be observed.

Permissible impact velocity:
$$V = \sqrt{\frac{2 \times E}{m_1 + m_2}}$$

V Permissible impact velocity
E Max. impact energy
m1 Moving mass (drive)
m2 Moving payload

Maximum permissible mass:
$$m_2 = \frac{2 \times E}{v^2} - m_1$$

 Note


The maximum impact energy is still maintained in combination with cushioning PPS.

Max. energy conversion capacity [J]

Piston Ø	20	25	32	40	50	63	80	100
For cushioning PPS	0.65	0.8	1	1.7	2.8	4.8	8	12

Max. transverse force F_q as a function of projection x


Ø 12 ... 63



— Ø 12
- - - Ø 16
- · - · - Ø 20

····· Ø 25
- · - · - Ø 32/40
- - - Ø 50/63

Ø 80 ... 125




- - - Ø 80/100
····· Ø 125
- - - Ø 125

Datasheet

Max. transverse force F_q as a function of projection x and lever arm a


Q – Square piston rod

Ø 12




- $a = 5 \text{ mm}$
- · - · - $a = 10 \text{ mm}$
- - - $a = 15 \text{ mm}$
- · · · · $a = 20 \text{ mm}$
- · - · - $a = 25 \text{ mm}$
- - - $a = 30 \text{ mm}$

Ø 16




- $a = 5 \text{ mm}$
- · - · - $a = 10 \text{ mm}$
- - - $a = 15 \text{ mm}$
- · · · · $a = 20 \text{ mm}$
- · - · - $a = 25 \text{ mm}$
- - - $a = 30 \text{ mm}$

Ø 20/25



- $a = 5 \text{ mm}$
- · - · - $a = 10 \text{ mm}$
- - - $a = 15 \text{ mm}$
- · · · · $a = 20 \text{ mm}$
- · - · - $a = 25 \text{ mm}$
- - - $a = 30 \text{ mm}$

Ø 32/40



- · - · - $a = 10 \text{ mm}$
- · · · · $a = 20 \text{ mm}$
- - - $a = 30 \text{ mm}$
- - - $a = 40 \text{ mm}$
- · - · - $a = 50 \text{ mm}$
- · - · - $a = 60 \text{ mm}$

 Note

- For cantilevers that are larger than those shown in the diagrams, torques on the piston rod must be ruled out.


- If $a = 0$, the corresponding transverse force line of the basic version of the ADN can be used (a page 15).

Datasheet

Max. transverse force F_q as a function of projection x and lever arm a


Q – Square piston rod

Ø 50/63




- a = 10 mm
- a = 20 mm
- a = 30 mm
- a = 40 mm
- a = 50 mm
- a = 60 mm

Ø 80/100



- a = 10 mm
- a = 20 mm
- a = 30 mm
- a = 40 mm
- a = 50 mm
- a = 60 mm

Ø 125



- a = 10 mm
- a = 20 mm
- a = 30 mm
- a = 40 mm
- a = 50 mm
- a = 60 mm

**Note**


- For cantilevers that are larger than those shown in the diagrams, torques on the piston rod must be ruled out.

- If $a = 0$, the corresponding transverse force line of the basic version of the ADN can be used (a page 15).

Datasheet

Max. transverse force F_q as a function of projection x

S1 – Reinforced piston rod



Weight [g]

Piston Ø	12	16	20	25	32	40	50	63	80	100	125
ADN-...											
Product weight with 0 mm stroke	64	75	128	181	265	361	531	755	1140	1741	2952
Additional weight per 10 mm stroke	12	14	22	26	29	38	51	60	80	99	116
Moving mass with 0 mm stroke	11	18	32	41	76	103	164	222	431	595	1020
Additional mass per 10 mm stroke	2	4	6	6	9	9	16	16	25	25	29
ADN-...-I											
Product weight with 0 mm stroke	62	71	119	172	240	318	489	713	1012	1605	2768
Additional weight per 10 mm stroke	12	14	22	26	29	38	51	60	80	99	116
Moving mass with 0 mm stroke	9	14	23	32	51	60	122	180	303	459	836
Additional mass per 10 mm stroke	2	4	6	6	9	9	16	16	25	25	29
ADN-...-S2											
Product weight with 0 mm stroke	68	83	144	200	294	389	582	805	1220	1830	3245
Additional weight per 10 mm stroke	15	18	29	33	38	47	68	76	105	123	156
Moving mass with 0 mm stroke	15	26	48	55	105	127	205	265	493	665	1308
Additional mass per 10 mm stroke	5	8	13	13	18	18	33	32	50	49	69
ADN-...-S20											
Product weight with 0 mm stroke	–	84	140	193	284	377	563	786	1162	1771	3076
Additional weight per 10 mm stroke	–	17	27	31	36	45	62	71	96	115	136
Moving mass with 0 mm stroke	–	22	42	48	96	115	186	245	435	606	1099
Additional mass per 10 mm stroke	–	7	11	11	16	16	27	27	41	41	49
ADN-...-Q											
Product weight with 0 mm stroke	65	78	132	180	270	361	537	749	1144	1741	2945
Additional weight per 10 mm stroke	12	14	22	26	28	37	46	55	75	94	108
Moving mass with 0 mm stroke	11	17	32	41	73	–	153	209	413	575	985
Additional mass per 10 mm stroke	2	4	6	6	8	8	11	11	20	20	21
ADN-...-S1											
Product weight with 0 mm stroke	–	–	–	183	–	394	–	886	–	2710	–
Additional weight per 10 mm stroke	–	–	–	26	–	44	–	68	–	136	–
Moving mass with 0 mm stroke	–	–	–	45	–	134	–	308	–	737	–
Additional mass per 10 mm stroke	–	–	–	6	–	15	–	24	–	38	–
ADN-...-PPS											
Product weight with 0 mm stroke	–	–	128	173	272	372	547	773	1162	1766	–
Additional weight per 10 mm stroke	–	–	22	26	29	38	51	60	80	99	–
Moving mass with 0 mm stroke	–	–	33	39	83	114	180	240	453	620	–
Additional mass per 10 mm stroke	–	–	6	6	9	9	16	16	25	25	–
ADN-...-TT/-R8											
Product weight with 0 mm stroke	–	–	133	181	280	380	561	786	1167	1768	–
Additional weight per 10 mm stroke	–	–	22	26	29	38	51	60	80	99	–
Moving mass with 0 mm stroke	–	–	35	44	82	109	175	234	447	612	–
Additional mass per 10 mm stroke	–	–	6	6	9	9	16	16	25	25	–


Datasheet

Weight [g]											
Piston Ø	12	16	20	25	32	40	50	63	80	100	125
ADN-...-K10											
Product weight with 0 mm stroke	–	–	131	183	281	373	562	780	1158	1754	2932
Additional weight per 10 mm stroke	–	–	18	22	23	29	40	48	61	80	86
Moving mass with 0 mm stroke	–	–	35	43	92	115	195	247	449	608	1000
Additional mass per 10 mm stroke	–	–	2	2	3	0	5	4	6	6	0
ADN-...-R3											
Product weight with 0 mm stroke	64	75	128	181	265	361	531	755	1301	2171	2952
Additional weight per 10 mm stroke	12	14	22	26	29	38	51	60	80	99	116
Moving mass with 0 mm stroke	11	18	32	41	76	103	164	222	431	595	1020
Additional mass per 10 mm stroke	2	4	6	6	9	9	16	16	25	25	29
ADN-...-K8											
Additional weight and mass per 10 mm piston rod extension	2	4	6	6	9	9	16	16	25	25	–
ADN-...-K2											
Additional weight and mass per 10 mm extended piston rod thread	2	2	4	4	6	6	9	9	16	16	–

Datasheet

Materials

Sectional view



Compact cylinder	Basic version, Q	R8	S6, S10, S11	R3	K10	F1A
[1] Cover						
ø 12 ... 63		Anodised aluminium				
ø 80 ... 125		Coated die-cast aluminium				
[2] Cylinder barrel		Anodised aluminium				
[3] Piston rod	High-alloy steel	Hard-chrome-plated tempered steel	High-alloy steel		Anodised aluminium	High-alloy steel
[4] Flange screws						
ø 12 ... 16		High-alloy steel		High-alloy steel	–	Steel, chemically nickel-plated
ø 20 ... 63		Galvanised steel		Tempered steel	Galvanised steel	
ø 80 ... 125		Standard screws, galvanised steel		Standard screws, high-alloy steel	Standard screws, galvanised steel	
–	Seals	Polyurethane		Fluoro rubber	Polyurethane	
Note on materials						
ADN-...		RoHS-compliant				
		LABS (PWIS) conformity: VDMA24364-B1/B2-L				
ø 12 ... 63		Cleanroom class 5 to ISO 14644-1				
ADN-...-S10/11		Contains paint-wetting impairment substances				
		LABS (PWIS) conformity: VDMA24364-Zone III				
ADN-...-F1A		Metals with copper, zinc or nickel as the main constituent are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils.				

Datasheet


Dimensions – Basic version

Download CAD data → www.festo.com

Ø 12 ... 63

Ø 80 ... 125

Ø 32 ... 63



+ = plus stroke length

[1] = Drilled hole for centring pin/sleeve






Ø	BG	D1 Ø	D5 Ø	E	EE	G	J2	J3	PW
[mm]	min.	H9							+0.2
12	17	9	6 ^{F9}	27.5 ^{+0.3}	M5	10.5	2	—	3.5
16				29 ^{+0.3}		11	2.6		
20	19.5		9 ^{F9}	35.5 ^{+0.3}		12			5
25				39.5 ^{+0.3}	G1/8	15	6		
32	26		47 ^{+0.3}	8					
40			54.5 ^{+0.3}	11.5					
50	27		12 ^{F9}	65.5 ^{+0.3}		16.5	20	2.6	
63				75.5 ^{+0.3}					
80	17	12	15	95.5 ^{+0.6}		21.5			
100	21.5			113.5 ^{+0.6}	G1/4	20			
125	20		—	134.6 ^{+0.3}					

ø [mm]	MM ø	PL	RT	ST	T2	TG	ZA	ZB	PPS
		+0.2		h13	+0.1	±0.2	±0.6	+1.2	+1.3
12	6	6	M4	5	2.1	16	35	39.2	–
16	8			7		18		39.7	
20	10		M5	9		22	37	42.5	42.5
25						26	39	44.5	45.3
32	12	8.2	M6	10	2.6	32.5	44	50	50.6
40						38	45	51.1	51.7
50	16		M8	13		46.5		49	52.7
63						56.5	56.5	57	
80	20	M10	17	72	54	62.9	63.4		
100				89	67	76	76.8		
125	25	10.5	M12	21		110	81	92	–

Datasheet

Dimensions – Variants Download CAD data → www.festo.com

Basic version





Datasheet

Dimensions – Variants

Download CAD data → www.festo.com

K8 – Extended piston rod





 **Note**

In combination with variants S2/S20, the piston rod thread is extended at one end

[1] Hex nut DIN 439-B
only with Ø 32 ... 125

+ = plus stroke length

R8 – Dust protection / TT – Low temperature



[1] Hex nut DIN 439-B
only with Ø 32 ... 125

+ = plus stroke length

ø	A	A1	A2	AF	AF5	B ø	D7 ø	D8	D9 ø	L5	KF	KF5	KK	
[mm]	−0.5			min.	min.									
12	10	1 ... 10	1 ... 300	8	−	−	−	−	−	−	M3	−	M5	
16	12			10			4.5		3.2	3	M4		M6	
20	16			1 ... 20	1 ... 400	14	12		18	6	3.8	2	M6	M5
25		19	16			14	27	8	4.5	3	M8	M6	M10x1.25	
32	22		20			16	31	10	6	3.5	M10	M8	M12x1.25	
40		28		1 ... 30	1 ... 500									20
50						40	1 ... 40	25	−	−	−	G1/4	11.7	
63														
80														
100														
125														



Ø [mm]	KK5	T3	T4	VD	WH			ZB			ZM		
					+1.3	PPS +1.4	R8/TT +1.3	+1.2	PPS +1.3	R8/TT +1.2		PPS	
12	M6	–	1.5	–	4.2	–	–	39.2	–	–	44.5 ^{+0.5}	–	
16	M8				4.7			39.7			45.7 ^{+0.5}		
20	M10x1.25	2	2.6	5.2	5.5	5.5	10.5	42.5	42.5	47.5	49.5 ^{+0.5}	49.5 ^{+0.5}	
25	M10							44.5	45.3	49.5	51.5 ^{+0.5}	51.5 ^{+0.5}	
32	M10	2.6	3.3	6.4	6	6.5	12.5	50	50.6	56.5	57.5 ^{+0.5}	58.6 ^{+0.6}	
40	M12				6.1	6.6		51.1	51.7	57.5	58.6 ^{+0.6}	59.7 ^{+0.7}	
50	M12	3.3	4.7		7.7	8.2	14.7	52.7	53.2	59.7	62.0 ^{+0.6}	63.1 ^{+0.7}	
63	M16				7.5	8	14.6	56.5	57	63.6	65.4 ^{+0.6}	66.5 ^{+0.7}	
80	M16	4.7	6.1		8.9	9.4	15.4	62.9	63.4	69.4	73.2 ^{+0.6}	74.3 ^{+0.7}	
100	M20x1.5 M20				9	9.8	15.5	76	76.8	82.5	86.4 ^{+0.6}	88 ^{+0.7}	
125	M20	–	7	–	11	–	–	92	–	–	104.4 ^{+0.6}	–	

Datasheet

Dimensions – Variants

Download CAD data → www.festo.com



Q – Square piston rod



[1] Hex nut DIN 439-B
only with Ø 32 ... 125

+ = plus stroke length

Q-S2 – Square, through piston rod




[1] Hex nut DIN 439-B
only with Ø 32 ... 125

+ = plus stroke length

++ = plus 2x stroke length

Q-S20 – Square, through, hollow piston rod





[1] Hex nut DIN 439-B
only with Ø 32 ... 125

+ = plus stroke length

++ = plus 2x stroke length

Q-K2 – Square piston rod with extended male thread




Note
In combination with
variants S2/S20, the piston
rod thread is extended at both
ends.

[1] Hex nut DIN 439-B
only with Ø 32 ... 125

+ = plus stroke length

Q-K5 – Square piston rod with special piston rod thread





+ = plus stroke length

Datasheet

Dimensions – Variants

Download CAD data → www.festo.com

Q-K8 – Square, extended piston rod


Note

In combination with variants S2/S20, the piston rod thread is extended at both ends.

[1] Hex nut DIN 439-B
only with Ø 32 ... 125

+ = plus stroke length



∅	A	A1	A2	AF	AF3	B1 □	D7 ∅	D8	D9 ∅
[mm]	−0.5			min.	min.				
12	10	1 ... 10	1 ... 300	8	8	5.5	–	–	–
16	12			10	10	7	4.5		3.2
20	16			14	12	9	6		3.8
25									
32	19	1 ... 20	1 ... 400	16	14	10	8		4.5
40				22	20	16	12	10	6
50									
63	28	1 ... 30	1 ... 500	20	20	16	–	G1/8	8
80				40	1 ... 40	25	24	20	G1/4
100									
125									

∅	L5	KF	KF3	KK	KK5	T2	T4	WH	ZB	ZM
[mm]								+1.3	+1.2	
12	–	M3	M3	M5	M6	1.5	1.5	4.2	39.2	44.5 ^{+0.5}
16	3	M4	M4	M6	M8			4.7	39.7	45.7 ^{+0.5}
20	2	M6	M5	M8	M10x1.25 M10	2	2.6	5.5	42.5	49.5 ^{+0.5}
25								5.5	44.5	51.5 ^{+0.5}
32	3	M8	M6	M10x1.25	M10	2.6	3.3	6	50	57.5 ^{+0.5}
40								6.1	51.1	58.6 ^{+0.6}
50	3.5	M10	M8	M12x1.25	M12	3.3	4.7	8.2	53.2	62.8 ^{+0.6}
63								8.1	57.1	66.6 ^{+0.6}
80	–	M12	M10	M16x1.5	M16	4.7	6.1	8.9	62.9	73.2 ^{+0.6}
100								9	76	86.4 ^{+0.6}
125		M16	M12	M20x1.5	M20	6.1	7	11	92	104.4 ^{+0.6}

Datasheet

Dimensions – Variants Download CAD data → www.festo.com

S1 – Reinforced piston rod
Ø 25



Ø	B Ø	BG	D1 Ø	E	EE	J3	PW	MM Ø	PL
[mm]	f8	min.	H9						
25	22	15	9	39.5 ^{+0.3}	M5	—	5	10	6
40	35	16		54.5 ^{+0.3}		15		16	8.2
63	42		12	75.5 ^{+0.3}	G1/8	23		20	
100	55	17		113.5 ^{+0.6}		40		25	10.5



Ø	RT	ST	T2	TG	VD	WH	ZA	ZB
[mm]		h13	+0.1	±0.2		+1.3	±0.6	+1.2
25	M5	9	2.1	26	6	11.8	39	50.9
40	M6	13		38	9.5	18	45	62.9
63	M8	17	2.6	56.5	12	21	49	70.2
100	M10	21		89	15.5	26.5	67	93.5

Datasheet

Dimensions – Variants

Download CAD data → www.festo.com


S1 – Reinforced piston rod



[1] Hex nut DIN 439-B
only with Ø 40 ... 100

+ = plus stroke length



S1-K2 – Reinforced piston rod with extended male piston rod thread



[1] Hex nut DIN 439-B
only with Ø 40 ... 100



+ = plus stroke length

S1-K5 – Reinforced piston rod with special piston rod thread



+ = plus stroke length

S1-K8 – Reinforced piston rod with piston rod extension



[1] Hex nut DIN 439-B
only with Ø 40 ... 100

+ = plus stroke length

Ø	A	A1	A2	AF	AF5	KF	KF5	KK	KK5	T3	T4	WH	ZB
[mm]	-0.5			min.	min.							+1.3	+1.2
25	16	1 ... 20	1 ... 300	14	12	M6	M5	M8	M10x1.25 M10	2	2.6	11.8	50.9
40	22		1 ... 400	20	16	M10	M8	M12x1.25	M10x1.25 M12	3.3	4.7	18	62.9
63	28				20	M12	M10	M16x1.5	M12x1.25 M16	4.7	6.1	21	70.2
100	40	1 ... 30	1 ... 500	25	–	M16	–	M20x1.5	M16x1.5 M20	–	7	26.5	93.5

Datasheet

Ordering data						
Type	Piston ø	Stroke	I – Piston rod with female thread P – Elastic cushioning rings/plates at both ends		A – Piston rod with male thread P – Elastic cushioning rings/plates at both ends	
	[mm]	[mm]	Part no.	Type	Part no.	Type
	12	5	536211	ADN-12-5-I-P-A	536204	ADN-12-5-A-P-A
		10	536212	ADN-12-10-I-P-A	536205	ADN-12-10-A-P-A
		15	536213	ADN-12-15-I-P-A	536206	ADN-12-15-A-P-A
		20	536214	ADN-12-20-I-P-A	536207	ADN-12-20-A-P-A
		25	536215	ADN-12-25-I-P-A	536208	ADN-12-25-A-P-A
		30	536216	ADN-12-30-I-P-A	536209	ADN-12-30-A-P-A
		35	8178328	ADN-12-35-I-P-A	8178327	ADN-12-35-A-P-A
		40	536217	ADN-12-40-I-P-A	536210	ADN-12-40-A-P-A
		50	8178550	ADN-12-50-I-P-A	8178548	ADN-12-50-A-P-A
		60	604883	ADN-12-60-I-P-A	8178549	ADN-12-60-A-P-A
	16	5	536226	ADN-16-5-I-P-A	536219	ADN-16-5-A-P-A
		10	536227	ADN-16-10-I-P-A	536220	ADN-16-10-A-P-A
		15	536228	ADN-16-15-I-P-A	536221	ADN-16-15-A-P-A
		20	536229	ADN-16-20-I-P-A	536222	ADN-16-20-A-P-A
		25	536230	ADN-16-25-I-P-A	536223	ADN-16-25-A-P-A
		30	536231	ADN-16-30-I-P-A	536224	ADN-16-30-A-P-A
		35	8178765	ADN-16-35-I-P-A	8178762	ADN-16-35-A-P-A
		40	536232	ADN-16-40-I-P-A	536225	ADN-16-40-A-P-A
		50	536341	ADN-16-50-I-P-A	536331	ADN-16-50-A-P-A
		60	8178766	ADN-16-60-I-P-A	8178763	ADN-16-60-A-P-A
	20	5	536242	ADN-20-5-I-P-A	536234	ADN-20-5-A-P-A
		10	536243	ADN-20-10-I-P-A	536235	ADN-20-10-A-P-A
		15	536244	ADN-20-15-I-P-A	536236	ADN-20-15-A-P-A
		20	536245	ADN-20-20-I-P-A	536237	ADN-20-20-A-P-A
		25	536246	ADN-20-25-I-P-A	536238	ADN-20-25-A-P-A
		30	536247	ADN-20-30-I-P-A	536239	ADN-20-30-A-P-A
		35	578011	ADN-20-35-I-P-A	8178859	ADN-20-35-A-P-A
		40	536248	ADN-20-40-I-P-A	536240	ADN-20-40-A-P-A
		50	536249	ADN-20-50-I-P-A	536241	ADN-20-50-A-P-A
		60	536362	ADN-20-60-I-P-A	536352	ADN-20-60-A-P-A
	25	5	536259	ADN-25-5-I-P-A	536251	ADN-25-5-A-P-A
		10	536260	ADN-25-10-I-P-A	536252	ADN-25-10-A-P-A
		15	536261	ADN-25-15-I-P-A	536253	ADN-25-15-A-P-A
		20	536262	ADN-25-20-I-P-A	536254	ADN-25-20-A-P-A
		25	536263	ADN-25-25-I-P-A	536255	ADN-25-25-A-P-A
		30	536264	ADN-25-30-I-P-A	536256	ADN-25-30-A-P-A
		35	608920	ADN-25-35-I-P-A	574647	ADN-25-35-A-P-A
		40	536265	ADN-25-40-I-P-A	536257	ADN-25-40-A-P-A
		50	536266	ADN-25-50-I-P-A	536258	ADN-25-50-A-P-A
		60	536383	ADN-25-60-I-P-A	536373	ADN-25-60-A-P-A
		70	8178880	ADN-25-70-I-P-A	8178877	ADN-25-70-A-P-A
		80	578450	ADN-25-80-I-P-A	576652	ADN-25-80-A-P-A

Datasheet

Ordering data					
Type	Piston ø	Stroke	I – Piston rod with female thread P – Elastic cushioning rings/plates at both ends	A – Piston rod with male thread P – Elastic cushioning rings/plates at both ends	
	[mm]	[mm]	Part no. Type	Part no. Type	
	32	5	536278 ADN-32-5-I-P-A	536268 ADN-32-5-A-P-A	
		10	536279 ADN-32-10-I-P-A	536269 ADN-32-10-A-P-A	
		15	536280 ADN-32-15-I-P-A	536270 ADN-32-15-A-P-A	
		20	536281 ADN-32-20-I-P-A	536271 ADN-32-20-A-P-A	
		25	536282 ADN-32-25-I-P-A	536272 ADN-32-25-A-P-A	
		30	536283 ADN-32-30-I-P-A	536273 ADN-32-30-A-P-A	
		35	8179019 ADN-32-35-I-P-A	576645 ADN-32-35-A-P-A	
		40	536284 ADN-32-40-I-P-A	536274 ADN-32-40-A-P-A	
		50	536285 ADN-32-50-I-P-A	536275 ADN-32-50-A-P-A	
		60	536286 ADN-32-60-I-P-A	536276 ADN-32-60-A-P-A	
		70	8173462 ADN-32-70-I-P-A	564092 ADN-32-70-A-P-A	
		80	536287 ADN-32-80-I-P-A	536277 ADN-32-80-A-P-A	
	40	5	536299 ADN-40-5-I-P-A	536289 ADN-40-5-A-P-A	
		10	536300 ADN-40-10-I-P-A	536290 ADN-40-10-A-P-A	
		15	536301 ADN-40-15-I-P-A	536291 ADN-40-15-A-P-A	
		20	536302 ADN-40-20-I-P-A	536292 ADN-40-20-A-P-A	
		25	536303 ADN-40-25-I-P-A	536293 ADN-40-25-A-P-A	
		30	536304 ADN-40-30-I-P-A	536294 ADN-40-30-A-P-A	
		35	8179033 ADN-40-35-I-P-A	8179031 ADN-40-35-A-P-A	
		40	536305 ADN-40-40-I-P-A	536295 ADN-40-40-A-P-A	
		50	536306 ADN-40-50-I-P-A	536296 ADN-40-50-A-P-A	
		60	536307 ADN-40-60-I-P-A	536297 ADN-40-60-A-P-A	
		70	8179034 ADN-40-70-I-P-A	582549 ADN-40-70-A-P-A	
		80	536308 ADN-40-80-I-P-A	536298 ADN-40-80-A-P-A	
	50	5	536320 ADN-50-5-I-P-A	536310 ADN-50-5-A-P-A	
		10	536321 ADN-50-10-I-P-A	536311 ADN-50-10-A-P-A	
		15	536322 ADN-50-15-I-P-A	536312 ADN-50-15-A-P-A	
		20	536323 ADN-50-20-I-P-A	536313 ADN-50-20-A-P-A	
		25	536324 ADN-50-25-I-P-A	536314 ADN-50-25-A-P-A	
		30	536325 ADN-50-30-I-P-A	536315 ADN-50-30-A-P-A	
		35	8178619 ADN-50-35-I-P-A	8178336 ADN-50-35-A-P-A	
		40	536326 ADN-50-40-I-P-A	536316 ADN-50-40-A-P-A	
		50	536327 ADN-50-50-I-P-A	536317 ADN-50-50-A-P-A	
		60	536328 ADN-50-60-I-P-A	536318 ADN-50-60-A-P-A	
		70	8178338 ADN-50-70-I-P-A	572851 ADN-50-70-A-P-A	
		80	536329 ADN-50-80-I-P-A	536319 ADN-50-80-A-P-A	
	63	10	536342 ADN-63-10-I-P-A	536332 ADN-63-10-A-P-A	
		15	536343 ADN-63-15-I-P-A	536333 ADN-63-15-A-P-A	
		20	536344 ADN-63-20-I-P-A	536334 ADN-63-20-A-P-A	
		25	536345 ADN-63-25-I-P-A	536335 ADN-63-25-A-P-A	
		30	536346 ADN-63-30-I-P-A	536336 ADN-63-30-A-P-A	
		35	8178659 ADN-63-35-I-P-A	8178283 ADN-63-35-A-P-A	
		40	536347 ADN-63-40-I-P-A	536337 ADN-63-40-A-P-A	
		50	536348 ADN-63-50-I-P-A	536338 ADN-63-50-A-P-A	
		60	536349 ADN-63-60-I-P-A	536339 ADN-63-60-A-P-A	
		70	8178285 ADN-63-70-I-P-A	8178284 ADN-63-70-A-P-A	
		80	536350 ADN-63-80-I-P-A	536340 ADN-63-80-A-P-A	

Datasheet

Ordering data						
Type	Piston ø	Stroke	I – Piston rod with female thread P – Elastic cushioning rings/plates at both ends		A – Piston rod with male thread P – Elastic cushioning rings/plates at both ends	
	[mm]	[mm]	Part no.	Type	Part no.	Type
	80	10	536363	ADN-80-10-I-P-A	536353	ADN-80-10-A-P-A
		15	536364	ADN-80-15-I-P-A	536354	ADN-80-15-A-P-A
		20	536365	ADN-80-20-I-P-A	536355	ADN-80-20-A-P-A
		25	536366	ADN-80-25-I-P-A	536356	ADN-80-25-A-P-A
		30	536367	ADN-80-30-I-P-A	536357	ADN-80-30-A-P-A
		40	536368	ADN-80-40-I-P-A	536358	ADN-80-40-A-P-A
		50	536369	ADN-80-50-I-P-A	536359	ADN-80-50-A-P-A
		60	536370	ADN-80-60-I-P-A	536360	ADN-80-60-A-P-A
		80	536371	ADN-80-80-I-P-A	536361	ADN-80-80-A-P-A
	100	10	536384	ADN-100-10-I-P-A	536374	ADN-100-10-A-P-A
		15	536385	ADN-100-15-I-P-A	536375	ADN-100-15-A-P-A
		20	536386	ADN-100-20-I-P-A	536376	ADN-100-20-A-P-A
		25	536387	ADN-100-25-I-P-A	536377	ADN-100-25-A-P-A
		30	536388	ADN-100-30-I-P-A	536378	ADN-100-30-A-P-A
		40	536389	ADN-100-40-I-P-A	536379	ADN-100-40-A-P-A
		50	536390	ADN-100-50-I-P-A	536380	ADN-100-50-A-P-A
		60	536391	ADN-100-60-I-P-A	536381	ADN-100-60-A-P-A
		80	536392	ADN-100-80-I-P-A	536382	ADN-100-80-A-P-A

Datasheet

Ordering data					
Type	Piston ø	Stroke	I – Piston rod with female thread		A – Piston rod with male thread
	[mm]	[mm]	PPS – Pneumatic cushioning, self-adjusting at both ends		PPS – Pneumatic cushioning, self-adjusting at both ends
			Part no.	Type	Part no. Type
	20	10	577158	ADN-20-10-I-PPS-A	577166 ADN-20-10-A-PPS-A
		15	577159	ADN-20-15-I-PPS-A	577167 ADN-20-15-A-PPS-A
		20	577160	ADN-20-20-I-PPS-A	577168 ADN-20-20-A-PPS-A
		25	577161	ADN-20-25-I-PPS-A	577169 ADN-20-25-A-PPS-A
		30	577162	ADN-20-30-I-PPS-A	577170 ADN-20-30-A-PPS-A
		35	8178865	ADN-20-35-I-PPS-A	8178863 ADN-20-35-A-PPS-A
		40	577163	ADN-20-40-I-PPS-A	577171 ADN-20-40-A-PPS-A
		50	577164	ADN-20-50-I-PPS-A	577172 ADN-20-50-A-PPS-A
		60	577165	ADN-20-60-I-PPS-A	577173 ADN-20-60-A-PPS-A
		70	8178866	ADN-20-70-I-PPS-A	593451 ADN-20-70-A-PPS-A
	25	10	577174	ADN-25-10-I-PPS-A	577182 ADN-25-10-A-PPS-A
		15	577175	ADN-25-15-I-PPS-A	577183 ADN-25-15-A-PPS-A
		20	577176	ADN-25-20-I-PPS-A	577184 ADN-25-20-A-PPS-A
		25	577177	ADN-25-25-I-PPS-A	577185 ADN-25-25-A-PPS-A
		30	577178	ADN-25-30-I-PPS-A	577186 ADN-25-30-A-PPS-A
		35	8178885	ADN-25-35-I-PPS-A	8178882 ADN-25-35-A-PPS-A
		40	577179	ADN-25-40-I-PPS-A	577187 ADN-25-40-A-PPS-A
		50	577180	ADN-25-50-I-PPS-A	577188 ADN-25-50-A-PPS-A
		60	577181	ADN-25-60-I-PPS-A	577189 ADN-25-60-A-PPS-A
		70	8178886	ADN-25-70-I-PPS-A	8178883 ADN-25-70-A-PPS-A
		80	8178887	ADN-25-80-I-PPS-A	8178884 ADN-25-80-A-PPS-A
	32	10	572646	ADN-32-10-I-PPS-A	572655 ADN-32-10-A-PPS-A
		15	572647	ADN-32-15-I-PPS-A	572656 ADN-32-15-A-PPS-A
		20	572648	ADN-32-20-I-PPS-A	572657 ADN-32-20-A-PPS-A
		25	572649	ADN-32-25-I-PPS-A	572658 ADN-32-25-A-PPS-A
		30	572650	ADN-32-30-I-PPS-A	572659 ADN-32-30-A-PPS-A
		35	8179023	ADN-32-35-I-PPS-A	8179021 ADN-32-35-A-PPS-A
		40	572651	ADN-32-40-I-PPS-A	572660 ADN-32-40-A-PPS-A
		50	572652	ADN-32-50-I-PPS-A	572661 ADN-32-50-A-PPS-A
		60	572653	ADN-32-60-I-PPS-A	572662 ADN-32-60-A-PPS-A
		70	8179024	ADN-32-70-I-PPS-A	8179022 ADN-32-70-A-PPS-A
		80	572654	ADN-32-80-I-PPS-A	572663 ADN-32-80-A-PPS-A
	40	10	572664	ADN-40-10-I-PPS-A	572673 ADN-40-10-A-PPS-A
		15	572665	ADN-40-15-I-PPS-A	572674 ADN-40-15-A-PPS-A
		20	572666	ADN-40-20-I-PPS-A	572675 ADN-40-20-A-PPS-A
		25	572667	ADN-40-25-I-PPS-A	572676 ADN-40-25-A-PPS-A
		30	572668	ADN-40-30-I-PPS-A	572677 ADN-40-30-A-PPS-A
		35	8179037	ADN-40-35-I-PPS-A	8179035 ADN-40-35-A-PPS-A
		40	572669	ADN-40-40-I-PPS-A	572678 ADN-40-40-A-PPS-A
		50	572670	ADN-40-50-I-PPS-A	572679 ADN-40-50-A-PPS-A
		60	572671	ADN-40-60-I-PPS-A	572680 ADN-40-60-A-PPS-A
		70	8179038	ADN-40-70-I-PPS-A	8179036 ADN-40-70-A-PPS-A
		80	572672	ADN-40-80-I-PPS-A	572681 ADN-40-80-A-PPS-A

Datasheet

Ordering data						
Type	Piston ø	Stroke	I – Piston rod with female thread PPS – Pneumatic cushioning, self-adjusting at both ends		A – Piston rod with male thread PPS – Pneumatic cushioning, self-adjusting at both ends	
	[mm]	[mm]	Part no.	Type	Part no.	Type
	50	10	572682	ADN-50-10-I-PPS-A	572691	ADN-50-10-A-PPS-A
		15	572683	ADN-50-15-I-PPS-A	572692	ADN-50-15-A-PPS-A
		20	572684	ADN-50-20-I-PPS-A	572693	ADN-50-20-A-PPS-A
		25	572685	ADN-50-25-I-PPS-A	572694	ADN-50-25-A-PPS-A
		30	572686	ADN-50-30-I-PPS-A	572695	ADN-50-30-A-PPS-A
		35	8178620	ADN-50-35-I-PPS-A	8178339	ADN-50-35-A-PPS-A
		40	572687	ADN-50-40-I-PPS-A	572696	ADN-50-40-A-PPS-A
		50	572688	ADN-50-50-I-PPS-A	572697	ADN-50-50-A-PPS-A
		60	572689	ADN-50-60-I-PPS-A	572698	ADN-50-60-A-PPS-A
		70	8178341	ADN-50-70-I-PPS-A	8178340	ADN-50-70-A-PPS-A
		80	572690	ADN-50-80-I-PPS-A	572699	ADN-50-80-A-PPS-A
	63	10	572700	ADN-63-10-I-PPS-A	572709	ADN-63-10-A-PPS-A
		15	572701	ADN-63-15-I-PPS-A	572710	ADN-63-15-A-PPS-A
		20	572702	ADN-63-20-I-PPS-A	572711	ADN-63-20-A-PPS-A
		25	572703	ADN-63-25-I-PPS-A	572712	ADN-63-25-A-PPS-A
		30	572704	ADN-63-30-I-PPS-A	572713	ADN-63-30-A-PPS-A
		35	609539	ADN-63-35-I-PPS-A	610152	ADN-63-35-A-PPS-A
		40	572705	ADN-63-40-I-PPS-A	572714	ADN-63-40-A-PPS-A
		50	572706	ADN-63-50-I-PPS-A	572715	ADN-63-50-A-PPS-A
		60	572707	ADN-63-60-I-PPS-A	572716	ADN-63-60-A-PPS-A
		70	609538	ADN-63-70-I-PPS-A	8178287	ADN-63-70-A-PPS-A
		80	572708	ADN-63-80-I-PPS-A	572717	ADN-63-80-A-PPS-A

Datasheet

Ordering data						
Type	Piston ø	Stroke	I – Piston rod with female thread PPS – Pneumatic cushioning, self-adjusting at both ends		A – Piston rod with male thread PPS – Pneumatic cushioning, self-adjusting at both ends	
	[mm]	[mm]	Part no.	Type	Part no.	Type
	80	10	572718	ADN-80-10-I-PPS-A	572727	ADN-80-10-A-PPS-A
		15	572719	ADN-80-15-I-PPS-A	572728	ADN-80-15-A-PPS-A
		20	572720	ADN-80-20-I-PPS-A	572729	ADN-80-20-A-PPS-A
		25	572721	ADN-80-25-I-PPS-A	572730	ADN-80-25-A-PPS-A
		30	572722	ADN-80-30-I-PPS-A	572731	ADN-80-30-A-PPS-A
		40	572723	ADN-80-40-I-PPS-A	572732	ADN-80-40-A-PPS-A
		50	572724	ADN-80-50-I-PPS-A	572733	ADN-80-50-A-PPS-A
		60	572725	ADN-80-60-I-PPS-A	572734	ADN-80-60-A-PPS-A
		80	572726	ADN-80-80-I-PPS-A	572735	ADN-80-80-A-PPS-A
	100	15	577191	ADN-100-15-I-PPS-A	577200	ADN-100-15-A-PPS-A
		20	577192	ADN-100-20-I-PPS-A	577201	ADN-100-20-A-PPS-A
		25	577193	ADN-100-25-I-PPS-A	577202	ADN-100-25-A-PPS-A
		30	577194	ADN-100-30-I-PPS-A	577203	ADN-100-30-A-PPS-A
		40	577195	ADN-100-40-I-PPS-A	577204	ADN-100-40-A-PPS-A
		50	577196	ADN-100-50-I-PPS-A	577205	ADN-100-50-A-PPS-A
		60	577197	ADN-100-60-I-PPS-A	577206	ADN-100-60-A-PPS-A
		80	577198	ADN-100-80-I-PPS-A	577207	ADN-100-80-A-PPS-A

Ordering data – Modular product system, basic version and variants

Ordering table									
Size	12	16	20	25	32	40	Conditions	Code	Enter code
Module no.	536203	536218	536233	536250	536267	536288			
Function	Compact cylinder, double-acting							ADN	ADN
Standard	Based on ISO 21287		Conforms to ISO 21287						
Piston Ø [mm]	12	16	20	25	32	40		-...	
Stroke [mm]	1 ... 300				1 ... 400		[10]	-...	
Piston rod thread	Male thread							-A	
	Female thread						[1]	-I	
Cushioning	Elastic cushioning rings/plates at both ends							-P	
	—		Pneumatic cushioning, self-adjusting at both ends				[8]	-PPS	
Position sensing	Via proximity switch							-A	-A

[1] I Not with piston rod type S20.

Not with extended male thread K2

[8] PPS Not with improved running performance K10, temperature resistance S6, low temperature TT, scraper R8
Minimum stroke 5 mm

[10] Stroke Minimum stroke 5 mm with a combination of piston rod thread I and piston rod type S2

Ordering data – Modular product system, basic version and variants

Ordering table									
Size	12	16	20	25	32	40	Conditions	Code	Enter code
Piston rod type	Through piston rod						[2]	-S2	
	–	Through, hollow piston rod					[2]	-S20	
[mm]	1 ... 300				1 ... 400				
Extended male thread [mm]	Extended male piston rod thread 1 ... 101 ... 20							-...K2	
Special piston rod thread	Male thread	M6	M8	M10x1.25 M10	M10x1.25 M10	M10 M12	M10 M12	-“...”K5	
	Female thread	–	–	M5	M5	M6	M6		
Extended piston rod [mm]	Extended piston rod 1 ... 3001 ... 400						[3]	-...K8	
Improved running performance	–	–	Smooth anodised aluminium piston rod				[4]	-K10	
Temperature resistance	Heat-resistant seals max. 120 °C							-S6	
Corrosion protection	High corrosion protection						[5]	-R3	
Captive rating plate	Laser-etched rating plate							-TL	
Low temperature [°C]	–	–	–40 ... +80				[6][7]	-TT	
Scraper	–	–	Dust protection				[6]	-R8	
Special material properties	Without								
	Recommended for production systems for manufacturing lithium-ion batteries						[9]	-F1A	

[2] S2, S20 Not with improved running performance K10.

Not with corrosion protection R3.

Not with scraper R8

[3] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[4] K10 Not with extended male thread K2.

Not with special piston rod thread K5.

Not with corrosion protection R3

[5] R3 Not with captive rating plate TL


Not with scraper R8

[6] TT, R8 Not with improved running performance K10.

Not with temperature resistance S6

[7] TT Not with scraper R8

[9] F1A Not with S6, S20, K10, R3, TL, TT, R8, PPS

**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

Ordering data – Modular product system, basic version and variants

Ordering table								
Size	50	63	80	100	125	Conditions	Code	Enter code
Module no.	536309	536330	536351	536372	536393			
Function	Compact cylinder, double-acting						ADN	ADN
Standard	Conforms to ISO 21287				Based on ISO 21287			
Piston Ø [mm]	50	63	80	–	–		-...	
	–	–	–	100	125		-...	
Stroke [mm]	1 ... 400		1 ... 500			[10]	-...	
Piston rod thread	Male thread						-A	
	Female thread					[1]	-I	
Cushioning	Elastic cushioning rings/plates at both ends						-P	
	Pneumatic cushioning, self-adjusting at both ends				–	[8]	-PPS	
Position sensing	Via proximity switch						-A	-A

[1] I Not with piston rod type S20.
Not with extended male thread K2

[8] PPS Not with improved running performance K10, temperature resistance S6, low temperature TT, scraper R8
Minimum stroke 5 mm

[10] Stroke Minimum stroke 5 mm with a combination of piston rod thread I and piston rod type S2

Ordering data – Modular product system, basic version and variants

Ordering table								
Size	50	63	80	100	125	Conditions	Code	Enter code
Piston rod type	Through piston rod					[2]	-S2	
	Through, hollow piston rod					[2]	-S20	
[mm]	1 ... 400		1 ... 500					
Extended male thread	Extended male piston rod thread							
[mm]	1 ... 20		1 ... 30		1 ... 40		-...K2	
Special piston rod thread	Male thread	M12 M16	M12 M16	M16 M20 M20x1.5	M16 M20 M20x1.5	M20	-“...”K5	
	Female thread	M8	M8	M10	M10	—		
Extended piston rod	Extended piston rod							
[mm]	1 ... 400		1 ... 500			[3]	-...K8	
Improved running performance	Smooth anodised aluminium piston rod					[4]	-K10	
[mm]	2 ... 400		5 ... 400	5 ... 500				
Temperature resistance	Heat-resistant seals max. 120 °C						-S6	
Corrosion protection	High corrosion protection					[5]	-R3	
Captive rating plate	Laser-etched rating plate						-TL	
Low temperature	-40 ... +80				—	[6][7]	-TT	
Scraper	Dust protection				—	[6]	-R8	
Special material properties	Without							
	Recommended for production systems for manufacturing lithium-ion batteries					[9]	-F1A	

[2] S2, S20 Not with improved running performance K10.

Not with corrosion protection R3.

Not with scraper R8

[3] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[4] K10 Not with extended male thread K2.

Not with special piston rod thread K5.

Not with corrosion protection R3

[5] R3 Not with captive rating plate TL


Not with scraper R8

[6] TT, R8 Not with improved running performance K10.

Not with temperature resistance S6

[7] TT Not with scraper R8

[9] F1A Not with S6, S20, K10, R3, TL, TT, R8, PPS

**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

Ordering data – Modular product system, S10 – constant motion, S11 – low friction

Ordering table										
Size	12	16	20	25	32	40	Conditions	Code	Enter code	
Module no.	536203	536218	536233	536250	536267	536288				
Function	Compact cylinder, double-acting							ADN		ADN
Standard	Based on ISO 21287		Conforms to ISO 21287							
Piston Ø [mm]	12	16	20	25	32	40		-...		
Stroke [mm]	1 ... 300				1 ... 400			-...		
Piston rod thread	Male thread							-A		
	Female thread						[1]	-I		
Cushioning	Elastic cushioning rings/plates at both ends							-P		-P
Position sensing	Via proximity switch							-A		-A
Extended male thread [mm]	Extended male piston rod thread							-...K2		
Special piston rod thread	Male thread		1 ... 10						-“...”K5	
	Female thread		1 ... 20							
	M6	M8	M10x1.25 M10	M10x1.25 M10	M10 M12	M10 M12				
	–	–	M5	M5	M6	M6				
Extended piston rod [mm]	Extended piston rod						[2]	-...K8		
	1 ... 300				1 ... 400					
Improved running performance	–	–	Smooth anodised aluminium piston rod				[3]	-K10		
Constant motion	Slow speed (constant motion at low piston speeds)						[4]	-S10		
	Restricted stroke									
[mm]	20 ... 300				20 ... 400					
Low friction	Low friction						[5]	-S11		
Corrosion protection	High corrosion protection						[6]	-R3		
Captive rating plate	Laser-etched rating plate							-TL		

[1] I Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[3] K10 Not with extended male thread K2
Not with special piston rod thread K5
Not with corrosion protection R3

[4] S10 Not with low friction S11

[5] S11 Not with constant motion S10

[6] R3 Not with captive rating plate TL

**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

Ordering data – Modular product system, S10 – constant motion, S11 – low friction

Ordering table								
Size	50	63	80	100	125	Conditions	Code	Enter code
Module no.	536309	536330	536351	536372	536393			
Function	Compact cylinder, double-acting						ADN	ADN
Standard	Conforms to ISO 21287				Based on ISO 21287			
Piston Ø [mm]	50	63	80	100	125		-...	
Stroke [mm]	1 ... 400		1 ... 500				-...	
Piston rod thread	Male thread						-A	
	Female thread					[1]	-I	
Cushioning	Elastic cushioning rings/plates at both ends						-P	-P
Position sensing	Via proximity switch						-A	-A
Extended male thread [mm]	Extended male piston rod thread						-...K2 -“...”K5	
Special piston rod thread	Male thread	M12 M16	M12 M16	M16 M20 M20x1.5	M16 M20 M20x1.5	M20		
	Female thread	M8	M8	M10	M10	—		
Extended piston rod [mm]	Extended piston rod		1 ... 400 1 ... 500			[2]	-...K8	
Improved running performance	Smooth anodised aluminium piston rod					[3]	-K10	
[mm]	2 ... 400	5 ... 400	5 ... 500					
Constant motion	Slow speed (constant motion at low piston speeds)					[4]	-S10	
[mm]	Restricted stroke		20 ... 400 20 ... 500					
Low friction	Low friction					[5]	-S11	
Corrosion protection	High corrosion protection					[6]	-R3	
Captive rating plate	Laser-etched rating plate						-TL	

[1] I Not with extended male thread K2


[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[3] K10 Not with extended male thread K2
Not with special piston rod thread K5
Not with corrosion protection R3

[4] S10 Not with low friction S11

[5] S11 Not with constant motion S10

[6] R3 Not with captive rating plate TL

**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

Ordering data – Modular product system, Q – Square piston rod, non-rotating

Ordering table										
Size	12	16	20	25	32	40	Conditions	Code		Enter code
Module no.	536203	536218	536233	536250	536267	536288				
Function	Compact cylinder, double-acting							ADN	ADN	
Standard	Based on ISO 21287		Conforms to ISO 21287							
Piston Ø [mm]	12	16	20	25	32	40		-...		
Stroke [mm]	1 ... 300				1 ... 400		[10]	-...		
Piston rod thread	Male thread							-A		
	Female thread						[1]	-I		
Cushioning	Elastic cushioning rings/plates at both ends							-P		-P
Position sensing	Via proximity switch							-A		-A
Protection against rotation	Square piston rod							-Q		-Q
Piston rod type	Through piston rod							-S2		
	–	Through, hollow piston rod						-S20		
	[mm]		Restricted stroke 1 ... 200				1 ... 300			
Extended male thread [mm]	Extended male piston rod thread 1 ... 10 1 ... 20							-...K2		
Special piston rod thread	Male thread	M6	M8	M10x1.25 M10	M10x1.25 M10	M10	M10	-“...”K5		
Extended piston rod [mm]	Extended piston rod 1 ... 300				1 ... 400		[2]	-...K8		
Temperature resistance	Heat-resistant seals max. 120 °C							-S6		
Corrosion protection	High corrosion protection						[3]	-R3		
Captive rating plate	Laser-etched rating plate							-TL		

[1] I Not with piston rod type S20.

Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[3] R3 Not with captive rating plate TL

[10] Stroke Minimum stroke 5 mm with a combination of piston rod thread I and piston rod type S2

**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

Ordering data – Modular product system, Q – Square piston rod, non-rotating

Ordering table								
Size	50	63	80	100	125	Conditions	Code	Enter code
Module no.	536309	536330	536351	536372	536393			
Function	Compact cylinder, double-acting						ADN	ADN
Standard	Conforms to ISO 21287				Based on ISO 21287			
Piston Ø [mm]	50	63	80	100	125		-...	
Stroke [mm]	1 ... 400		1 ... 500				-...	
Piston rod thread	Male thread						-A	
	Female thread					[1]	-I	
Cushioning	Elastic cushioning rings/plates at both ends						-P	-P
Position sensing	Via proximity switch						-A	-A
Protection against rotation	Square piston rod						-Q	-Q
Piston rod type	Through piston rod						-S2	
	Through, hollow piston rod						-S20	
	Restricted stroke							
[mm]	1 ... 300		1 ... 400					
Extended male thread	Extended male piston rod thread						-...K2	
[mm]	1 ... 20		1 ... 30		1 ... 40			
Special piston rod thread	Male thread	M12	M12	M16	M16	M20	-“...”K5	
Extended piston rod	Extended piston rod						-...K8	
[mm]	1 ... 400		1 ... 500			[2]		
Temperature resistance	Heat-resistant seals max. 120 °C						-S6	
Corrosion protection	High corrosion protection					[3]	-R3	
Captive rating plate	Laser-etched rating plate						-TL	

[1] I Not with piston rod type S20.

Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

[3] R3 Not with captive rating plate TL

**Note**

NSF-H1 lubricants are used in combination with R3 and in combination with R3 and K2, K5 or K8.

Ordering data – Modular product system, S1 – Reinforced piston rod

Ordering table								
Size	25	40	63	100	Conditions	Code	Enter code	
Module no.	536250	536288	536330	536372				
Function	Compact cylinder, double-acting					ADN	ADN	
Standard	Conforms to ISO 21287							
Piston Ø [mm]	25	40	63	100		-...		
Stroke [mm]	5 ... 300	10 ... 400		10 ... 500		-...		
Piston rod thread	Male thread					-A		
	Female thread				[1]	-I		
Cushioning	Elastic cushioning rings/plates at both ends					-P	-P	
Position sensing	Via proximity switch					-A	-A	
Extended male thread [mm]	Extended male piston rod thread 1 ... 20			1 ... 30		-...K2		
Special piston rod thread	Male thread	M10x1.25 M10	M10x1.25 M12	M12x1.25 M16	M16x1.5 M20	-“...”K5		
	Female thread	M5	M8	M10	—			
Extended piston rod [mm]	Extended piston rod 1 ... 300		1 ... 400		1 ... 500	[2]	-...K8	
Temperature resistance	Heat-resistant seals max. 120 °C					-S6		
Increased transverse force	Reinforced piston rod or extended piston rod bearing					-S1	-S1	
Captive rating plate	Laser-etched rating plate					-TL		

[1] I Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Type codes

001	Series	
ADN	Compact cylinder, double-acting, based on ISO 21287	

002	Piston diameter	
20	20	
25	25	
32	32	
40	40	
50	50	
63	63	
80	80	
100	100	

003	Stroke	
...	10 ... 500	

004	Clamping unit	
KP	Attached	

005	Piston rod thread type	
A	Male thread	
I	Female thread	

006	Cushioning	
P	Elastic cushioning rings/plates on both sides	

007	Position sensing	
A	For proximity sensor	

008	Piston rod thread extension	
	None	
...K2	1 ... 30 mm	

009	Custom thread	
"M6"K5	M6	
"M8"K5	M8	
"M10"K5	M10	
"M10x-1,25"K5	M10x1.25	
"M12"K5	M12	
"M16"K5	M16	
"M20x-1,5"K5	M20x1.5	
"M5"K5	M5	
"M20"K5	M20	


010	Piston rod extension	
	None	
...K8	1 ... 500 mm	

011	Captive rating plate	
	Rating plate, glued	
TL	Laser etched rating plate	

Compact cylinders ADN-KP, standard hole pattern, with clamping unit

Datasheet

Function



Variants



K2



K5



K8



⌀ - Diameter
20 ... 100 mm

└ - Stroke length
10 ... 500 mm



Note

Additional measures are required for use in safety-related applications; in Europe, for example, the standards listed under the EC Machinery Directive must be observed.

Without additional measures in accordance with legally specified minimum requirements, the product is not suitable as a safety-related component in control systems.

General technical data

Piston Ø	20	25	32	40	50	63	80	100
Pneumatic connection								
Cylinders	M5	M5	G1/8	G1/8	G1/8	G1/8	G1/8	G1/8
KP	M5	M5	M5	G1/8	G1/8	G1/8	G1/8	G1/8
Female piston rod thread								
–	M6		M8		M10		M12	
K5	M5		M6		M8		M10	
Male piston rod thread								
–	M8		M10x1.25		M12x1.25		M16x1.5	
K5	M10; M10x1.25		M10; M12		M12; M16		M16; M20; M20x1.5	
Axial backlash under load	[mm]	0.5			0.8			
Design	Piston							
	Piston rod							
	Cylinder barrel							
Cushioning	Elastic cushioning rings/plates at both ends							
Position sensing	Via proximity switch							
Type of mounting	With through-hole							
	With female thread							
	With accessories							
Mounting position	Any							
Clamping type with operating direction	At both ends							

Operating and environmental conditions

Operating and environmental conditions		
Operating medium		Compressed air to ISO 8573-1:2010 [7:4:4]
Note on the operating/ pilot medium		Lubricated operation possible (in which case lubricated operation will always be required)
Operating pressure	[MPa]	0.15 ... 1
	[bar]	1.5 ... 10
	[psi]	21.76 ... 145
Min. release pressure	[MPa]	0.3
	[bar]	3
	[psi]	43.5
Ambient temperature ¹⁾	[°C]	−10 ... +80
Corrosion resistance class CRC ²⁾		2 - Moderate corrosion stress

1) Note operating range of proximity switches

2) More information www.festo.com/x/topic/crc

Datasheet

Impact energy [J]								
Piston Ø	20	25	32	40	50	63	80	100
Max. impact energy in the end positions	0.2	0.3	0.4	0.7	1	1.3	1.8	2.5

**Note**

These specifications represent the maximum values that can be achieved. The maximum permissible impact energy must be observed.

Permissible impact velocity:
$$V = \sqrt{\frac{2 \times E}{m_1 + m_2}}$$

Maximum permissible mass:

$$m_2 = \frac{2 \times E}{V^2} - m_1$$

V Permissible impact velocity
E Max. impact energy
m1 Moving mass (drive)
m2 Moving payload

Forces [N]								
Piston Ø	20	25	32	40	50	63	80	100
Theoretical force at 6 bar, advancing	188	295	483	754	1178	1870	3016	4712
Theoretical force at 6 bar, retracting	141	247	415	633	990	1682	2721	4418
Static holding force	350	350	600	1000	1400	2000	5000	5000

**Note:**


The specified holding force refers to a static load. If this value is exceeded, slippage may occur. Dynamic forces occurring during operation must

not exceed the static holding force. The clamping unit is not backlash-free in the clamped condition if varying loads are applied to the piston rod

Actuation

The clamping unit may only be released if the forces at the piston have reached equilibrium. Otherwise, there is a risk of accidents due to sudden movement of the piston rod.

Blocking off the compressed air supply at both ends (e.g. with a 5/3-way valve) does not provide any safety.


Max. transverse force F_q as a function of projection x

Weight [g]								
Piston Ø	20	25	32	40	50	63	80	100
Product weight with 0 mm stroke	282	344	503	789	1268	1894	3973	5497
Additional weight per 10 mm stroke	22	26	29	45	60	68	93	112
Moving mass with 0 mm stroke	53	63	100	173	296	368	755	932
Additional mass per 10 mm stroke	6	6	9	16	25	25	39	39

Datasheet

Materials

Sectional view




Compact cylinder		
[1]	Cover	Anodised aluminium
[2]	Cylinder barrel	Anodised aluminium
[3]	Piston rod	High-alloy steel
[4]	Flange screws	Ø 20 ... 63 Galvanised steel
		Ø 80 ... 100 Standard screws, galvanised steel
–	Seals	Polyurethane, nitrile rubber
	Note on materials	RoHS-compliant

Datasheet

Dimensions – Basic version


Download CAD data → www.festo.com

Ø 20 ... 63



Ø 20 ... 25

Only direct mounting is possible with this variant.




+ = plus stroke length


Dimensions – Basic version

Download CAD data → www.festo.com

Ø 80, 100



Only direct mounting is possible with this variant.



+ = plus stroke length


Ø [mm]	BG min.	D1 Ø H9	D2 Ø	D5 Ø	E	E1	EE	G	G1	H1	J2
20	19.5	9	20	9 ^{F9}	35.5 ^{+0.3}	M5	M5	49.8	12	63	2.6
25					39.5 ^{+0.3}			50.6		65	
32					47 ^{+0.3}			56.4		68	
40	26	12	24	12 ^{F9}	54.5 ^{+0.3}	G1/8	G1/8	60.4	15	89	8
50					65.5 ^{+0.3}			67.4		108	
63					75.5 ^{+0.3}			76.8		120	
80	17	12	38	15	95.5 ^{+0.6}			99	16.5	167	11.5
100	21.5				113.5 ^{+0.6}			99.6		176	

ø	PW	MM ø	PL	PL1	RT	ST	T2	TG	ZA	ZB
[mm]	+0.2		+0.2	+0.2		h13	+0.2	±0.2	±0.6	+1.2
20	5	10	42.8	6	M5	9	2.1	22	74.8	80.8
25			44.6					26	77.6	83.1
32		12	49.6	M6	10	32.5		85.4	91.4	
40			16		53.6	13		38	90.4	96.5
50		20	60.6	8.2	M8	17		46.5	97.4	105.6
63	70		56.5				110.8	118.9		
80	2.6		25		90.7	M10	21	72	136.5	145.4
100		88.6		10.5	89			145.1	154.1	

Datasheet

Dimensions – Variants Download CAD data → www.festo.com


Basic version



[1] Hex nut DIN 439-B
only with Ø 32 ... 100

+ = plus stroke length


K2 – Extended male piston rod thread



[1] Hex nut DIN 439-B
only with Ø 32 ... 100


+ = plus stroke length

K5 – Special piston rod thread



+ = plus stroke length

K8 – Extended piston rod



[1] Hex nut DIN 439-B
only with Ø 32 ... 100

+ = plus stroke length

Datasheet

∅	A	A1	A2	AF	AF5	KF	KF5		
[mm]	−0.5			min.	min.				
20	16	1 ... 20	1 ... 300	14	12	M6	M5		
25			1 ...400	16	14	M8	M6		
32	22				20	16	M10	M8	
40						28	1 ... 30	1 ... 500	20
50									
63									
80									
100									

∅	KK	KK5	T3	T4	WH	ZB
[mm]					+1.3	+1.2
20	M8	M10x1.25	2	2.6	5.5	80.8
25		M10				83.1
32	M10x1.25	M10	2.6	3.3	6	91.4
40		M12			6.1	96.5
50	M12x1.25	M12	3.3	4.7	8.2	105.6
63		M16			8.1	118.9
80	M16x1.5	M16	4.7	6.1	8.9	145.4
100		M20x1.5 M20			9	154.1

Compact cylinders ADN-KP, standard hole pattern, with clamping unit

Ordering data – Modular product system

Ordering table								
Size	20	25	32	40	Conditions	Code		Enter code
Module no.	548206	548207	548208	548209				
Function	Compact cylinder, double-acting, standard hole pattern, with clamping unit					ADN		ADN
Piston ø [mm]	20	25	32	40		-...		
Stroke [mm]	10 ... 300		10 ... 400			-...		
Clamping unit	Attached					-KP		-KP
Piston rod thread	Male thread					-A		
	Female thread				[1]	-I		
Cushioning	Elastic cushioning rings/plates at both ends					-P		-P
Position sensing	Via proximity switch					-A		-A
Extended male thread [mm]	Extended male piston rod thread					-...K2		
	1 ... 20							
Special piston rod thread	Male thread	M10x1.25 M10	M10x1.25 M10	M10 M12	M10 M12	-“...”K5		
	Female thread	M5	M5	M6	M6			
Extended piston rod [mm]	Extended piston rod		1 ... 400		[2]	-...K8		
Captive rating plate	Laser-etched rating plate					-TL		

[1] I Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Ordering data – Modular product system

Ordering table													
Size		50		63		80		100		Conditions	Code		Enter code
Module no.		548210		548211		548212		548213					
Function		Compact cylinder, double-acting, standard hole pattern, with clamping unit									ADN		
Piston ø	[mm]	50		63		80		100			-...		
Stroke	[mm]	10 ... 400				10 ... 500					-...		
Clamping unit		Attached									-KP	-KP	
Piston rod thread		Male thread									-A		
		Female thread								[1]	-I		
Cushioning		Elastic cushioning rings/plates at both ends									-P	-P	
Position sensing		Via proximity switch									-A	-A	
Extended male thread		Extended male piston rod thread									-...K2		
													[mm]
Special piston rod thread	Male thread	M12	M12	M16	M16		-“...”K5						
		M16	M16	M20	M20								
	Female thread	M8	M8	M10	M10								
Extended piston rod		Extended piston rod									-...K8		
													[mm]
Captive rating plate		Laser-etched rating plate									-TL		

[1] I Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Type codes

001	Series	
ADN	Compact cylinder, double-acting, based on ISO 21287	

002	Piston diameter	Ø 32 ... 63
20	20	
25	25	
32	32	
40	40	
50	50	
63	63	
80	80	
100	100	

003	Stroke	
...	10 ... 500	

004	End-position locking	
ELB	Both sides	
ELH	Rear	
ELV	Front	

005	Piston rod thread type	
A	Male thread	
I	Female thread	

006	Cushioning	
P	Elastic cushioning rings/plates on both sides	

007	Position sensing	
A	For proximity sensor	

008	Piston rod thread extension	Ø 20 ... 25
	None	
...K2	1 ... 30 mm	


009	Custom thread	
"M6"K5	M6	
"M8"K5	M8	
"M10"K5	M10	
"M10x1,25"K5	M10x1.25	
"M12"K5	M12	
"M16"K5	M16	
"M20x1,5"K5	M20x1.5	
"M5"K5	M5	
"M20"K5	M20	

010	Piston rod extension	
	None	
...K8	1 ... 500 mm	

011	Captive rating plate	
	Rating plate, glued	
TL	Laser etched rating plate	

Datasheet

Function



Ø Diameter
20 ... 100 mm

Stroke length
10 ... 500 mm

Variants




K2



K5



K8



Note

Additional measures are required for use in safety-related applications; in Europe, for example, the standards listed under the EC Machinery Directive must be observed.

Without additional measures in accordance with legally specified minimum requirements, the product is not suitable as a safety-related component in control systems.

General technical data

Piston Ø	20	25	32	40	50	63	80	100
Pneumatic connection	M5	M5	G1/8	G1/8	G1/8	G1/8	G1/8	G1/8
Female piston rod thread								
–	M6	M8	M10	M12				
K5	M5	M6	M8	M10				
Male piston rod thread								
–	M8	M10x1.25	M12x1.25	M16x1.5				
K5	M10; M10x1.25	M10; M12	M12; M16	M16; M20; M20x1.5				
Max. axial backlash with end position locked [mm]	1.3						2.1	
Design	Piston							
	Piston rod							
	Cylinder barrel							
End-position locking								
ELB	At both ends							
ELV	Front							
ELH	Rear							
Cushioning	Elastic cushioning rings/plates at both ends							
Position sensing	Via proximity switch							
Type of mounting	With female thread							
	With accessories							
Mounting position	Any							



Note

- Screws with a head or similar must not be used in place of end-position locking, as there is a risk that the function will be impaired if they are screwed in too deeply.
- The exhaust bore must not be closed.
- The piston rod can be locked in any stroke position once the drive is brought mechanically into its end position.
- End-position locking has been designed to prevent the load from dropping in case of pressure failure.
- Avoid operating the cylinder using a 3-way valve, especially with the function “mid-position closed” and those with “metallic sealing”. The residual pressure that is enclosed on the locking side of the cylinder can release the locking function.
- The cylinder must not be operated with external stops (e.g. shock absorber, buffer, oil brake, etc.):
 - It may not be possible to reliably reach the internal end position.
- The locking mechanism can wear out prematurely. (If the pressure in the opposite chamber drops to less than the locking pressure, the locking piston will prematurely fall to its lower end position.)

Datasheet

Operating and environmental conditions									
Piston Ø		20	25	32	40	50	63	80	100
Operating medium		Compressed air to ISO 8573-1:2010 [7:4:4]							
Note on the operating/ pilot medium		Lubricated operation possible (in which case lubricated operation will always be required)							
Operating pressure	[MPa]	0.25 ... 1				0.15 ... 1			
	[bar]	2.5 ... 10				1.5 ... 10			
	[psi]	36.26 ... 145				21.76 ... 145			
Ambient temperature ¹⁾	[°C]	-20 ... +80							
Corrosion resistance class CRC ²⁾		2 - Moderate corrosion stress							

1) Note operating range of proximity switches

2) More information www.festo.com/x/topic/crc

Forces [N]								
Piston Ø	20	25	32	40	50	63	80	100
Theoretical force at 6 bar, advancing	188	295	483	754	1178	1870	3016	4712
Theoretical force at 6 bar, retracting	141	247	415	686	1057	1750	2827	4524
Static holding force	250	500			2000		5000	

Sizing example



Note

When sizing pneumatic cylinders, it is recommended as a basic principle that only 50% of the indicated theoretical forces (see above) be used

Assuming:

Mounting position = vertical

Workpiece load = 44 kg

$$F = m \times g = 44 \text{ kg} \times 9.81 \text{ m/s}^2 \\ = 431.6 \text{ N}$$

To be determined:

Suitable piston diameter

Example with piston diameter 32 mm:

Theoretical force at 6 bar, advancing = 483 N

50% of the theoretical force = 241.5 N

Static holding force with piston diameter 32 mm = 500 N

The static holding force of end-position locking is within the permissible range (max. 500 N) for a workpiece load of 44 kg (431.6 N); however, the cylinder would be at 89% capacity.

Results:

A cylinder with a piston diameter of 40 mm is therefore recommended for this application.

Impact energy [J]								
Piston Ø	20	25	32	40	50	63	80	100
Max. impact energy in the end positions	0.2	0.3	0.4	0.7	1	1.3	1.8	2.5




Note

These specifications represent the maximum values that can be achieved. The maximum permissible impact energy must be observed.

Permissible impact velocity:
$$V = \sqrt{\frac{2 \times E}{m_1 + m_2}}$$

Maximum permissible mass:
$$m_2 = \frac{2 \times E}{v^2} - m_1$$

V Permissible impact velocity
E Max. impact energy
m1 Moving mass (drive)
m2 Moving payload


Max. transverse force F_q as a function of projection x

Datasheet

Weight [g]								
Piston Ø	20	25	32	40	50	63	80	100
End position locking at both ends								
Product weight with 0 mm stroke	234	339	518	665	1334	1734	3300	4735
Additional weight per 10 mm stroke	22	26	29	38	51	59	79	98
Moving mass with 0 mm stroke	43	53	85	101	199	248	475	637
Additional mass per 10 mm stroke	6	6	9	9	16	16	25	25
End-position locking at the front								
Product weight with 0 mm stroke	177	248	387	498	922	1228	2296	3448
Additional weight per 10 mm stroke	22	26	29	38	51	59	79	98
Moving mass with 0 mm stroke	35	46	75	98	175	225	464	626
Additional mass per 10 mm stroke	6	6	9	9	16	16	25	25
End-position locking at rear								
Product weight with 0 mm stroke	181	252	380	505	920	1217	2233	3409
Additional weight per 10 mm stroke	22	26	29	38	51	59	79	98
Moving mass with 0 mm stroke	37	45	73	89	168	217	413	582
Additional mass per 10 mm stroke	6	6	9	9	16	16	25	25

Materials

Sectional view



Compact cylinder

[1]	Cover	Anodised aluminium
[2]	Cylinder barrel	Anodised aluminium
[3]	Piston rod	High-alloy steel
[4]	Flange screws	Ø 20 ... 63 Galvanised steel
		Ø 80 ... 100 Standard screws, galvanised steel
–	Seals	Polyurethane, nitrile rubber
	Note on materials	RoHS-compliant

Datasheet


Dimensions – Basic version

Download CAD data → www.festo.com


ELB – End-position locking at both ends

Ø 20 ... 63


Ø 32 ... 63




Ø 80 ... 100



ELV – End-position locking at the front



ELH – End-position locking at rear



Datasheet



∅ [mm]	BG min.	D1 ∅ H9	D2 ∅	D5 ∅	E	EE	G	G1	H1	J2	L4	L5
20	18	9	9	9 ^{F9}	35.5 ^{+0.3}	M5	25	12	45.5	2.6	18.5	12.5
25			13		39.5 ^{+0.3}		29.5		53.3		20.8	14
32					47 ^{+0.3}	G1/8	33	15	58	6	22.5	15
40					54.5 ^{+0.3}				61.8	8		
50	20	12	20	12 ^{F9}	65.5 ^{+0.3}		77		27.5	20.5		
63										75.5 ^{+0.3}	82	11.5
80			30	15	95.5 ^{+0.6}		55	16.5	103.5			
100					113.5 ^{+0.6}		57	21.5	113.5	20	35	27

∅	PW	MM ∅	PL	PL1	RT	ST	T2	TG	ZA ±0.6		ZB +1.2	
[mm]	+0.2					h13	+0.1	±0.2	ELB	ELV, ELH	ELB	ELV, ELH
20	5	10	6	6	M5	9	2.1	22	63	50	68.8	55.5
25								26	74	56.5	79.5	62
32		12	16	8.2	M6	10		32.5	80	62	86	68
40								38	81	63	87.1	69
50					16	21		M8	13	46.5	101	73
63	56.5	105	77				113.1			85.1		
80	2.6	20	28		10.5	M10	17	2.6	72	131	92.5	139.9
100				89					138	102.5	147	111.5

Datasheet

Dimensions – Variants Download CAD data → www.festo.com



Basic version



[1] Hex nut DIN 439-B
only with Ø 32 ... 100

+ = plus stroke length



K2 – Extended male piston rod thread



[1] Hex nut DIN 439-B
only with Ø 32 ... 100



+ = plus stroke length

K5 – Special piston rod thread



+ = plus stroke length

K8 – Extended piston rod



[1] Hex nut DIN 439-B
only with Ø 32 ... 100

+ = plus stroke length

Datasheet

∅	A	A1	A2	AF	AF5	KF	KF5				
[mm]	−0.5			min.	min.						
20	16	1 ... 20	1 ... 300	14	12	M6	M5				
25			1 ...400	16	14	M8	M6				
32	19										
40	22			16	M10	M8					
50							20				
63				20	M12	M10					
80		28	1 ... 30				1 ... 500				
100											

∅	KK	KK5	T3	T4	WH	ZB +1.2	
[mm]					+1.3	ELB	ELV, ELH
20	M8	M10x1.25 M10	2	2.6	5.5	68.8	55.5
25						79.5	62
32	M10x1.25	M10 M12	2.6	3.3	6	86	68
40					6.1	87.1	69
50	M12x1.25	M12 M16	3.3	4.7	8.2	109.2	81.2
63					8.1	113.1	85.1
80	M16x1.5	M16 M20x1.5 M20	4.7	6.1	8.9	139.9	101.4
100					9	147	111.5

Ordering data – Modular product system

Ordering table									
Size		20	25	32	40	Conditions	Code		Enter code
Module no.		548214	548215	548216	548217				
Function		Compact cylinder, double-acting, standard hole pattern, with end-position locking					ADN		ADN
Piston ø	[mm]	20	25	32	40		-...		
Stroke	[mm]	10 ... 300		10 ... 400			-...		
End-position locking		At both ends					-ELB		
		Front					-ELV		
		Rear					-ELH		
Piston rod thread		Male thread					-A		
		Female thread				[1]	-I		
Cushioning		Elastic cushioning rings/plates at both ends					-P		-P
Position sensing		Via proximity switch					-A		-A
Extended male thread		Extended male piston rod thread							
	[mm]	1 ... 20					-...K2		
Special piston rod thread	Male thread	M10x1.25 M10	M10x1.25 M10	M10 M12	M10 M12		-“...”K5		
	Female thread	M5	M5	M6	M6				
Extended piston rod		Extended piston rod							
	[mm]	1 ... 300		1 ... 400		[2]	-...K8		
Captive rating plate		Laser-etched rating plate					-TL		

[1] I Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length

Ordering data – Modular product system

Ordering table												
Size	50		63		80		100		Conditions	Code	Enter code	
Module no.	548218		548219		548220		548221					
Function	Compact cylinder, double-acting, standard hole pattern, with end-position locking									ADN	ADN	
Piston Ø	[mm]	50	63		80		100			-...		
Stroke	[mm]	10 ... 400			10 ... 500					-...		
End-position locking	At both ends									-ELB		
	Front									-ELV		
	Rear									-ELH		
Piston rod thread	Male thread									-A		
	Female thread								[1]	-I		
Cushioning	Elastic cushioning rings/plates at both ends									-P	-P	
Position sensing	Via proximity switch									-A	-A	
Extended male thread	[mm]	Extended male piston rod thread			1 ... 20			1 ... 30			-...K2	
Special piston rod thread	Male thread	M12 M16	M12 M16		M16 M20 M20x1.5		M16 M20 M20x1.5			-“...”K5		
	Female thread	M8	M8		M10		M10					
Extended piston rod	[mm]	Extended piston rod			1 ... 400			1 ... 500		[2]	-...K8	
Captive rating plate	Laser-etched rating plate									-TL		

[1] I Not with extended male thread K2

[2] K8 The sum of the stroke length and piston rod extension must not exceed the maximum permissible stroke length


Type codes

001	Series	
AEN	Compact cylinder, single-acting, based on ISO 21287	
002	Piston diameter [mm]	
12	12	
16	16	
20	20	
25	25	
32	32	
40	40	
50	50	
63	63	
80	80	
100	100	
003	Stroke [mm]	
...	1 ... 25	
004	Piston rod thread type	
A	Male thread	
I	Female thread	
005	Cushioning	
P	Elastic cushioning rings/plates on both sides	
006	Position sensing	
A	For proximity sensor	
007	Active direction	
Z	Single-acting, pulling	
	Single-acting, pushing	

008	Piston rod thread extension	
	None	
...K2	1 ... 30 mm	
009	Custom thread	
"M5"K5	M5	
"M6"K5	M6	
"M8"K5	M8	
"M10"K5	M10	
"M10x1,25"K5	M10x1.25	
"M12"K5	M12	
"M16"K5	M16	
"M20"K5	M20	
"M20x1,5"K5	M20x1.5	
010	Piston rod extension	
	None	
...K8	1 ... 25 mm	
011	Improved running performance	
	None	
K10	Smooth anodised aluminium coated piston rod	
012	Temperature resistance	
	Standard	
S6	Heat-resistant seals max. 120 °C	
013	Captive rating plate	
	Rating plate, glued	
TL	Laser etched rating plate	

Datasheet

Function



Pulling

Ø - Diameter
12 ... 100 mm

l - Stroke length
1 ... 25 mm

 www.festo.com

Variants



S6



K2



K5




K8




K10



Q



AEN- ... -A-P-A



AEN- ... -A-P-A-Z

General technical data

Piston Ø	12	16	20	25	32	40	50	63	80	100
Design	Piston									
	Piston rod									
	Cylinder barrel									
Cushioning	Elastic cushioning rings/plates at both ends									
Position sensing	Via proximity switch									
Type of mounting	With through-hole									
	With female thread									
	With accessories									
Mounting position	Any									

Technical data – Basic version and variants

Piston Ø	12	16	20	25	32
Pneumatic connection	M5	M5	M5	M5	G1/8
Female piston rod thread					
–	M3	M4	M6	M6	M8
K5	–	–	M5	M5	M6
Male piston rod thread					
–	M5	M6	M8	M8	M10x1.25
K5	M6	M8	M10; M10x1.25	M10; M10x1.25	M10; M12
Q-K5	–	M8	M10; M10x1.25	M10; M10x1.25	M10

Piston Ø	40	50	63	80	100
Pneumatic connection	G1/8	G1/8	G1/8	G1/8	G1/8
Female piston rod thread					
–	M8	M10	M10	M12	M12
K5	M6	M8	M8	M10	M10
Male piston rod thread					
–	M10x1.25	M12x1.25	M12x1.25	M16x1.5	M16x1.5
K5	M10; M12	M12; M16	M12; M16	M16; M20; M20x1.5	M16; M20; M20x1.5
Q-K5	M10	M12	M12	M16	M16

Datasheet

Operating and environmental conditions										
Piston Ø	12	16	20	25	32	40	50	63	80	100
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]									
Note on the operating/ pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)									
Operating pressure										
in [MPa]										
–	0.15 ... 1		0.1 ... 1							
Z	0.17 ... 1	0.22 ... 1	0.13 ... 1		0.07 ... 1	0.06 ... 1				
Q	0.15 ... 1		0.1 ... 1							
Q-S6	0.15 ... 0.6		0.1 ... 0.6							
in [bar]										
–	1.5 ... 10		1 ... 10							
Z	1.7 ... 10	2.2 ... 10	1.3 ... 10		0.7 ... 10	0.6 ... 10				
Q	1.5 ... 10		1 ... 10							
Q-S6	1.5 ... 6		1 ... 6							
in [psi]										
–	21.76 ... 145		14.5 ... 145							
Z	24.66 ... 145	31.91 ... 145	18.85 ... 145		10.15 ... 145	8.7 ... 145				
Q	21.76 ... 145		14.5 ... 145							
Q-S6	21.76 ... 87		14.5 ... 87							
Ambient temperature1) [°C]										
–	–20 ... +80									
S6	0 ... +120									
Corrosion resistance class CRC ²⁾	2 - Moderate corrosion stress									

1) Note operating range of proximity switches

2) More information www.festo.com/x/topic/crc

Forces [N] and impact energy [J]										
Piston Ø	12	16	20	25	32	40	50	63	80	100
AEN										
Theoretical force at 6 bar, advancing	56	95	162	259	441	702	1098	1783	2899	4511
AEN-...-Z, pulling										
Theoretical force at 6 bar, retracting	39	65	115	211	373	634	977	1663	2610	4323
Max. impact energy at the end positions	0.04	0.04	0.04	0.08	0.1	0.15	0.18	0.28	0.35	0.7

 **Note**

These specifications represent the maximum values that can be achieved. The maximum permissible impact energy must be observed.

Permissible impact velocity: $V = \sqrt{\frac{2 \times E}{m_1 + m_2}}$


Maximum permissible mass: $m_2 = \frac{2 \times E}{V^2} - m_1$

V Permissible impact velocity
E Max. impact energy
m1 Moving mass (drive)
m2 Moving payload


Datasheet

Spring return force F as a function of stroke l

Ø 12 ... 20



Ø 25 ... 100



Note

The degree of friction depends on the mounting position and the type of load involved. Single-acting cylinders should as far as possible be operated without transverse loads.

Weight [g]										
Piston Ø	12	16	20	25	32	40	50	63	80	100
AEN-...										
Product weight with 0 mm stroke	67	78	131	168	273	361	532	752	1135	1733
Additional weight per 10 mm stroke	12	14	22	26	29	38	51	60	80	99
Moving mass with 0 mm stroke	11	18	32	41	76	103	164	220	425	587
Additional mass per 10 mm stroke	2	4	6	6	9	9	16	16	25	25
AEN-...-I										
Product weight with 0 mm stroke	65	75	122	159	248	336	490	710	1050	1648
Additional weight per 10 mm stroke	12	14	22	26	29	38	51	60	80	99
Moving mass with 0 mm stroke	9	15	23	32	51	78	122	178	340	502
Additional mass per 10 mm stroke	2	4	6	6	9	9	16	16	25	25
AEN-...-Q										
Product weight with 0 mm stroke	—	78	130	168	270	362	539	754	1147	1741
Additional weight per 10 mm stroke	—	14	22	26	28	37	47	55	75	94
Moving mass with 0 mm stroke	—	18	32	41	73	97	155	210	415	567
Additional mass per 10 mm stroke	—	4	6	6	8	8	11	11	20	20
AEN-...-K10										
Product weight with 0 mm stroke	—	—	134	170	278	366	551	764	1135	1725
Additional weight per 10 mm stroke	—	—	18	22	23	32	41	47	61	80
Moving mass with 0 mm stroke	—	—	35	43	89	108	184	231	425	579
Additional mass per 10 mm stroke	—	—	2	2	3	3	5	4	6	6
AEN-...-K8										
Additional weight and mass per 10 mm piston rod extension	2	4	6	6	9	9	16	16	25	25
AEN-...-K2										
Additional weight and mass per 10 mm extended piston rod thread	2	2	4	4	6	6	9	9	16	16
AEN-...-Z										
Product weight with 0 mm stroke	64	74	125	166	265	361	532	752	1135	1733
Additional weight per 10 mm stroke	12	14	22	26	29	38	51	60	80	99
Moving mass with 0 mm stroke	11	18	32	41	76	103	164	220	425	587
Additional mass per 10 mm stroke	2	4	6	6	9	9	16	16	25	25

Datasheet

Materials
Sectional view



Datasheet

Compact cylinder		Basic version	S6
[1] Cover	ø 12 ... 80	Anodised aluminium	
	ø 100	Coated die-cast aluminium	
[2] Cylinder barrel		Anodised aluminium	
[3] Piston rod		High-alloy steel	
[4] Flange screws	ø 12 ... 16	High-alloy steel	
	ø 20 ... 63	Galvanised steel	
	ø 80 ... 100	Standard screws, galvanised steel	
– Seals		Polyurethane	Fluoro rubber
Note on materials		RoHS-compliant	


Datasheet

Dimensions – Basic version

Download CAD data → www.festo.com



Ø 12 ... 63

Ø 32 ... 63




Ø 12 ... 25

Ø 12



+ = plus stroke length

Ø 80 ... 100



+ = plus stroke length

Datasheet

∅	BG	D1 ∅ H9	D5 ∅	E	EE	G	J2	J3	PW
[mm]	min.								+0.2
12	17	9	6 ^{F9}	27.5 ^{+0.3}	M5	10.5	2	—	3.5
16				29 ^{+0.3}		11	2.6		
20	19.5		9 ^{F9}	35.5 ^{+0.3}		12			5
25				39.5 ^{+0.3}	G1/8	15	6		
32	26			47 ^{+0.3}					
40				54.5 ^{+0.3}			11.5		
50	27	12 ^{F9}	65.5 ^{+0.3}	20					
63			75.5 ^{+0.3}						
80	17		15	95.5 ^{+0.6}		16.5			
100	21.5			113.5 ^{+0.6}		21.5			



∅	MM ∅	PL	RT	ST	T2	TG	ZA	ZB
[mm]		+0.2		h13	+0.1	±0.2	±0.3	+1.2
12	6	6	M4	5	2.1	16	35	39.2
16	8			7		18		39.7
20	10		M5	9		22	37	42.5
25						26	39	44.5
32	12	8.2	M6	10		32.5	44	50
40						38	45	51.1
50	16		M8	13	2.6	46.5		53.2
63						56.5	49	57.1
80	20		M10	17		72	54	62.9
100		89				67	76	

Datasheet

Dimensions – Variants

Download CAD data → www.festo.com



Basic version



[1] Hex nut DIN 439-B
only with Ø 32 ... 100

+ = plus stroke length

Z – Pulling




[1] Hex nut DIN 439-B
only with Ø 32 ... 100

+ = plus stroke length

++ = plus 2x stroke length



K2 – Extended male piston rod thread



[1] Hex nut DIN 439-B
only with Ø 32 ... 100



+ = plus stroke length

K5 – Special piston rod thread



+ = plus stroke length

K8 – Extended piston rod



[1] Hex nut DIN 439-B
only with Ø 32 ... 100

+ = plus stroke length

Datasheet

∅	A	A1	A2	AF	AF5	KF	KF5		
[mm]	−0.5			min.	min.				
12	10	1 ... 10	1 ... 300	8	–	M3	–		
16	12			10		M4			
20	16	1 ... 20		1 ... 400	14	12	M6	M5	
25			20		16	14	M8	M6	
32	22				16	16	M10	M8	
40				28			1 ... 30	1 ... 500	20
50									
63									
80									
100									



∅ [mm]	KK	KK5	T3	T4	WH +1.3	ZB +1.2
12	M5	M6	–	1.5	4.2	39.2
16	M6	M8			4.7	39.7
20	M8	M10x1.25	2	2.6	5.5	42.5
25		M10				44.5
32	M10x1.25	M10	2.6	3.3	6	50
40		M12			6.1	51.1
50	M12x1.25	M12	3.3	4.7	8.2	53.2
63		M16			8.1	57.1
80	M16x1.5	M16	4.7	6.1	8.9	62.9
100		M20x1.5 M20			9	76

Datasheet

Dimensions – Variants

Download CAD data → www.festo.com



Q – Square piston rod



[1] Hex nut DIN 439-B
only with Ø 32 ... 100


+ = plus stroke length
++ = plus 2x stroke length

Q – Z – Pulling



+ = plus stroke length


Q-K2 – Square piston rod with extended male thread



[1] Hex nut DIN 439-B
only with Ø 32 ... 100



+ = plus stroke length

Q-K5 – Square piston rod with special piston rod thread



+ = plus stroke length

Q-K8 – Square, extended piston rod



[1] Hex nut DIN 439-B
only with Ø 32 ... 100

+ = plus stroke length

Datasheet

∅	A	A1	A2	AF3	B1 □	KF3
[mm]	−0.5			min.		
16	12	1 ... 10	1 ... 300	10	7	M4
20	16	1 ... 20		12	9	M5
25						
32	19		1 ...400	14	10	M6
40						
50	22	16		12	M8	
63						
80	28	1 ... 30	1 ... 500	20	16	M10
100						

∅	KK	KK5	T2	WH	ZB
[mm]				+1.3	+1.2
16	M6	M8	1.5	4.7	39.7
20	M8	M10x1.25 M10	2	5.5	42.5
25					44.5
32	M10x1.25	M10	2.6	6	50
40				6.1	51.1
50	M12x1.25	M12	3.3	8.2	53.2
63				8.1	57.1
80	M16x1.5	M16	4.7	8.9	62.9
100				9	76

Ordering data – Modular product system, basic version and variants

Ordering table									
Size	12	16	20	25	32	Conditions	Code		Enter code
Module no.	536414	536415	536416	536417	536418				
Function	Compact cylinder, single-acting						AEN		AEN
Standard	Based on ISO 21287		Conforms to ISO 21287						
Piston Ø [mm]	12	16	20	25	32		-...		
Stroke [mm]	1 ... 10	1 ... 25					-...		
Thread type	Male thread						-A		
	Female thread					[1]	-I		
Cushioning	Elastic cushioning rings/plates at both ends						-P		-P
Position sensing	Via proximity switch						-A		-A
Effective direction	Single-acting, pulling						-Z		
Extended male thread [mm]	Extended male piston rod thread					[2]	-...K2		
	1 ... 10		1 ... 20						
Special piston rod thread	Male thread	M6	M8	M10x1.25 M10	M10x1.25 M10	M10 M12	[2]	-“...”K5	
	Female thread	–	–	M5	M5	M6			
Extended piston rod [mm]	Extended piston rod						-...K8		
	1 ... 10		1 ... 25						
Improved running performance	–	–	Smooth anodised aluminium piston rod				-K10		
Temperature resistance	Heat-resistant seals max. 120 °C						-S6		
Captive rating plate	Laser-etched rating plate						-TL		

[1] I Not with extended male thread K2

[2] K2, K5 Not with improved running performance K10

Ordering data – Modular product system, basic version and variants

Ordering table									
Size	40	50	63	80	100	Conditions	Code		Enter code
Module no.	536419	536420	536421	536422	536423				
Function	Compact cylinder, single-acting						AEN		AEN
Standard	Conforms to ISO 21287								
Piston Ø [mm]	40	50	63	80	100		-...		
Stroke [mm]	1 ... 25						-...		
Thread type	Male thread						-A		
	Female thread					[1]	-I		
Cushioning	Elastic cushioning rings/plates at both ends						-P		-P
Position sensing	Via proximity switch						-A		-A
Effective direction	Single-acting, pulling						-Z		
Extended male thread [mm]	Extended male piston rod thread						[2]	-...K2	
	1 ... 20			1 ... 30					
Special piston rod thread	Male thread	M10 M12	M12 M16	M12 M16	M16 M20 M20x1.5	M16 M20 M20x1.5	[2]	-“...”K5	
	Female thread	M6	M8	M8	M10	M10			
Extended piston rod [mm]	Extended piston rod 1 ... 25						-...K8		
Improved running performance	Smooth anodised aluminium piston rod						-K10		
Temperature resistance	Heat-resistant seals max. 120 °C						-S6		
Captive rating plate	Laser-etched rating plate						-TL		

[1] I Not with extended male thread K2

[2] K2, K5 Not with improved running performance K10

Ordering data – Modular product system, Q – Square piston rod, non-rotating

Ordering table								
Size	16	20	25	32	Conditions	Code		Enter code
Module no.	536415	536416	536417	536418				
Function	Compact cylinder, single-acting					AEN		AEN
Standard	Based on ISO 21287	Conforms to ISO 21287						
Piston ø [mm]	16	20	25	32		-...		
Stroke [mm]	1 ... 25					-...		
Thread type	Male thread					-A		
	Female thread				[1]	-I		
Cushioning	Elastic cushioning rings/plates at both ends					-P		-P
Position sensing	Via proximity switch					-A		-A
Effective direction	Single-acting, pulling					-Z		
Protection against rotation	Square piston rod					-Q		-Q
Extended male thread [mm]	Extended male piston rod thread							
	1 ... 10	1 ... 20				-...K2		
Special piston rod thread	Male thread	M8	M10x1.25 M10	M10x1.25 M10	M10	-“...”K5		
Extended piston rod [mm]	Extended piston rod							
	1 ... 25					-...K8		
Temperature resistance	Heat-resistant seals max. 120 °C					-S6		
Captive rating plate	Laser-etched rating plate					-TL		

[1] I Not with extended male thread K2

Ordering data – Modular product system, Q – Square piston rod, non-rotating


Ordering table								
Size	40	50	63	80	100	Conditions	Code	Enter code
Module no.	536419	536420	536421	536422	536423			
Function	Compact cylinder, single-acting						AEN	AEN
Standard	Conforms to ISO 21287							
Piston ø [mm]	40	50	63	80	100		-...	
Stroke [mm]	1 ... 25						-...	
Thread type	Male thread						-A	
	Female thread					[1]	-I	
Cushioning	Elastic cushioning rings/plates at both ends						-P	-P
Position sensing	Via proximity switch						-A	-A
Effective direction	Single-acting, pulling						-Z	
Protection against rotation	Square piston rod						-Q	-Q
Extended male thread [mm]	Extended male piston rod thread							
	1 ... 20			1 ... 30			-...K2	
Special piston rod thread	Male thread	M10	M12	M12	M16	M16	-“...”K5	
Extended piston rod [mm]	Extended piston rod							
	1 ... 25						-...K8	
Temperature resistance	Heat-resistant seals max. 120 °C						-S6	
Captive rating plate	Laser-etched rating plate						-TL	

[1] I Not with extended male thread K2

Accessories

Foot mounting HNA/HNA-...-R3

Material:
HNA: Galvanised steel
HNA-...-R3: steel,
with protective coating
RoHS-compliant



Dimensions and ordering data

for ø	AB ø	AH	AO	AT	AU	SA	TR	US	XA
[mm]	H14	JS14		±0.5	±0.2		±0.2	−0.5	
12	5.8	21	5	3	13	61	16	26	52.2
16		22	4.75				18	27.5	52.9
20	7	27	6.25	4	16	69	22	34.5	58.7
25		29					26	38.5	60.7
32		33.5					7	32	46
40	10	38	9	5	18	81	36	54	69.2
50		45	8				45	64	74.2
63		50					91	50	75
80	12	63	10.5	6	26	106	63	93	89
100	14.5	74	12.5				27	121	75


for $\varnothing$ [mm]	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part no.	Type	CRC ¹⁾	Weight [g]	Part no.	Type
12	1 - low	39	537237	HNA-12	3	39	537252	HNA-12-R3
16	1 - low	42	537238	HNA-16	3	42	537253	HNA-16-R3
20	1 - low	84	537239	HNA-20	3	84	537254	HNA-20-R3
25	1 - low	90	537240	HNA-25	3	90	537255	HNA-25-R3
32	1 - low	123	537241	HNA-32	3	123	537256	HNA-32-R3
40	1 - low	157	537242	HNA-40	3	157	537257	HNA-40-R3
50	1 - low	278	537243	HNA-50	3	278	537258	HNA-50-R3
63	1 - low	328	537244	HNA-63	3	328	537259	HNA-63-R3
80	1 - low	634	537249	HNA-80	3	634	537260	HNA-80-R3
100	1 - low	814	537250	HNA-100	3	814	537261	HNA-100-R3

1) More information www.festo.com/x/topic/crc

Accessories

Flange mounting FNC

Material:
Galvanised steel
RoHS-compliant




Dimensions and ordering data											
for ø	E	FB ø	MF	R	TF	UF	ZF	CRC ¹⁾	Weight	Part no.	Type
[mm]						±1			[g]		
12	28	5.5	8	–	40	50	47.2	1 - low	79	537245	FNC-12
16	29				43	55	47.9	1 - low	88	537246	FNC-16
20	36	6.6			55	70	50.7	1 - low	141	537247	FNC-20
25	40				60	76	52.7	1 - low	165	537248	FNC-25
32	45	7	10	32	64	80	60.2	1 - low	221	174376	FNC-32
40	54	9		36	72	90	61.2	1 - low	291	174377	FNC-40
50	65		12	45	90	110	65.2	1 - low	536	174378	FNC-50
63	75			50	100	120	69.2	1 - low	679	174379	FNC-63
80	93	12	16	63	126	150	79	1 - low	1495	174380	FNC-80
100	110	14		75	150	175	92	1 - low	2041	174381	FNC-100
125	132	16	20	90	180	210	112	1 - low	3775	174382	FNC-125

1) More information www.festo.com/x/topic/crc

Accessories

Swivel flange SNCL/SNCL-...-R3

Material:
SNCL 12 ... 25:
Wrought aluminium alloy
SNCL 32 ... 125:
Die-cast aluminium
SNCL-...-R3: Wrought aluminium
alloy with protective coating
RoHS-compliant



+ = plus stroke length

Dimensions and ordering data

for $\varnothing$ [mm]	CD $\varnothing$ H10	E	EW	FL ± 0.2	L	MR	TG	XC
12	6	25 $_{-0.6}$	12 $_{h12}$	16	10	6	16	55.2
16		27.5 $_{-0.6}$					18	55.9
20	8	34.5 $_{-0.6}$	16 $_{h12}$	20	14	8	22	62.7
25		38.5 $_{-0.6}$					26	64.7
32	10	45 $+0.2/-0.5$	26 $_{-0.2/-0.6}$	22	13	10	32.5	72.2
40	12	54 $_{-0.5}$	28 $_{-0.2/-0.6}$	25	16	12	38	75.2
50		64 $_{-0.6}$	32 $_{-0.2/-0.6}$	27			46.5	80.2
63	16	75 $_{-0.6}$	40 $_{-0.2/-0.6}$	32	21	16	56.5	89.2
80		93 $_{-0.8}$	50 $_{-0.2/-0.6}$	36			72	99
100	20	110 $+0.3/-0.8$	60 $_{-0.2/-0.6}$	41	27	20	89	117
125	25	131 $_{-0.8}$	70 $_{-0.2/-0.6}$	50	30	25	110	142

for $\varnothing$ [mm]	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part no.	Type	CRC ¹⁾	Weight [g]	Part no.	Type
12	2 - moderate	20	537790	SNCL-12	3	20	537794	SNCL-12-R3
16	2 - moderate	21	537791	SNCL-16	3	21	537795	SNCL-16-R3
20	2 - moderate	38	537792	SNCL-20	3	38	537796	SNCL-20-R3
25	2 - moderate	41	537793	SNCL-25	3	41	537797	SNCL-25-R3
32	1 - low	71	174404	SNCL-32	–	–	–	–
40	1 - low	95	174405	SNCL-40	–	–	–	–
50	1 - low	158	174406	SNCL-50	–	–	–	–
63	1 - low	225	174407	SNCL-63	–	–	–	–
80	1 - low	436	174408	SNCL-80	–	–	–	–
100	1 - low	606	174409	SNCL-100	–	–	–	–
125	1 - low	1135	174410	SNCL-125	–	–	–	–

1) More information www.festo.com/x/topic/crc

Accessories

Swivel flange SNCS/CRSNCS/SNCS-...-R3

Material:

SNCS 32 ... 50: Die-cast

aluminium

SNCS 63 ... 125: Wrought

aluminium alloy

CRSNCS 32 ... 80:


High-alloy stainless steel

SNCS-...-R3 100 ... 125:

Wrought aluminium alloy with

protective coating

RoHS-compliant



Dimensions and ordering data							
for $\varnothing$	CN $\varnothing$		E		EP	EX	FL
[mm]	ADN-...	ADN-...-R3	ADN-...	ADN-...-R3	± 0.2		± 0.2
32	10 ^{+0.013}	10+0.015/-0.04	45+0.2/-0.5	45 _{-0.5}	10.5	14	22
40	12 ^{+0.015}	12+0.018/-0.04	54 _{-0.5}	54 _{-0.5}	12	16	25
50	16 ^{+0.015}	16+0.018/-0.04	64 _{-0.6}	64 _{-0.6}	15	21	27
63	16 ^{+0.015}	16+0.018/-0.04	74.5 ± 0.5	75 _{-0.6}	15	21	32
80	20 ^{+0.018}	20+0.021/-0.04	92.2 ± 0.8	93 _{-0.8}	18	25	36
100	20 ^{+0.018}	20+0.021/-0.04	109+1/-0.7	109+1/-0.7	18	25	41
125	30 ^{+0.018}	30+0.021/-0.04	132+1/-0.7	132+1/-0.7	25	37	50

for $\varnothing$	LT	MS		RA		TG	XC
[mm]		ADN-...	ADN-...-R3	ADN-... +1	ADN-...-R3 +1		
32	13	15 ^{+0.5}	15 ^{+0.5}	14.5	14.5	32.5	72.2
40	16	17 ^{+0.5}	17 ^{+0.5}	17.5	17.5	38	75.2
50	16	20 ^{+0.5}	20 ^{+0.5}	18.5	19	46.5	80.2
63	21	23 _{-0.5}	22 ^{+0.5}	23	23	56.5	89.2
80	22	28 _{-0.5}	27 ^{+0.5}	25	25	72	99
100	27	30 ± 0.5	30 ± 0.5	95	100	89	117
125	30	39 ± 0.5	39 ± 0.5	100	100	110	142

for $\varnothing$	Basic version				High corrosion protection			
[mm]	CRC ¹⁾	Weight [g]	Part no.	Type	CRC ¹⁾	Weight [g]	Part no.	Type
32	1 - low	86	174397	SNCS-32	4	161	2895920	CRSNCS-32
40	1 - low	122	174398	SNCS-40	4	239	2895921	CRSNCS-40
50	1 - low	216	174399	SNCS-50	4	403	2895922	CRSNCS-50
63	2 - moderate	281	174400	SNCS-63	4	576	2895923	CRSNCS-63
80	2 - moderate	557	174401	SNCS-80	4	1173	2895924	CRSNCS-80
100	2 - moderate	683	174402	SNCS-100	3	684	2895925	SNCS-100-R3
125	2 - moderate	1369	174403	SNCS-125	3	1369	2895926	SNCS-125-R3

1) More information www.festo.com/x/topic/crc

Accessories

Clevis foot LBG/LBG-...-R3

The pivot pin is secured against rotation with a spring pin.


Material:

LBG 32 ... 63: Stainless steel casting

LBG 80 ... 125: Spheroidal graphite cast iron

LBG-...-R3: High-alloy stainless steel

RoHS-compliant



Dimensions and ordering data															
for $\varnothing$	BR		CB	CK	D3	GL	HB	L2	LE	PH	RA	TE	UB	UL	UR
[mm]		ADN-...-R3		$\varnothing$	$\varnothing$		$\varnothing$								
32	12	12	14.1	10	4.8	16	6.8	35	24	32	20	42	28	56	36
40	14	14	16.1	12	5.8	20	6.8	39	26	36	26	44	30	58	41.5
50	15	15	21.1	16	5.8	25	9.2	50	33	45	31	56	40	70	47
63	17	17	21.1	16	7.8	25	9.2	50	38	50	31	56	40	70	49
80	17	17	25.1	20	7.8	30	11	60	49	63	36	70	50	89	55
100	20	22	25.1	20	9.8	41	11	60	56	71	46	70	50	89	65
125	25	25	37.2	30	11.8	60	14	89	70	90	70	106	80	128	96



for $\varnothing$	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part no.	Type	CRC ¹⁾	Weight [g]	Part no.	Type
[mm]								
32	2 - moderate	220	31761	LBG-32	3	220	2078790	LBG-32-R3
40	2 - moderate	300	31762	LBG-40	3	300	2078792	LBG-40-R3
50	2 - moderate	540	31763	LBG-50	3	540	2078794	LBG-50-R3
63	2 - moderate	580	31764	LBG-63	3	580	2078795	LBG-63-R3
80	2 - moderate	1050	31765	LBG-80	3	1050	2078797	LBG-80-R3
100	2 - moderate	1375	31766	LBG-100	3	1375	2078799	LBG-100-R3
125	2 - moderate	4140	31767	LBG-125	3	4140	2078837	LBG-125-R3

1) More information www.festo.com/x/topic/crc

Accessories

Multi-position kit DPNA

Material:
Flange:
Wrought aluminium alloy
Screws: Galvanised steel
RoHS-compliant



+ = plus stroke length

Dimensions and ordering data

for ø	L2	B1	Max. overall stroke length	CRC ¹⁾	Weight	Part no.	Type1)
[mm]			[mm]		[g]		
12	35	13	600	2 - moderate	28	537263	DPNA-12
16					33	537264	DPNA-16
20					50	537265	DPNA-20
25					39	537266	DPNA-25
32	44	15	800		99	537267	DPNA-32
40	45				129	537268	DPNA-40
50					16	537269	DPNA-50
63	49				249	537270	DPNA-63
80	54	17	1000		474	537271	DPNA-80
100	67	19.5			712	537272	DPNA-100

 Note


The maximum total stroke length must not be exceeded when combining cylinders and multi-position kits.

1) More information www.festo.com/x/topic/crc

Accessories

Clevis foot LBN

Material:
Galvanised steel
RoHS-compliant




Dimensions and ordering data													
for Ø	CM	EK Ø	FL	GL	HB Ø	LE	MR	RG	UX	CRC ¹⁾	Weight	Part no.	Type
[mm]											[g]		
12/16	12.1	6	27 +0.3/-0.2	13	5.5	24	7	15	25	1 - low	40	6058	LBN-12/16
20/25	16.1	8	30 +0.4/-0.2	16	6.6	26	10	20	32	1 - low	84	6059	LBN-20/25

1) More information www.festo.com/x/topic/crc

Clevis foot CRLBN, stainless steel

Material:
High-alloy steel
RoHS-compliant



Dimensions and ordering data													
for Ø	CM	EK Ø	FL	GL	HB Ø	LE	MR	RG	UX	CRC ¹⁾	Weight	Part no.	Type
[mm]											[g]		
12/16	12.1	6	27 +0.3/−0.2	13	5.5	24	7	15	25	4 - very high	39	161862	CRLBN-12/16
20/25	16.1	8	30 +0.4/−0.2	16	6.6	26	10	20	32	4 - very high	82	161863	CRLBN-20/25

1) More information www.festo.com/x/topic/crc

Accessories

Swivel flange SNCB/SNCB-...-R3



Material:

SNCB: Die-cast aluminium

SNCB-...-R3: Die-cast aluminium

with protective coating

RoHS-compliant



Dimensions and ordering data									
for $\varnothing$	CB	E	EK $\varnothing$	FL	L	MR	TG	UB	XC
[mm]	H14		H9/e8	± 0.2		-0.5		h14	
32	26	$45+0.2/-0.5$	10	22	13	8.5	32.5	45	72
40	28	$54_{-0.5}$	12	25	16	12	38	52	76
50	32	$64_{-0.6}$	12	27	16	12	46.5	60	80
63	40	$75_{-0.6}$	16	32	21	16	56.5	70	89
80	50	$93_{-0.8}$	16	36	22	16	72	90	99
100	60	$110+0.3/-0.8$	20	41	27	20	89	110	117
125	70	$131_{-0.8}$	25	50	30	25	110	130	142

for $\varnothing$ [mm]	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part no.	Type	CRC ¹⁾	Weight [g]	Part no.	Type
32	1 - low	103	174390	SNCB-32	3	100	176944	SNCB-32-R3
40	1 - low	155	174391	SNCB-40	3	151	176945	SNCB-40-R3
50	1 - low	233	174392	SNCB-50	3	228	176946	SNCB-50-R3
63	1 - low	375	174393	SNCB-63	3	371	176947	SNCB-63-R3
80	1 - low	636	174394	SNCB-80	3	632	176948	SNCB-80-R3
100	1 - low	1035	174395	SNCB-100	3	986	176949	SNCB-100-R3
125	1 - low	1860	174396	SNCB-125	3	1776	176950	SNCB-125-R3

1) More information www.festo.com/x/topic/crc

Accessories


Trunnion flange ZNCF/CRZNG

Material:

ZNCF: Stainless steel casting

CRZNG: Electropolished stainless steel casting

RoHS-compliant



Dimensions and ordering data

for $\varnothing$ [mm]	C2)	C3)	TD $\varnothing$ e9	TK	TL	TM	US	XH	XL
32	71	86	12	16	12	50	45	2	58
40	87	105	16	20	16	63	54	4	61.1
50	99	117	16	24	16	75	64	4	64.7
63	116	136	20	24	20	90	75	4	68.5
80	136	156	20	28	20	110	93	5	76.9
100	164	189	25	38	25	132	110	10	95
125	192	217	25	50	25	160	131	14	117



for $\varnothing$ [mm]	Basic version				R3 – High corrosion protection			
	CRC ¹⁾	Weight [g]	Part no.	Type	CRC ¹⁾	Weight [g]	Part no.	Type
32	2 - moderate	150	174411	ZNCF-32	4	150	161852	CRZNG-32
40	2 - moderate	285	174412	ZNCF-40	4	285	161853	CRZNG-40
50	2 - moderate	473	174413	ZNCF-50	4	473	161854	CRZNG-50
63	2 - moderate	687	174414	ZNCF-63	4	687	161855	CRZNG-63
80	2 - moderate	1296	174415	ZNCF-80	4	1296	161856	CRZNG-80
100	2 - moderate	2254	174416	ZNCF-100	4	2254	161857	CRZNG-100
125	2 - moderate	3484	174417	ZNCF-125	4	3484	185362	CRZNG-125

1) More information www.festo.com/x/topic/crc

Accessories

Trunnion support LNZG

Material:
Trunnion support: Anodised aluminium
Plain bearing: Plastic
RoHS-compliant







Dimensions and ordering data															
for Ø	CR	DA	FK	FN	FS	H1	HB	KE	NH	TH	UL	CRC ¹⁾	Weight	Part no.	Type
[mm]	Ø	Ø	Ø				Ø								
	D11	H13	±0.1				H13			±0.2			[g]		
32	12	11	15	30	10.5	15	6.6	6.8	18	32	46	2 - moderate	83	32959	LNZG-32
40, 50	16	15	18	36	12	18	9	9	21	36	55	2 - moderate	129	32960	LNZG-40/50
63, 80	20	18	20	40	13	20	11	11	23	42	65	2 - moderate	178	32961	LNZG-63/80
100, 125	25	20	25	50	16	24.5	14	13	28.5	50	75	2 - moderate	306	32962	LNZG-100/125





1) More information www.festo.com/x/topic/crc

Accessories




Ordering data – Piston rod attachments



Designation	for ø	Part no.	Type
Rod eye SGS			
	16	9254	SGS-M6
	20, 25	9255	SGS-M8
	32, 40	9261	SGS-M10x1.25
	50, 63	9262	SGS-M12x1.25
	80, 100	9263	SGS-M16x1.5
	125	9264	SGS-M20x1.5
Rod clevis SG			
	12	–	
	16	3110	SG-M6
	20, 25	3111	SG-M8
	32, 40	6144	SG-M10x1.25
	50, 63	6145	SG-M12x1.25
	80, 100	6146	SG-M16x1.5
	125	6147	SG-M20x1.5
Coupling piece KSG			
	12, 16, 20, 25	–	
	32, 40	32963	KSG-M10x1.25
	50, 63	32964	KSG-M12x1.25
	80, 100	32965	KSG-M16x1.5
	125	32966	KSG-M20x1.5
Adapter AD			
	12	–	
	16	157328	AD-M6-M5
		157329	AD-M6-1/8
		157330	AD-M6-1/4
	20	157331	AD-M8-1/8
	25	157332	AD-M8-1/4
	32	157333	AD-M10x1.25-1/8
	40	157334	AD-M10x1.25-1/4
	50	160256	AD-M12x1.25-1/4
	63	160257	AD-M12x1.25-3/8


Datasheets a Internet: piston rod attachment

Designation	for ø	Part no.	Type
Rod clevis SGA for rod eye SGS			
	12, 16, 20, 25	–	
	32, 40	32954	SGA-M10x1.25
	50, 63	10767	SGA-M12x1.25
	80, 100	10768	SGA-M16x1.5
	125	10769	SGA-M20x1.5
Self-aligning rod coupler FK			
	12	30984	FK-M5
	16	2061	FK-M6
	20, 25	2062	FK-M8
	32, 40	6140	FK-M10x1.25
	50, 63	6141	FK-M12x1.25
	80, 100	6142	FK-M16x1.5
	125	6143	FK-M20x1.5
Self-aligning rod coupler DARP			
	12	8170112	DARP-M5-F
	16	8170115	DARP-M6-F
	20, 25	8170116	DARP-M8-F
	32, 40	8170119	DARP-M10P-F
	50, 63	8170120	DARP-M12P-F
	80, 100	8170121	DARP-M16P-F
	125	8170124	DARP-M20P-F
Coupling piece KSZ			
	12	–	
	16	36123	KSZ-M6
	20, 25	36124	KSZ-M8
	32, 40	36125	KSZ-M10x1.25
	50, 63	36126	KSZ-M12x1.25
	80, 100	36127	KSZ-M16x1.5
	125	36128	KSZ-M20x1.5

Accessories

Ordering data – Piston-rod attachments, corrosion-resistant				Datasheets a Internet: piston rod attachment			
Designation	for ø	Part no.	Type	Designation	for ø	Part no.	Type
Rod eye CRSGS				Rod clevis CRSG			
	12	–			12	–	
	16	195580	CRSGS-M6		16, 20	13567	CRSG-M6
	20, 25	195581	CRSGS-M8		20, 25	13568	CRSG-M8
	32, 40	195582	CRSGS-M10x1.25		32, 40	13569	CRSG-M10x1.25
	50, 63	195583	CRSGS-M12x1.25		50, 63	13570	CRSG-M12x1.25
	80, 100	195584	CRSGS-M16x1.5		80, 100	13571	CRSG-M16x1.5
	125	195585	CRSGS-M20x1.5		125	13572	CRSG-M20x1.5
Self-aligning rod coupler CRFK							
	32, 40	2305778	CRFK-M10x1.25				
	50, 63	2305779	CRFK-M12x1.25				
	80, 100	2490673	CRFK-M16x1.5				
	125	2545677	CRFK-M20x1.5				

Ordering data – Mounting components				Datasheets a Internet: clevis foot			
Designation	for ø	Part no.	Type	Designation	for ø	Part no.	Type
Right-angle clevis foot LBG for rod eye SGS				Right-angle clevis foot LQG for rod eye SGS			
	32, 40	31761	LBG-32		32, 40	31768	LQG-32
	50, 63	31762	LBG-40		50, 63	31769	LQG-40
	80, 100	31763	LBG-50		80, 100	31770	LQG-50
		31764	LBG-63			31771	LQG-63
	125	31765	LBG-80		125	31772	LQG-80
		31766	LBG-100			31773	LQG-100



Ordering data – Mounting components, high corrosion protection				Datasheets a Internet: clevis foot			
Designation	for ø	Part no.	Type	Designation	for ø	Part no.	Type
Clevis foot LBG-R3 for rod eye CRSGS							
	32, 40					2078790	LBG-32-R3
	50, 63					2078792	LBG-40-R3
	80, 100					2078794	LBG-50-R3
						2078795	LBG-63-R3
						2078797	LBG-80-R3
	125					2078799	LBG-100-R3

Ordering data – One-way flow control valves				Datasheets → Internet: grla			
Connection		Material		Part no.		Type	
for ø		For tubing O.D.					
For exhaust air							
	12, 16, 20, 25	3	Metal design	193137	GRLA-M5-QS-3-D		
		4		193138	GRLA-M5-QS-4-D		
		6		193139	GRLA-M5-QS-6-D		
	32, 40, 50, 63, 80, 100	3		193142	GRLA-1/8-QS-3-D		
		4		193143	GRLA-1/8-QS-4-D		
		6		193144	GRLA-1/8-QS-6-D		
		8		193145	GRLA-1/8-QS-8-D		
		125		6	193146	GRLA-1/4-QS-6-D	
				8	193147	GRLA-1/4-QS-8-D	
	10			193148	GRLA-1/4-QS-10-D		

Accessories




Ordering data – One-way flow control valves				Datasheets a Internet: grlz	
	Connection		Material	Part no.	Type
	for Ø	For tubing O.D.			
For supply air					
	12, 16, 20, 25	3	Metal design	193153	GRLZ-M5-QS-3-D
		4		193154	GRLZ-M5-QS-4-D
		6		193155	GRLZ-M5-QS-6-D
	32, 40, 50, 63, 80, 100	3		193156	GRLZ-1/8-QS-3-D
		4		193157	GRLZ-1/8-QS-4-D
		6		193158	GRLZ-1/8-QS-6-D
		8		193159	GRLZ-1/8-QS-8-D
		125		–	151195


Ordering data – One-way flow control valves for cylinders ADN _H and ADN _M					Datasheets → Internet: grla	
	Connection		Material	Part no.	Type	
	for Ø	For tubing O.D.				
For exhaust air						
	25, 40	3	Metal design	193137	GRLA-M5-QS-3-D	
		4		193138	GRLA-M5-QS-4-D	
	63, 100	4		193143	GRLA-1/8-QS-4-D	
		6		193144	GRLA-1/8-QS-6-D	
		8		193145	GRLA-1/8-QS-8-D	


Ordering data – Proximity switch for T-slot, magneto-resistive						Datasheets a Internet: smt	
	Type of mounting	Switching output	Electrical connection	Cable length [m]	Part no.	Type	
N/O							
	Inserted in the slot from above, flush with the cylinder profile, short design	PNP	Cable, 3-core	2.5	574335	SMT-8M-A-PS-24V-E-2.5-OE	
			Plug M8x1, 3-pin	0.3	574334	SMT-8M-A-PS-24V-E-0.3-M8D	
			1x M12 plug, 3-pin	0.3	574337	SMT-8M-A-PS-24V-E-0.3-M12	
		NPN	Cable, 3-core	2.5	574338	SMT-8M-A-NS-24V-E-2.5-OE	
			1x M8 plug, 3-pin	0.3	574339	SMT-8M-A-NS-24V-E-0.3-M8D	
N/C							
	Inserted in the slot from above, flush with the cylinder profile, short design	PNP	Cable, 3-core	7.5	574340	SMT-8M-A-PO-24V-E-7.5-OE	


Ordering data – Proximity switch for T-slot, magneto-resistive						Datasheets a Internet: smt	
	Type of mounting	Electrical connection, outlet direction of connection	Switching output	Cable length [m]	Part no.	Type	
N/O							
	Inserted into the slot lengthwise	Cable, 3-core, crosswise	PNP	2.5	547859	SMT-8G-PS-24V-E-2.5Q-OE	
		Plug M8x1, 3-pin, crossways		0.3	547860	SMT-8G-PS-24V-E-0.3Q-M8D	
		Cable, 3-core, crosswise	NPN	2.5	8065028	SMT-8G-NS-24V-E-2.5Q-OE	
		Plug M8x1, 3-pin, crossways		0.3	8065027	SMT-8G-NS-24V-E-0.3Q-M8D	


Accessories

Ordering data – Proximity switches for T-slot, magnetic reed						Datasheets → Internet: sme
	Type of mounting	Switching output	Electrical connection	Cable length [m]	Part no.	Type
N/O						
	Inserted in the slot from above, flush with the cylinder profile	Contacting	Cable, 3-core	2.5	543862	SME-8M-DS-24V-K-2.5-OE
				5.0	543863	SME-8M-DS-24V-K-5.0-OE
			Cable, 2-core	2.5	543872	SME-8M-ZS-24V-K-2.5-OE
			Plug M8x1, 3-pin	0.3	543861	SME-8M-DS-24V-K-0.3-M8D
	Inserted in the slot lengthwise, flush with the cylinder profile	Contacting	Cable, 3-core	2.5	150855	SME-8-K-LED-24
			Plug M8x1, 3-pin	0.3	150857	SME-8-S-LED-24
N/C						
	Inserted in the slot lengthwise, flush with the cylinder profile	Contacting	Cable, 3-core	7.5	160251	SME-8-O-K-LED-24

Connecting cables NEBA, straight, M8 connection						
	Electrical connection 1, connection technology	Electrical connection 2, connection technology	Electrical connection 2, number of pins/cores	Cable length	Part no.	Type
	M8x1 A-coded to EN 61076-2-104	Open end	3	2.5 m	8078223	NEBA-M8G3-U-2.5-N-LE3
				5 m	8078224	NEBA-M8G3-U-5-N-LE3

Connecting cables NEBA, straight, M12 connection						
	Electrical connection 1, connection technology	Electrical connection 2, connection technology	Electrical connection 2, number of pins/cores	Cable length	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	Open end	3	2.5 m	8078236	NEBA-M12G5-U-2.5-N-LE3
				5 m	8078237	NEBA-M12G5-U-5-N-LE3

Connecting cables NEBA, angled, M8 connection						
	Electrical connection 1, connection technology	Electrical connection 2, connection technology	Electrical connection 2, number of pins/cores	Cable length	Part no.	Type
	M8x1 A-coded to EN 61076-2-104	Open end	3	2.5 m	8078230	NEBA-M8W3-U-2.5-N-LE3
				5 m	8078231	NEBA-M8W3-U-5-N-LE3

Connecting cables NEBA, angled, M12 connection						
	Electrical connection 1, connection technology	Electrical connection 2, connection technology	Electrical connection 2, number of pins/cores	Cable length	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	Open end	3	2.5 m	8078245	NEBA-M12W5-U-2.5-N-LE3
				5 m	8078246	NEBA-M12W5-U-5-N-LE3

Accessories

Ordering data – Proximity switch, cuboid shape, pneumatic			Datasheets → Internet: smpo	
	Pneumatic connection		Part no.	Type
3/2-way valve, normally closed				
	Female thread M5		178563	SMPO-8E
Ordering data – Mounting kit for proximity switch SMPO-8E			Datasheets → Internet: smb	
	Assembly		Part no.	Type
	Clamped in T-slot		178230	SMB-8E
Ordering data – Slot cover for T-slot				
	Assembly	Length	Part no.	Type
	Insertable	2x 0,5 m	151680	ABP-5-S