

# Solenoid valve MN1H-5/2-D-2-FR-S-C

Part number: 159718

FESTO



[General operating condition](#)

## Data sheet

| Feature   | Value   |
|---|---|
| Valve function  | 5/2-way, monostable                           |
| Type of actuation                                     | Electric                                      |
| Construction width                                    | 54 mm   |
| Standard nominal flow rate (standardised to DIN 1343) | 2300 l/min                                    |
| pneumatic working port                                | Sub-base size 2 to ISO 5599-1<br>G3/8         |
| Operating voltage                                     | Via solenoid coil, must be ordered separately |
| Operating pressure                                    | -0.09 MPa ... 1.6 MPa                         |
| Operating pressure                                    | -0.9 bar ... 16 bar                           |
| Design  | Piston gate valve                             |
| Type of reset   | Mechanical spring                             |
| Maritime classification                               | See certificate                               |
| Certificate issuing authority                         | DNV-TAA000032X                                |
| Degree of protection                                  | IP65  |
| Nominal size  | 11.5 mm                                       |
| Grid dimension  | 56 mm   |
| Exhaust-air function                                  | With flow control option                      |
| Sealing principle                                     | Soft  |
| Mounting position                                     | optional                                      |
| Conforms to standard                                  | ISO 5599-1                                    |
| Manual override                                       | Detenting via accessory<br>Non-detenting      |
| ISO code  | 269   |
| Type of piloting                                      | Pilot actuated                                |
| Pilot air supply                                      | External                                      |
| Flow direction  | Reversible                                    |
| Symbol  | 00991190                                      |
| lap   | Overlap                                       |
| Pilot pressure  | 0.3 MPa ... 1 MPa                             |
| Pilot pressure  | 3 bar ... 10 bar                              |
| Suitability for vacuum                                | yes   |
| Switching time off                                    | 62 ms   |
| Switching time on                                     | 24 ms   |
| Max. positive test pulse with 0 signal                | 3700 µs                                       |
| Max. negative test pulse with 1 signal                | 4600 µs                                       |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [7:4:4]     |

| Feature                            | Value  |
|------------------------------------|--|
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Vibration resistance               | Transport application test with severity level 1 to FN 942017-4 and EN 60068-2-6           |
| Shock resistance                   | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27                          |
| LABS (PWIS) conformity             | VDMA24364-B1/B2-L  |
| Media temperature                  | -5 °C ... 50 °C  |
| Sound pressure level               | 85 dB(A)   |
| Pilot medium                       | Compressed air to ISO 8573-1:2010 [7:4:4]  |
| Ambient temperature                | -5 °C ... 50 °C  |
| Product weight                     | 710 g  |
| Electrical connection              | Via N1 coil, to be ordered separately  |
| Type of mounting                   | On sub-base<br>Via through-hole and screw  |
| Pilot exhaust port 84              | M5   |
| Pilot air port 14                  | Sub-base size 2 to ISO 5599-1  |
| Pneumatic connection, port 1       | Sub-base size 2 to ISO 5599-1  |
| Pneumatic connection, port 2       | Sub-base size 2 to ISO 5599-1  |
| Pneumatic connection, port 3       | Sub-base size 2 to ISO 5599-1  |
| Pneumatic connection, port 4       | Sub-base size 2 to ISO 5599-1  |
| Pneumatic connection, port 5       | Sub-base size 2 to ISO 5599-1  |
| Note on materials                  | RoHS-compliant   |
| Material seals                     | HNBR<br>NBR  |
| Material housing                   | Die-cast aluminium   |