

Input module CTSL-D-16E-M12-5

Part number: 1387359

FESTO



 General operating condition

Data sheet

Feature	Value
Protocol	I-Port IO-Link®
Dimensions W x L x H	143 mm x 103 mm x 32 mm
Type of mounting	With through-hole With H-rail
Product weight	250 g
Ambient temperature	-5 °C ... 50 °C
Storage temperature	-20 °C ... 70 °C
Degree of protection	IP65 IP67
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK RoHS instructions
KC characters	KC EMC
Certification	RCM compliance mark c UL us - Listed (OL)
Certificate issuing authority	UL E239998
Note on materials	RoHS-compliant
Housing material	PA-reinforced
Cover material	PA-reinforced
LED display (product-specific)	1 PS electrical operating voltage 16 channel status 2 group diagnostics
LED display (bus-specific)	X20: I-Port / IO-Link®
Max. number of inputs	16
Baud rate	38.4 kbit/s, 230.4 kbit/s
Electrical connection	M12
DC operating voltage range	18 V ... 30 V
Nominal operating voltage DC	24 V
Logic current consumption at logic nominal operating voltage	≤35 mA
Reverse polarity protection	for operating voltage
Input characteristics	IEC1131-T2
Switching level	Signal 0: ≤ 5 V Signal 1: ≥ 11 V
Input switching logic	PNP (positive switching)
Input debounce time	0.5 ms (3 ms, 10 ms, 20 ms parameterizable)

Feature	Value
Max. residual current per module	1.2 A
Electrical isolation between channels	no
Fuse protection (short circuit)	Internal electronic fuse per group
IO-Link®, Connection technology	Device, 5-pin
IO-Link®, number of ports	1
IO-Link®, port class	B
IO-Link®, protocol version	Device V 1.0
IO-Link®, communication mode	COM2 (38.4 kBd), COM3 (230.4 kBd)
IO-Link®, process data width IN	2 Byte
IO-Link®, minimum cycle time	Device 3.2 ms