

Air solenoid valve

VZWD-L-M22C-M-G18-30-V-1P4-15-R1

FESTO

Part number: 1491852



[PDF](#) General operating condition

Data sheet

| Feature | Value |
|----------------------------------|--|
| Structural design | Directly actuated poppet valve |
| Actuation type | Electrical |
| Sealing principle | Soft |
| Mounting position | Any |
| Type of mounting | In-line installation |
| Fitting connection | G1/8 |
| Electrical connection | Plug As per EN 175301-803 Rectangular design |
| Nominal width | 3 mm |
| Valve function | 2/2-way, closed, monostable |
| Manual override | None |
| Flow direction | Non-reversible |
| Medium | Compressed air as per ISO 8573-1:2010 [7:4:4] Inert gas Mineral oil Water Neutral liquids Other flow media on request |
| Nominal pressure of fitting PN | 100 |
| Pressure difference | 0 MPa |
| Differential pressure | 0 bar |
| Pressure difference | 0 psi |
| Coil characteristics | 24 V DC: 11.0 W |
| Insulation class | H |
| Permissible voltage fluctuations | +/- 10% |
| Duty cycle | 100% |
| Reset method | Mechanical spring |
| Type of control | directly |
| Symbol | 00992979 |
| Medium pressure | 0 MPa ... 1.5 MPa |

| Feature | Value |
|---|----------------------------|
| Medium pressure | 0 bar ... 15 bar |
| Medium pressure | 0 psi ... 217.5 psi |
| Max. viscosity | 22 mm ² /s |
| Temperature of medium | -10 °C ... 80 °C |
| Ambient temperature | -10 °C ... 35 °C |
| Leak rate to EN 12266-1 | A |
| Flow rate Kv | 0.2 m ³ /h |
| Normal nominal flow rate (normalized to DIN 1343) | 210 l/min |
| On switching time | 20 ms |
| Switching time off | 18 ms |
| Note on materials | RoHS compliant |
| LABS (PWIS) conformity | VDMA24364 Zone III |
| Housing material | high-alloy stainless steel |
| Material number of housing | 1,4305 |
| Seals material | FPM |
| Armature tube material | High-alloy steel |
| Product weight | 500 g |
| Degree of protection | IP65 |
| Corrosion resistance class (CRC) | 3 - High corrosion stress |
| Max. tightening torque for connecting thread | 10 Nm |
| Max. tightening torque for coil fastening | 2 Nm |