

Vacuum suction cup ESS-80-SF

Part number: 189321

FESTO



[PDF](#) General operating condition

Data sheet

| Feature | Value |
|---|--|
| Min. workpiece radius | 400 mm |
| Nominal width | 6 mm |
| Suction cup diameter | 80 mm |
| Suction cup volume | 19.312 cm ³ |
| Connection position | up |
| Mounting position | Any |
| Symbol | 00991485 |
| Classification of suction cup holder | Size 5 |
| Suction cup shape | Round, flat |
| Operating pressure | -0.095 MPa ... 0 MPa |
| Operating pressure | -0.95 bar ... 0 bar |
| Operating pressure | -13.775 psi ... 0 psi |
| Nominal operating pressure | -0.07 MPa |
| Nominal operating pressure | -0.7 bar |
| Nominal operating pressure | -10.15 psi |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7::-] |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-A1-L |
| For use in the food industry | See supplementary material information |
| Ambient temperature | -10 °C ... 200 °C |
| Holding force at nominal operating pressure | 309.7 N |
| Lateral force at nominal operating pressure | 139.5 N |
| Product weight | 133 g |
| Type of mounting | Via vacuum connection |
| Vacuum connection | M10 |
| Color | Gray |
| Shore hardness | 60 +/-5 |
| Material of screwed plug | POM Steel, nickel-plated Steel, galvanized and chrome-plated |
| Note on materials | RoHS compliant |

| Feature | Value |
|----------------------|-------|
| Suction cup material | FPM |