

# Vacuum generator VN-10-M-I3-PQ2-VQ2

Part number: 193554

FESTO



[PDF](#) General operating condition

## Data sheet

| Feature                                       | Value   |
|---|---|
| Nominal width of Laval nozzle                 | 0.95 mm                                       |
| Width dimension                               | 13 mm   |
| Mounting position                             | Any   |
| Ejector characteristics                       | High vacuum<br>Inline                         |
| Structural design                             | Straight design                               |
| Symbol  | 00991491                                      |
| Operating pressure for max. suction rate      | 5 bar   |
| Operating pressure                            | 1 bar ... 8 bar                               |
| Operating pressure for max. vacuum            | 5.8 bar                                       |
| Max. vacuum                                   | 86 %  |
| Nominal operating pressure                    | 6 bar   |
| Max. suction rate with respect to atmosphere  | 28 l/min                                      |
| Air supply time at nominal operating pressure | 0.96 s  |
| Operating medium                              | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media      | Operation with oil lubrication not possible   |
| Corrosion resistance class (CRC)              | 1 - Low corrosion stress                      |
| LABS (PWIS) conformity                        | VDMA24364-B1/B2-L                             |
| Temperature of medium                         | 0 °C ... 60 °C                                |
| Ambient temperature                           | 0 °C ... 60 °C                                |
| Product weight                                | 23 g  |
| Type of mounting                              | Line installation                             |
| Pneumatic connection 1                        | QS-6  |
| Pneumatic connection 3                        | Not ducted                                    |
| Vacuum connection                             | QS-6  |
| Note on materials                             | RoHS-compliant                                |
| Seals material                                | NBR   |
| Female nozzle material                        | POM   |
| Housing material                              | POM-reinforced                                |
| Material of jet nozzle                        | Wrought aluminum alloy                        |
| Material of pneumatic fitting                 | Brass<br>Nickel-plated                        |