

# Input/output module CPX-L-8DE-8DA-16-KL-3POL

Part number: 572607

FESTO



 General operating condition

## Data sheet

Feature	Value
Dimensions W x L x H	50 mm x 107 mm x 41 mm
Product weight	171 g
Ambient temperature	-5 °C ... 50 °C
Storage temperature	-20 °C ... 70 °C
Degree of protection	IP20
Corrosion resistance class (CRC)	(when installed)
LABS (PWIS) conformity	VDMA24364-B2-L
Certification	c UL - Recognized (OL)
Note on materials	RoHS-compliant
Housing material	PA-reinforced
LED indicators	1 group diagnostics 16 channel status
Diagnostics	Short circuit/overload per channel Undervoltage of outputs
No. of outputs	8
Parameterization	Input debounce time Fail-safe modes per channel Forcing per channel Idle mode per channel Signal extension time Response to short circuit Module monitoring
DC operating voltage range	18 V ... 30 V
Nominal operating voltage DC	24 V
Intrinsic current consumption at nominal operating voltage	Typ. 15 mA
No. of inputs	8
Input characteristics	IEC1131-T2, type 01
Switching level	Signal 0: $\leq 5$ V Signal 1: $\geq 15$ V
Input switching logic	PNP (positive switching)
Input debounce time	3 ms (0.1 ms, 10 ms, 20 ms parameterizable)
Max. residual current of inputs per module	1.8 A
Characteristic curve outputs	IEC1131-T2
Switching logic at outputs	PNP (positive switching)
Max. residual current of outputs per module	2 A
Max. power supply per channel	0.25 A (6 W lamp load)
Electrical isolation between channels	no
Electrical isolation between channel and internal bus	no

Feature	Value
Fuse protection (short circuit)	Internal electronic fuse per channel