

Manifold rail VABM-L1-18S-G38-10

Part number: 574463

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|---|--|
| Width dimension | 19 mm |
| Max. no. of valve positions | 16 |
| Operating pressure | -0.09 MPa ... 1 MPa |
| Operating pressure | -0.9 bar ... 10 bar |
| Certification | RCM compliance mark c UL us - recognized (OL) |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Suitability for the production of Li-ion batteries | Suitable for battery production with reduced Cu/Zn/Ni values (F1a) |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 5 according to ISO 14644-1 |
| Max. tightening torque for DIN rail mounting | 1.5 Nm |
| Max. tightening torque for valve mounting | 1.18 Nm |
| Max. tightening torque for wall mounting | 3 Nm |
| Product weight | 794 g |
| Pneumatic connection 1 | G3/8 |
| Pneumatic connection 3 | G3/8 |
| Pneumatic connection 5 | G3/8 |
| Note on materials | RoHS compliant |
| Manifold rail material | Wrought aluminum alloy |