

Mini slide DGST-6-30-PA

Part number: 8085107

FESTO



[PDF](#) [General operating condition](#)

Data sheet

| Feature | Value |
|---|--|
| Stroke | 30 mm |
| Adjustable end-position range/front length | 13.1 mm |
| Adjustable end-position range/rear length | 11.6 mm |
| Piston diameter | 6 mm |
| Drive unit operating mode | Yoke |
| Cushioning | Elastic cushioning rings/pads at both ends |
| Mounting position | Any |
| Guide | Recirculating ball bearing |
| Structural design | Yoke Piston rod Slide |
| Position sensing | Via proximity switch |
| Symbol | 00991249 |
| Operating pressure | 0.15 MPa ... 0.8 MPa |
| Operating pressure | 1.5 bar ... 8 bar |
| Operating pressure | 21.75 psi ... 116 psi |
| Max. speed | 0.5 m/s |
| Repetition accuracy | ≤ 0.3 mm |
| Mode of operation | Double-acting |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 6 according to ISO 14644-1 |
| Ambient temperature | -10 °C ... 60 °C |
| Impact energy in the end positions | 0.018 J |
| Cushioning length | 0.9 mm |
| Max. force F _y | 240 N |
| Max. force F _z | 240 N |
| Max. torque M _x | 1.1 Nm |
| Max. torque M _y | 1.2 Nm |
| Max. torque M _z | 1.2 Nm |
| Theoretical force at 6 bar, retracting | 25 N |
| Theoretical force at 6 bar, advancing | 34 N |

| Feature | Value |
|----------------------|----------------------------------|
| Moving mass | 70 g |
| Product weight | 134 g |
| Type of mounting | With through-hole |
| Pneumatic connection | M3 |
| Note on materials | RoHS compliant |
| Cover material | Wrought aluminum alloy |
| Seals material | HNBR |
| Guide material | POM TPE-E High-alloy steel |
| Housing material | Wrought aluminum alloy |
| Piston rod material | high-alloy stainless steel |