

PROFIBUS interface CPX-AP-I-PB-M12

Part number: 8086608

FESTO



 General operating condition

Data sheet

Feature	Value
Dimensions W x L x H	45 mm x 170 mm x 35 mm
Type of mounting	On H-rail with accessories With through-hole
Max. number of modules	56
Product weight	186 g
Ambient temperature	-20 °C ... 60 °C
Storage temperature	-40 °C ... 70 °C
Relative air humidity	5 - 95% Non-condensating
Degree of protection	IP65 IP67
Note on degree of protection	Unused connections sealed
Corrosion resistance class (CRC)	1 - Low corrosion stress
Max. cable length	50 m system communication
LABS (PWIS) conformity	VDMA24364-B2-L
Cleanroom suitability, measured according to ISO 14644-14	Statically installed element, no meaningful evaluation possible according to ISO 14644-1
CE marking (see declaration of conformity)	As per EU EMC directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC
KC characters	KC-EMV
Certification	RCM compliance mark c UL us - Listed (OL)
Certificate issuing authority	UL E239998
Note on materials	RoHS compliant
Housing material	PC Die-cast zinc, nickel-plated
O-ring material	FPM
Diagnostics via LED	Diagnostics per module Power supply for electronics/sensors Load power supply System diagnostics Maintenance required
Diagnostics via bus	APDD invalid Load switch-off Communication with AP module interrupted Electronics/sensors overvoltage Overvoltage load Electronics/sensors undervoltage Undervoltage load
Note on fieldbus interface	Terminating resistor on socket possible

Feature	Value
Fieldbus interface, type	PROFIBUS
Fieldbus interface, protocol	PROFIBUS DP-V1
Fieldbus interface, function	Incoming bus connection
Fieldbus interface, connection type	Plug
Fieldbus interface, connection technology	M12x1, B-coded as per EN 61076-2-101
Fieldbus interface, number of poles/wires	5
Fieldbus interface, galvanic isolation	Yes
Fieldbus interface, transmission rate	1.5 Mbps 12 Mbit/s 187.5 kbps 19.2 kbps 3 Mbit/s 500 kbps 6 Mbit/s 9.6 kbps 93.75 kbps
Fieldbus interface 2, type	PROFIBUS
Fieldbus interface 2, protocol	PROFIBUS DP-V1
Fieldbus interface 2, function	Forwarding bus connection
Fieldbus interface 2, connection type	Socket
Fieldbus interface 2, connection technology	M12x1, B-coded as per EN 61076-2-101
Fieldbus interface 2, number of poles/wires	5
Fieldbus interface 2, galvanic isolation	Yes
Fieldbus interface 2, transmission rate	1.5 Mbps 12 Mbit/s 187.5 kbps 19.2 kbps 3 Mbit/s 500 kbps 6 Mbit/s 9.6 kbps 93.75 kbps
Max. address capacity inputs	244 byte
Max. address capacity outputs	244 byte
Configuration support	GSD file
Communication interface, function	System communication XF20 OUT / XF21 OUT
Communication interface, connection type	2x port
Communication interface, connection technology	M8x1, D-coded as per EN 61076-2-114
Communication interface, number of pins/wires	4
Communication interface, protocol	AP
Communication interface, shielding	Yes
Power supply, function	Incoming electronics/sensors and load
Power supply, type of connection	Plug
Power supply, connection technology	M8x1, A-coded as per EN 61076-2-104
Power supply, number of pins/wires	4
Voltage forwarding, function	Outgoing electronics/sensors and load
Voltage forwarding, connection type	Socket
Voltage forwarding, connection technology	M8x1, A-coded as per EN 61076-2-104
Voltage forwarding, number of pins/wires	4
Note regarding operating voltage	SELV/PELV fixed power supplies required Note voltage drop
Nominal operating voltage DC load	24 V
Permissible voltage fluctuations load	±25%
Nominal operating voltage DC for electronics/sensors	24 V
Permissible voltage fluctuations for electronics/sensors	±25%
Max. power supply	2 x 4 A (external fuse required)
Intrinsic current consumption at nominal operating voltage for electronics/sensors	Typically 80 mA

Feature	Value
Intrinsic current consumption at nominal operating voltage load	Typically 5 mA
Power failure buffering	10 ms
Reverse polarity protection	Yes