

# EtherNet/IP interface CPX-AP-A-EP-M12

Part number: 8129244

FESTO



 General operating condition

## Data sheet

Feature	Value
Dimensions W x L x H	50.1 mm x 107.3 mm x 57.5 mm
Width dimension	50.1 mm
Type of mounting	Screwed tightly
Max. number of modules	80
Product weight	113 g
Mounting position	Any
Ambient temperature	-20 °C ... 50 °C
Note on ambient temperature	Observe ambient temperature derating according to IEC 61131-2:2017
Storage temperature	-20 °C ... 70 °C
Relative air humidity	5 - 95 % Non-condensing
Nominal altitude of use above sea level	≤ 2000 m ASL (≥ 79.5 kPa)
Max. installation height	3500 m
Information on max. installation height	Observe ambient temperature derating according to IEC 61131-2:2017
Corrosion resistance class (CRC)	1 - Low corrosion stress
Vibration resistance	Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6
Note on vibration resistance	SG1 on H-rail SG2 on direct mounting Transport application test with severity level 1 as per FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27
Note on shock resistance	30 g/11 ms as per EN 60068-2-27 SG1 on H-rail SG2 on direct mounting Shock test with severity level 1 as per FN 942017-5 and EN 60068-2-27
Protection class	III
Contamination level	2
Overvoltage category	II
Max. cable length	100 m Ethernet/IP
LABS (PWIS) conformity	VDMA24364-B2-L
Material fire test	UL94 V-0 (housing)
Note on materials	RoHS-compliant Halogen-free Free of phosphoric acid ester
Cover material	PBT-reinforced
Inspection window material	PC
Material of screws	Steel, nickel-plated

Feature	Value
Threaded sleeve material	High-alloy stainless steel
O-ring material	FPM
Diagnostics via LED	Diagnostics per module Ethernet/IP communication Power supply for electronics/sensors Load power supply System diagnostics Maintenance required
Diagnostics via bus	APDD invalid Load switch-off Communication error Electronics/sensors overvoltage Load overvoltage Electronics/sensors undervoltage Load undervoltage
Fieldbus interface, type	Ethernet
Fieldbus interface, protocol	ACD (Address Conflict Detection) DLR (Device Level Ring) EtherNet/IP EtherNet/IP QoS EtherNet/IP Quickconnect Modbus/TCP (Modbus/UDP) SNMP
Fieldbus interface, function	Bus connection, incoming/forwarding
Fieldbus interface, connection type	2x socket
Fieldbus interface, connection technology	M12x1, D-coded as per EN 61076-2-101
Fieldbus interface, connection pattern	00995716
Fieldbus interface, number of poles/wires	4
Fieldbus interface, galvanic isolation	yes
Fieldbus interface, transmission rate	100 Mbit/s
Fieldbus interface, note on transmission rate	100 Mbit, switched fast Ethernet
Max. address capacity inputs	4096 byte
Information on inputs	EP: 488 bytes Modbus: 4096 bytes
Max. address capacity outputs	4096 byte
Note on outputs	EP: 496 bytes Modbus: 4096 bytes
Module parameters	Configuration of voltage monitoring, load supply PL
Internal cycle time	< 1 ms
Configuration support	EDS file
Communication interface, function	System communication XF20 OUT
Communication interface, connection type	Socket
Communication interface, connection technology	M8x1, D-coded as per EN 61076-2-114
Communication interface, number of pins/wires	4
Communication interface, connection pattern	00995937
Communication interface, protocol	AP
Communication interface, shielding	yes
Note regarding operating voltage	SELV/PELV fixed power supplies required Note voltage drop
Note on nominal operating voltage DC	Protected Extra-Low-Voltage as per IEC 60204-1
Nominal operating voltage DC load	24 V
Permissible voltage fluctuations load	± 25 %
Nominal operating voltage DC for electronics/sensors	24 V
Permissible voltage fluctuations for electronics/sensors	± 25 %
Intrinsic current consumption at nominal operating voltage for electronics/sensors	Typically 95 mA
Intrinsic current consumption at nominal operating voltage load	Typically 3 mA
Power failure buffering	10 ms

Feature	Value
Potential separation between the supply voltages electronics/sensor technology and load/valves	yes
Reverse polarity protection	yes