


Air solenoid valve CPV10-M1H-5LS-M7

Part number: 161414



[PDF General operating condition](#)

Datasheet product reliability

The information in this "Product reliability data sheet" is based on products being used as intended. This includes complying with all specifications in data sheets, catalogues, user documentation and the general operating conditions. The user alone is responsible for determining whether a product is suitable for a particular application.

| Feature | Value |
|---|--|
| Service-life value B_{10} ¹⁾ | 20 Mio cycles |
| Fault exclusion | Bursting of the valve housing: externally directed failure of the material structure with a sudden release of the medium and associated pressure drop (according to ISO 5598, 3.2.85). |
| Well-tried component ²⁾ | Yes |
| Design characteristics | Pneumatic spring return Pneumatic spring return Supply air via duct 14 |
| Lap | Overlap |
| Max. positive test pulse with 0 signal | 1400 μ s |
| Max. negative test pulse with 1 signal | 700 μ s |

- 1) The ascertainment of characteristic service life values is based on the ISO 19973 "Pneumatic fluid power - Assessment of component reliability by testing".
- 2) The product is a well-tried product for a safety-related application according to ISO 13849-1. The relevant basic and well- tried safety principles according ISO 13849-2 for this product are fulfilled. The suitability of the product for a precise application must be verified by the user.