

Angle seat valve VZX-A-B-TS6-13-M2-V13T-30-K-46-17-V4

Part number: 8060527



[PDF General operating condition](#)

Datasheet product reliability

The information in this "Product reliability data sheet" is based on products being used as intended. This includes complying with all specifications in data sheets, catalogues, user documentation and the general operating conditions. The user alone is responsible for determining whether a product is suitable for a particular application.

Feature	Value
Safety Integrity Level (SIL) ¹⁾	Safety Integrity Level 2
Certified for safety function to ISO 13849 and IEC 61508 (SIL) ²⁾	Up to Safety Integrity Level 2 low demand mode Up to Safety Integrity Level 1 high demand mode
Certificate issuing authority	TÜV 968/V 1039.01/20
Probability of Failure per Hour (PFH) ³⁾	$1.36 \cdot 10^{-7}$
Probability of Failure on Demand (PFD) ⁴⁾	$5.95 \cdot 10^{-4}$
Mean time to dangerous failure (MTTF _d) ⁵⁾	841 years

- 1) Further measures can be necessary to fulfil the stated Safety Integrity Level (SIL). For these measures refer to the relevant documentation.
- 2) Further measures can be necessary to fulfil the stated Safety Integrity Level (SIL). For these measures refer to the relevant documentation.
- 3) For components affected by wear this value will be reached, if for the precise application the mean number of annual operations (nop) is equal or lower than the assumed annual operations of this product. The assumed mean number of annual operations is stated in this datasheet.
- 4) For components affected by wear this value will be reached, if for the precise application the mean number of annual operations (nop) is equal or lower than the assumed annual operations of this product. The assumed mean number of annual operations is stated in this datasheet.
- 5) The ascertainment of the MTTF_d value is based on the IEC 61709 "Electric components - Reliability - Reference conditions for failure rates and stress models for conversion" respectively on the SN 29500.